






SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1958	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	STICK IT	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Aerosol Heavy-Duty Adhesive Spray	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable aerosols: Category 1 Skin corrosion/irritation: Category 2 Serious eye damage/eye irritation: Category 2A Reproductive toxicity (fertility): Category 2 Specific target organ toxicity, single exposure: Category 3 narcotic effects Specific target organ toxicity, repeated exposure: Category 2 Environmental hazards: Not classified. OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:			
--	--------------------------------------	----------------	---	---	---

HAZARD STATEMENTS:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Immediately call a poison center/doctor. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Not available.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Acetone	67-64-4	20-40
Propane	74-98-6	20-40
Dimethyl Ether	115-10-6	10-20
n-Hexane	110-54-3	10-20
2-Methylpentane	107-83-5	2.5-10
3-Methylpentane	96-14-0	1-2.5
Other components below reportable levels		10-20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause

redness and pain. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Alcohol resistant foam. Dry powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion, do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

MATERIALS AND METHODS FOR CLEANUP:

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see Section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)


COMPONENTS	TYPE	VALUE
Dimethyl Ether (CAS 115-10-6)	STEL	2 ppm
	TWA	0.75 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³
		1000 ppm
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m ³
		500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³
		1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
3-Methylpentane (CAS 96-14-2)	STEL	1000 ppm
	TWA	500 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Dimethyl Ether (CAS 115-10-6)	Ceiling	0.3 ppm

n-Hexane (CAS 110-54-3)	TWA	50 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards COMPONENTS				
Acetone (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm		
Dimethyl Ether (CAS 115-10-6)	Ceiling TWA	0.1 ppm 0.016 ppm		
n-Hexane (CAS 110-54-3)	TWA	180 mg/m ³ 50 ppm		
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm		
US. Workplace Environmental Exposure Level (WEEL) Guides COMPONENTS				
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m ³ 1000 ppm		
BIOLOGICAL LIMIT VALUE:				
ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	urine	*
* - For sampling details, please see the source document.				
EXPOSURE GUIDELINES:				
US - California OELs: Skin designation:				
n-Hexane (CAS 110-54-3) Can be absorbed through the skin.				
US ACGIH Threshold Limit Values: Skin designation:				
n-Hexane (CAS 110-54-3) Can be absorbed through the skin.				
APPROPRIATE ENGINEERING CONTROLS:				
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.				
INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:				
				
Eye Protection: Wear safety glasses with side shields (or goggles).				
Skin Protection: Hand Protection: Wear appropriate chemical resistant gloves. Skin Protection: Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.				
Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.				
Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.				
General Hygiene Considerations: When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				

9. Physical & Chemical Properties			
Physical State:	Gas.	Flammability (solid/gas):	Not available.
Form:	Aerosol.	Flammability Limit-lower (%):	2.2% estimated.
Color:	Not available.	Flammability Limit-upper (%):	8.6% estimated.
Odor:	Not available.	Explosive Limit - lower (%):	Not available.
Odor Threshold:	Not available.	Explosive Limit - upper (%):	Not available.
pH:	Not available.	Vapor Pressure:	62 psig @70F estimated.
Melting/Freezing Point:	Not available.	Vapor Density:	Not available.
Initial Boiling Point/Range:	122.35 °F (50.2 °C) estimated.	Relative Density:	Not available.
Partition Coeff (n-octanol/water):	Not available.	Solubility (water):	Not available.
Viscosity:	Not available.	Auto-Ignition Temperature:	682.34 °F (361.3 °C) estimated.
Specific Gravity:	0.724 estimated.	Decomposition Temperature:	Not available.
Flash Point:	-156.0 °F (-104.4 °C) Propellant estimated.	Evaporation Rate:	Not available.

10. Stability & Reactivity Information	
REACTIVITY:	
The product is stable and non-reactive under normal conditions of use, storage and transport.	
CHEMICAL STABILITY:	
Material is stable under normal conditions.	
POSSIBILITY OF HAZARDOUS REACTIONS:	
Hazardous polymerization does not occur.	
INCOMPATIBLE MATERIALS:	
Strong oxidizing agents.	
CONDITIONS TO AVOID:	
Avoid temperatures exceeding the flash point. Contact with incompatible materials.	

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information**PRIMARY ROUTE OF ENTRY:****Eyes:** Causes serious eye irritation.**Skin:** Causes skin irritation.**Inhalation:** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.**Ingestion:** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.**SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:**

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

ACUTE TOXICITY:

May be fatal if swallowed and enters airways. Narcotic effects.

COMPONENTS	SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
	Rabbit	> 9.4 ml/kg, 24 Hours
		> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Dimethyl Ether (CAS 115-10-6)		
Acute		
<i>Inhalation</i>		
NOEL	Rat	2 ppm, 6 Hours
<i>Oral</i>		
LD50	Rat	460 mg/kg
n-Hexane (CAS 110-54-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
		> 5 ml/kg, 4 Hours
<i>Inhalation</i>		
LC50	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
<i>Oral</i>		
LD50	Rat	1355 mg/l
		658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Causes skin irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not available.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.**REPRODUCTIVE TOXICITY:**

Suspected of damaging fertility.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Respiratory system. Skin. Eyes. Central nervous system. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.

ASPIRATION HAZARD:

May be fatal if swallowed and enters airways.

CHRONIC EFFECTS:

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological Information**ECOTOXICITY:**

Toxic to aquatic life with long lasting effects.

PRODUCT	SPECIES		TEST RESULTS
Stick It			
Aquatic			
Crustacea	EC50	Daphnia	105.183 mg/l, 48 hours estimated
Fish	LC50	Fish	17.8322 mg/l, 96 hours estimated
COMPONENTS	SPECIES		TEST RESULTS
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Dimethyl Ether (CAS 115-10-6)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	4.3 - 7.8 mg/l, 48 hours
Fish	LC50	Striped bass (Morone saxatilis)	10.302 - 16.743 mg/l, 96 hours
n-Hexane (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

No data available.

Partition coefficient n-octanol / water (log Kow):

2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Dimethyl Ether	0.1
n-Hexane	3.9
Propane	2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference: Acetone (CAS 67-64-1) U002

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse empty containers.

14. Transportation Information

DOT: UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es)
 Class: 2.1
Subsidiary Risk: -
Label(s): 2.1
Packing Group: Not applicable.



Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Special Provisions: N82

Packaging Exceptions: 306

Packaging Nonbulk: None.

Packaging Bulk: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN Number:** UN1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1



Packing Group: Not applicable.

Environmental Hazards: Yes.

ERG Code: 10L

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Other Information:

Passenger and Cargo Aircraft: Allowed.

Cargo Aircraft Only: Allowed.

Packaging Exceptions: LTD QTY

IMDG: **UN NUMBER:** UN1950

UN Proper Shipping Name: AEROSOLS

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1



Packing Group: Not applicable.

Environmental Hazards:

Marine pollutant: Yes.

EmS: F-D, S-U

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:

Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Acetone (CAS 67-64-1) Listed.

n-Hexane (CAS 110-54-3) Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories: Immediate Hazard – Yes.

Delayed Hazard – Yes.

Fire Hazard – Yes.

Pressure Hazard – Yes.

Reactivity Hazard – No.

SARA 302 Extremely hazardous substance

Chemical Name	CAS #	Reportable Quantity	Threshold Planning Quantity	Threshold Planning Quantity, Lower Value	Threshold Planning Quantity, Upper Value
---------------	-------	---------------------	-----------------------------	--	--

Phenol	108-95-2	1000		500 lbs	10000 lbs
--------	----------	------	--	---------	-----------

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting)

Chemical Name	CAS #	% by Weight
n-Hexane	110-54-3	10-20
Ethyl Benzene	100-41-4	0.01-0.1
Styrene	100-42-5	0.01-0.1

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Dimethyl Ether (CAS 115-10-6)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number: Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)):

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number:

Acetone (CAS 67-64-1) 6532

US STATE REGULATIONS**US. Massachusetts RTK - Substance List:**

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act:

2-Methylpentane (CAS 107-83-5)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law:

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Rhode Island RTK:

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information**DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.