

T-LUBE #1760

Aerosol Penetrating Clean Gel Lubricant with PTFE



Features:

- Safe on most plastics
- Provides a moisture resistant film
- High tack
- Clear stringing gel
- Food Processing Acceptability: H2
- Resists water washout
- Penetrates as an oil, sets to a tacky, grease-like gel
- Protects against rust and corrosion



Description:

T-LUBE is a high tack lubricating gel that provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Contains a fine PTFE and gel lubricant mixture which helps provide superior wear and lubrication deep inside working parts. Resists water washout and weathering. Prevents rust and corrosion and covers parts with a moisture-resistant barrier. This product is suitable for use as a lubricant where there is no possibility of food contact in food processing and food handling establishments. For use by machine shops, HVAC and plumbing operations, automotive, manufacturing, food processing plants.

Applications:

- Chains
- Gears
- Hinges
- Sprockets
- Pistons
- Cable
- Slides
- Wire Rope
- Valves
- Cams
- Sleeves
- Shafts
- Rings
- Seals
- Bushings

Product Characteristics:

Physical State:	Liquid
Form:	Spray aerosol
Odor:	No data available
Initial Boiling Point/Range:	No data available
Vapor Pressure:	No data available
Solubility (water):	No data available
Density:	No data available
Relative Density:	No data available
pH:	No data available
Flash Point:	Estimated -17°C
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable
Class:	2.1
Packing Group:	II

Directions:

SHAKE WELL BEFORE USING. Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12 to 14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.

Caution: Do not use near heat, sparks or open flame.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

Yes.