

TOOL KOOL #1745

Clinging Coolant and Lubricant for Machining Operations



Features:

- Lubricates and cools
- Clinging Formula
- Protects finished pieces from rust and corrosion
- Foaming spray
- Increases production
- Withstands extreme pressure
- Extends tool life



Description:

TOOL KOOL is a heavy-duty cutting lubricant that is formulated for all types of machine shop uses. It contains a special synthetic blend of lubricants and thickening agents making it ideal for difficult machining, tapping and thread cutting operations that involve high carbon steel, alloy steel, stainless steel, as well as free machining soft steel. Its unique formula clings to the cutting bit to provide excellent lubrication and rapid heat removal, to extend valuable tool life and ensure a superior finish. TOOL KOOL is made especially to withstand extreme pressure and keep operating temperatures low.

Applications:

- Milling
- Tapping
- Boring
- Thread Cutting
- Cutting
- Sawing
- Grinding Wheels
- Machine Tools

Product Characteristics:

Appearance:	Clear spray/mist
Color:	Colorless
Odor:	Solvent.
Boiling Point:	Not available
Vapor Pressure:	Not available
Water Solubility:	Insoluble
Relative Density:	0.8
Flash Point:	< 50°F (liquid portion)
VOC Content (Wt. %):	31
pH:	Not applicable
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable
Class:	2.1
Packing Group:	-

Directions:

SHAKE WELL BEFORE USING. Hold nozzle 6 to 8 inches from surface requiring lubrication. Generously spray onto cutting surface or tool. Reapply as necessary to maintain lubrication level.

Note: Not recommended for use on copper or aluminum.

Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

Not available.