

TRUEX #1761

Aerosol Open Gear & Cable Lubricant



Features:

- Protects even under water
- Prolongs gear and equipment life
- Becomes tacky quickly & stays tacky
- Will not build up between gear teeth
- Effective in temperatures from 0°F to 200°F
- Will not drip, melt, sling off or dry out
- Non-chlorinated, non-toxic and non-corrosive
- Recoats and reapplies with each revolution



Description:

TRUEX is a super tough adhesive lubricant which penetrates deep into gears, cables and heavy-duty mechanisms. Thickens quickly to a tacky, black stringy adhesive lubricant. It is fortified with Molybdenum Disulfide, providing a shield that maintains a cushion of lubricant between gear teeth and other friction-producing surfaces. Absorbs high shock loads, extreme pressure and prevents chipping and scuffing. It forms a protective, water-resistant coating that prevents corrosion in outdoor, and even underwater, applications. This product features a single action valve that produces a pinpoint spray for easy penetration in hard to reach areas.

Applications:

- Construction Equipment
- Earth Moving Equipment
- Marine Equipment
- Textile and Steel Mill Machinery
- Winches and Cranes
- Offshore Drilling Rigs
- Mining Equipment
- Dredging Equipment
- Drag Lines
- Tug Boats
- Concrete Trucks
- Elevators

Product Characteristics:

Appearance:	Black, aerosol
Odor:	Solvent
Boiling Point/Range:	55.37°F (12.99°C) estimated
Vapor Pressure:	65 psig @70°F estimated
Specific Gravity:	0.636 estimated
Solubility(water):	Not available
Relative Density:	Not available
Flash Point:	-156.0°F (-104.4°C) Propellant estimated
Evaporation Rate:	Not available
pH:	Not available
Relative Density	Not available
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
UN Number:	UN1950
Class:	2.1
Packing Group:	Not applicable

Directions:

SHAKE WELL. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application.

Caution: do not use near heat, sparks or open flame.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

Yes.