

TRUEX EXTRA #1729

Aerosol Open Gear Lubricant



Features:

- Increases life of all gear, chains, cables and wire ropes
- High viscosity allows it to stick without running
- Forms film that resists rust and corrosion
- Tacky adhesive continuously recoats and lubricates all gears
- Effective at high temperature



Description:

This extra-heavy viscosity lubricant penetrates deep into gears, cables and heavy mechanisms, imparting a very tacky, black adhesive lubricant. Prevents corrosion and resists oxidation by repelling moisture. Can be used in extreme weather conditions and underwater. Product is fortified with Molybdenum Disulfide to provide a cushion of lubricant between gear teeth and other surfaces. It is perfect for 5th wheels due to its wear-resistance and adhesion. Reduces down time and noise due to metal-to-metal contact.

Applications:

- Drag Lines
- Textile Machinery
- Open Gears
- Offshore Drilling Equipment
- Elevator Cables
- Sprockets
- Concrete Trucks
- Earth Movers
- Construction Equipment
- Slow Moving Chains

Product Characteristics:

Appearance:	Dark spray/mist
Physical State:	Liquid
Color:	Dark brown
Odor:	Solvent/cherry
Boiling Point:	Not available
Vapor Pressure:	Not available
Water Solubility:	Insoluble
Relative Density:	0.9
Flash Point:	< 0°F (liquid portion)
VOC Content (Wt. %):	50
pH:	Not applicable
Relative Density:	0.9
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable
Class:	2.1
Packing Group:	--

Directions:

Shake well before using. Remove protective cap. Hold 6-8 inches from surface and apply an even coat. Turn on machinery and allow lubricant to spread over working surfaces. Apply a second thinner coating to ensure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying turn upside down and spray until nozzle is clear.

Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

Not available.