

TACKY #1284

Aerosol Belt Dressing



Features:

- Improves fan and drive belts worn by age, heat and friction and lengthens belt life
- Removes grease and dirt from surface to increase traction
- Penetrates deeply to keep surfaces soft and pliable
- Up/down valve allows application inward to reach places
- Increases equipment slippage
- Reduces belt slippage
- Nonstaining
- Food Processing Acceptability: P1



Description:

Prevent belt slippage and keep equipment running at top performance with this handy aerosol spray. TACKY is formulated with several liquid resins that provide the necessary adhesion belts need to firmly grip sheaves and pulleys. While it is extremely tacky, it will not glaze and can be used on a variety of materials, including rubber, leather, fabric and synthetics. Resists water wash-off and performs effectively under wet conditions.

Applications:

- "V" Belts
- Leather
- Synthetic Belts
- Flat Beds
- Rubber
- Generators
- Round Belts
- Fabric
- Conveyors

Product Characteristics:

Physical State:	Gas
Form:	Aerosol
Odor:	Not available
Explosive Properties:	Not explosive
Oxidizing Properties:	Not oxidizing
Initial Boiling Point/Range:	194°F (90°C) estimated
Flash Point:	-156.0°F (-104.4°C) Propellant estimated
Solubility (water):	Not available
Vapor Pressure:	45-55 psig @70°F estimated
Flammability (solid/gas):	Not available
Auto-Ignition Temperature:	779.98°F (415.55°C) estimated
Specific Gravity:	0.826 estimated
Flammability Limit (lower)%:	6.7% estimated
Flammability Limit (upper)%:	43.8% estimated
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity).
Class:	2.1
Packing Group:	Not applicable
Subsidiary Risk:	6.1 (PGIII)
Labels:	2.1,6.1

Directions:

NOTE: In many instances protective guards must be removed in order to apply belt dressing properly. In such cases, please use extreme care to prevent accidents. Be sure to replace guards after treatment.

Apply a little at a time to inner surface of belt while machinery is in motion. Spray using a back and forth motion until the surface is completely wet. On most belts, the spray may be applied to the sheaves, pulleys, or directly onto the belt itself. Repeat occasionally to maintain full power and optimize belt life.

Pictograms:



Signal Word:

Danger.

Personal Protective Equipment Required:



DOT Placard:

