

TRUE BOND PATCH #2462

Ready-To-Use Asphalt Patching Compound



Features:

- Will not harden until compressed
- Long lasting – unaffected by freezing temperatures
- Matches original blacktop surfaces
- Can be used on wet or dry surface
- Easy to apply- no mixing required
- Smaller aggregate allows better fill
- Will not track
- Area can be immediately opened to traffic
- Shelf life of up to 2 years



Description:

TRUE BOND PATCH is a ready-mix compound of finely graded mineral aggregate and specially prepared asphalt and additives for repairing holes in asphalt or concrete surface. It sticks to asphalt and concrete without a primer, even in cold, wet weather.

Applications:

- Parking Lots
- Driveways
- Streets

Product Characteristics:

Appearance:	Viscous
Odor:	Solvent (mineral spirits)
Vapor Pressure:	No information available
Specific Gravity:	No information available
Solubility:	Insoluble.
Flash Point:	>93°C/>200°F
VOC:	No information available
Storage:	Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition. Store locked up.
Transport Information:	
Proper Shipping Name:	Not regulated
UN Number:	Not regulated
Class:	Not regulated

DOT Placard:

Not regulated.

Directions:

The surface should be clean of grease, oil and dirt. If extremely dusty, hose the surface down with water. The surface need not be dry before applying. Take care to keep vertical edges of hole as clean as possible to allow for best adhesion. Material works best over a solid base; do not use over mud or clay. Remove material from the drum just as it is and place it where needed by shoveling or pouring it in. Level material slightly higher than desired depth to allow for compaction. Pack it down with a hand tamper or roller. If the void is deeper than 1 inch, tamp material down in successive layers of 1 inch to assure maximum compression. No drying or curing time is required. Area can be immediately opened to traffic.

Coverage rate is approximately 7 square feet at 1 inch deep.

Pictograms:



Signal Word:

WARNING.

Personal Protective Equipment Required:

