

WHITE LUBE #1723

Aerosol White Lithium Grease



Features:

- Drop point to 350°F
- Penetrates into gears as a liquid then sets up to a thick grease
- Contains no chlorinated solvents
- Food Processing Acceptability: H2
- No hexane or CFC's
- White lubricant is nonstaining
- Withstands extreme temperatures (up to 350°F)
- High resistance to rusting and corrosion will not wash away, run off or dry out



Description:

WHITE LUBE sprays as a deep penetrating oil that flows and creeps into areas which are difficult to lubricate. Then, as the solvent carrier evaporates, the liquid forms into thick water-resistant grease that is also resistant to high temperatures. After setting up, the grease will not wash away with water while providing non-staining lubrication which guards surfaces against rust and corrosion. It is an excellent product for industrial and automotive uses.

Applications:

- Hoists
- Cams
- Conveyors
- Linkages
- Dryers
- Pumps
- Threads
- Side Bearings
- Chain Drivers
- Wire Rope
- Gears & Hinges
- Winches
- Rollers
- O-Rings
- Fittings
- Ovens
- Valves
- Manifold Heat Valves
- Regulators
- Striker Plates
- Springs
- Chains & Locks
- Couplings
- Slides

Product Characteristics:

Physical State:	Liquid
Odor:	Solvent
Boiling Point/ Range:	209.3°F (98.5°C) estimated
Specific Gravity:	0.511 estimated
Flammability(solid/gas):	Not applicable
Flash Point:	-156.0°F (-104.4°C) Propellant estimated
Heat of Combustion (NFPA 30B):	36.76 kJ/g estimated
Flammability Limit-lower (%):	0.7% estimated
Flammability Limit-upper (%):	8% estimated
Explosive Properties:	Not explosive
Oxidizing Properties:	Not oxidizing
Auto-Ignition Temperature:	421°F (216.11°C) estimated
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
Label(s):	2.1
Class:	2.1
Packing Group:	Not applicable

Directions:

Shake well before using. Attach snorkel tube and spray lightly. A highly concentrated all-purpose, white grease lubricant that leaves a long-lasting film.

Shelf life of 1+ year(s).

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

