SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER: 1723

PRODUCT NAME: WHITE LUBE

PRODUCT DESCRIPTION: Aerosol White Lithium Grease

COMPANY INFORMATION: **PRO CHEM, INC.**
1475 Bluegrass Lakes Parkway
Alpharetta, GA 30004

COMPANY PHONE: 1-800-241-8180

EMERGENCY TELEPHONE: 1-800-241-8180

INFOTRAC: 1-800-535-5053

2. Hazards Identification

GHS CLASSIFICATION:
Flammable aerosols: Category 1
Aspiration hazard: Category 1
Environmental Hazards: Hazardous to the aquatic environment, acute hazard: Category 2
Hazardous to the aquatic environment, long-term hazard: Category 2

SIGNAL WORD:
DANGER

SYMBOL:

OSHA DEFINED HAZARDS: Not classified.

HAZARD STATEMENTS:

Extremely flammable aerosol. May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. IF EXPOSED OR CONCERNED: Get medical advice/attention

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Distillates (Petroleum), Hydrotreated Light	64742-47-8	20 - 40
Propane	74-98-6	10 - 20
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	2.5 - 10
n-Heptane	142-82-5	2.5 - 10
Titanium dioxide	13463-67-7	1 - 2.5
Zinc Oxide	1314-13-2	1 - 2.5
Other components below reportable levels		40 - 60

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION: If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

INGESTION: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Aspiration may cause pulmonary edema and pneumonitis.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO_2).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

FIRE FIGHTING EQUIPMENT/INSTRCUTIONS:

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure buildup. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA. Structural firefighter's protective clothing will only provide limited protection.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during cleanup. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEANUP METHODS:

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS.
Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind or expose containers to heat, flame, sparks or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 3 Aerosol.
Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (See Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR1910.1000)

COMPONENTS	TYPE	VALUE	FORM
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m³ 500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m³ 1000 ppm	
Titanium dioxide (CAS13463-67-7)	PEL	15 mg/m³	Total dust.
Zinc Oxide (CAS 1314-13-2)	PEL	5 mg/m³ 5 mg/m³ 15 mg/m³	Fume. Respirable fraction. Total dust.

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE	
n-Heptane (CAS 142-82-5)	STEL TWA	500 ppm 400 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m³	
Zinc Oxide (CAS 1314-13-2)	STEL TWA	10 mg/m³ 2 mg/m³	Respirable fraction. Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE	
n-Heptane (CAS 142-82-5)	Ceiling TWA	1800 mg/m³ 440 ppm 350 mg/m³ 85 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m³ 1000 ppm	
Zinc Oxide (CAS 1314-13-2)	Ceiling STEL TWA	15 mg/m³ 10 mg/m³ 5 mg/m³ 5 mg/m³	Dust. Fume. Fume. Dust.

BIOLOGICAL LIMIT VALUE:

No biological exposure limits noted for the ingredient(s).

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

Face/Eye Protection: Face shield is recommended. Wear safety glasses with side shields (or goggles).
Skin Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Other: Wear suitable protective clothing.
Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.
Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.
General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Physical State:	Liquid.	**Flammability (solid/gas):**	Not available.
Form:	Aerosol.	**Flammability Limit–lower (%):**	0.7% estimated.
Color:	Not available.	**Flammability Limit–upper (%):**	8% estimated.
Odor:	Not available.	**Explosive Properties:**	Not explosive.
Odor Threshold:	Not available.	**Explosive Limit – lower (%):**	Not available.
pH:	Not available.	**Explosive Limit – upper (%):**	Not available.
Melting/Freezing Point:	Not available.	**Vapor Pressure:**	Not available.
Boiling Point/Range:	209.3°F (98.5°C) estimated.	**Vapor Density:**	Not available.
Partition Coeff (n-octanol/water):	Not available.	**Relative Density:**	Not available.
Heat of Combustion (NFPA 30B):	39.65 kJ/g estimated.	**Solubility (water):**	Not available.
Viscosity:	Not available.	**Auto-Ignition Temperature:**	421°F (216.11°C) estimated.
Evaporation Rate:	Not available.	**Decomposition Temperature:**	Not available.
Oxidizing Properties:	Not oxidizing.	**Flash Point:**	-156.0°F (-104.4°C) Propellant estimated.

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and nonreactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: Direct contact with eyes may cause temporary irritation.
Skin: No adverse effects due to skin contact are expected.
Inhalation: No adverse effects due to inhalation are expected.
Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Aspiration may cause pulmonary edema and pneumonitis.

ACUTE TOXICITY:

May be fatal if swallowed and enters airways.

COMPONENTS	SPECIES	TEST RESULTS
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Guinea pig; Rabbit	>9.4 ml/kg, 24 Hours
	Rabbit	>1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	>5000 mg/m^3, 4 Hours
		>4980 mg/m^3
		>4980 mg/m^3, 4 Hours
		>4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg

n-Heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	>2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	>29.29 mg/l, 4 Hours
Oral		
LD50	Rat	>5000 mg/kg

Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

Titanium dioxide (CAS 13463-67-7)		
Acute		
Inhalation		
LC50	Rat	>2.28 mg/l, 4 Hours
Oral		
LD50	Mouse	>5000 mg/kg
	Rat	>2000 mg/kg

Zinc Oxide (CAS 1314-13-2)		
Acute		
Dermal		
LD50	Rat	>2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5700 mg/m³
Oral		
LD50	Mouse	2000 - 5000 mg/kg
	Rat	>5000 mg/kg

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Direct contact with eyes may cause temporary irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity:

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens:

Not listed.

REPRODUCTIVE TOXICITY:

This product is not expected to cause reproductive or developmental effects.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

Not classified.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Not classified.

ASPIRATION HAZARD:

May be fatal if swallowed and enters airways.

12. Ecological Information

ECOTOXICITY:

Toxic to aquatic life with long lasting effects.

PRODUCT		SPECIES	TEST RESULTS
WHITE LUBE			
Aquatic			
Algae	IC50	Algae	50256 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2478 mg/L, 48 Hours
Fish	LC50	Fish	134 mg/L, 96 Hours
COMPONENTS		**SPECIES**	**TEST RESULTS**
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	>1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	>1000 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Zinc Oxide (CAS 1314-13-2)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2246 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

Partition coefficient n-octanol / water (log Kow):

n-Heptane	4.66
Propane	2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (See: Disposal Instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not reuse empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950

UN PROPER SHIPPING NAME: Aerosols, flammable, (each not exceeding 1 L capacity)

TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

PACKING GROUP: Not applicable.

SPECIAL PRECAUTIONS FOR USER: Not available.

SPECIAL PROVISIONS: N82

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: None.

PACKAGING BULK: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN NUMBER:** UN1950

UN PROPER SHIPPING NAME: Aerosols, flammable

TRANSPORT HAZARD CLASS(ES)"

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS: Yes.
ERG CODE: 10L
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
OTHER INFORMATION:
PASSENGER AND CARGO AIRCRAFT: Allowed with restrictions.
CARGO AIRCRAFT ONLY: Allowed with restrictions.
PACKAGING EXCEPTIONS: LTD QTY

IMDG: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: AEROSOLS
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: -
Label(s): None.


PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS:
Marine pollutant: Yes.
General Information: IMDG Regulated Marine Pollutant
EmS: F-D, S-U
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
PACKAGING EXCEPTIONS: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:
Not established.

15. Regulatory Information

US FEDERAL REGULATIONS:
This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4): Not listed.
SARA 304 EMERGENCY RELEASE NOTIFICATION: Not regulated.
OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050): Not listed.
SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories	Immediate Hazard – Yes.
	Delayed Hazard – No.
	Fire Hazard – Yes.
	Pressure Hazard – No.
	Reactivity Hazard – No.

SARA 302 Extremely Hazardous Substance: Not listed.
SARA 311/312 Hazardous Chemical: No.
SARA 313 (TRI reporting): Not regulated.

OTHER FEDERAL REGULATIONS:
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
Propane (CAS 74-98-6)
Safe Drinking Water Act (SDWA): Not regulated.

US STATE REGULATIONS:
US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.
US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.(a)):
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)
Titanium dioxide (CAS 13463-67-7)
US. Massachusetts RTK - Substance List:
n-Heptane (CAS 142-82-5)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Zinc Oxide (CAS 1314-13-2)
US. New Jersey Worker and Community Right-to-Know Act:
n-Heptane (CAS 142-82-5)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Zinc Oxide (CAS 1314-13-2)
US. Pennsylvania Worker and Community Right-to-Know Law:
n-Heptane (CAS 142-82-5)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Zinc Oxide (CAS 1314-13-2)
US. Rhode Island RTK:
Propane (CAS 74-98-6)
US. California Proposition 65:
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
US - California Proposition 65 - CRT: Listed Date/Carcinogenic Substance:

Benzene (CAS 71-43-2)	Listed: February 27, 1987
Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed Date/Developmental Toxin:

Benzene (CAS 71-43-2) Listed: December 26, 1997

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed Date/Male Reproductive Toxin:

Benzene (CAS 71-43-2) Listed: December 26, 1997

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.