


SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1781	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	WORK HORSE	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Aerosol Non-Melt Grease Spray	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Aspiration Hazard - Category 1 Toxic to Reproduction - Category 2 Skin Irritation - Category 2 Eye Irritation - Category 2 Specific Target Organ Toxicity (repeated exposure) - Category 2 Specific Target Organ Toxicity (single exposure) - Category 3 Flammable Aerosols - Category 1 Gasses under pressure - Compressed gas	SIGNAL WORD: DANGER	SYMBOL:	
--	--------------------------------------	----------------	--

HAZARD STATEMENTS:

Keep out of reach of children. Read label and SDS before use. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause damage to central nervous system through prolonged or repeated exposure via inhalation. Suspected of damaging fertility or the unborn child. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands and face thoroughly after handling. Wear protective gloves. Wear eye protection.

Response: If exposed or concerned: Get medical attention. **IF SWALLOWED:** Immediately call a poison center or a doctor. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional and national regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

Not applicable.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Butane	106-97-8	5 - 10
Hydrotreated Heavy Naphthenic Distillate	64742-52-5	15 - 25
Propane	74-98-6	15 - 25
Hexane	110-54-3	15 - 20
Acetone	67-64-1	1 - 5

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: DANGER. Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION:

Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION:

Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Use water spray, fog or foam.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion.

Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

Carbon Dioxide, Carbon Monoxide.

SPECIFIC FIRE-FIGHTING METHODS:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Put on appropriate personal protective equipment (see Section 8)

ENVIRONMENTAL PRECAUTIONS:

Prevent runoff from entering drains, sewers, streams or other bodies of water.

METHODS & MATERIALS FOR CONTAINMENT & CLEANUP:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7. Handling and Storage

SAFE HANDLING:

Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

SAFE STORAGE & INCOMPATIBILITIES:

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120°F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place.

8. Exposure Controls / Personal Protection

Butane (106-97-8)	ACGIH TLV	1000 ppm
Hexane (110-54-3)	OSHA PEL	500 ppm
	ACGIH TLV	50 ppm
Hydrotreated Heavy Naphthenic Distillate (64742-52-5)	OSHA PEL	5 mg/m ³
	ACGIH TLV	5 mg/m ³
Acetone (67-64-1)	OSHA PEL	750 ppm
	ACGIH TLV	500 ppm
Propane (74-98-6)	ACGIH TLV	1000 ppm

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation required.

9. Physical & Chemical Properties

Appearance:	Red grease.	Explosive Limit Ranges:	Not available.
Physical State:	Liquid.	Explosive Properties:	Not available.
Color:	Red.	Vapor Density:	Not available.
Odor:	Solvent.	Vapor Pressure:	Not available.
Odor Threshold:	Not available.	Relative Density:	0.8
pH:	Not applicable.	Solubility (water):	Insoluble.
Melting/Freezing Point:	Not available.	Auto-Ignition Temp:	Not available.
Boiling Point:	Not available.	Decomposition Temp:	Not available.
Viscosity:	Not available.	Partition Coeff(n-octanol/water):	Not available.
Flash Point:	< 0°F (liquid portion).	VOC content (wt. %):	49.6.
Evaporation Rate:	Not available.	Oxidizing Properties:	Not available.

10. Stability & Reactivity Information

REACTIVITY:

Under normal conditions of storage and use, hazardous reactions will not occur.

CHEMICAL STABILITY:

Stable under normal conditions.

CONDITIONS TO AVOID:

High temperatures, open flames, sparks, welding.

INCOMPATIBLE MATERIALS:

Acids and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS:

CO, CO₂

Vapors may ignite at temperatures exceeding flash point.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

Skin: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

Inhalation: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

Ingestion: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

ACUTE TOXICITY:

Components	Species	Test Results
Hexane		
Acute Dermal LD50	Rabbit	3000 mg/Kg
Inhalation LC50	Rat	4 hr, rat 48000 ppm.

CARCINOGENICITY:

This material is not listed as a carcinogen by IARC, NTP or OSHA.

REPRODUCTIVE TOXICITY:

Suspected of damaging fertility or the unborn child.

SPECIFIC TARGET ORGAN TOXICITY

Central nervous system.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

12. Ecological Information

ECOTOXICITY:

Product	Species	Test Results
Hexane		
Aquatic Fish	LC50 pimephales promelast	96 h, 2.1 - 2.98 mg/l

13. Disposal Consideration

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

14. Transportation Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

DOT: **UN Number:** UN1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es):
Class: 2.1
Packing Group: -

15. Regulatory Information

US FEDERAL REGULATIONS:

All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Acetone 5000 lbs

Hexane 5000 lbs

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

Hazard categories:

Immediate Hazard – Yes.

Delayed Hazard – Yes.

Fire Hazard – Yes.

Pressure Hazard – Yes.

Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous chemical: No.

SARA 313 (TRI reporting): Hexane

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS. If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

OTHER FEDERAL REGULATIONS:

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s):

D001

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.