# XL 866 #1719

## **Aerosol Chain and Cable Lubricant**



#### Features:

- · Fortified with Moly and PTFE
- Contains no chlorinated solvents or ozone depleters
- · Penetrates for fast set up
- · Resists throw off
- Special valve for precise control and elimination of overspray
- Water and acid resistant
- · Lubricates and reduces friction
- · Ideal for chains, cables and moving assemblies
- Food Processing Acceptability: H2

#### **Description:**

XL 866 is a mixture of penetrants, anti-oxidants, oils and greases for use on chains, cables and wire ropes. Fortified with both molybdenum disulfide and PTFE, the formula provides superior lubricity, protection, longevity and temperature resistance. Penetrates deep inside the core of wire rope to provide superior lubrication at the point of greatest stress. Using this product prevents metal-to-metal contact and reduces friction, heat, stress and wear during operation. May be used under widely varying climatic conditions and will not break down under heat, stress and prolonged use.



## **Applications:**

- Chains & Cables
- Wire Ropes
- Chain Saws
- Drive Chains
- Hoist Chains
- Drag Chains
- Roller Assemblies
- · Conveyor Chains
- Sprockets

#### For Use By:

- Factories
- Industrial Plants
- Mining Operations
- Bottling Companies
- Food Processing Plants
- Manufacturing Plants
- Hotels/Motels
- Breweries
- · Industrial Rendering
- · Military Facilities
- Steel Mills
- Canneries

## **Product Characteristics:**

Appearance:		Aerosol containing a liquefied gas	
Color:		Black, green	
Odor:		Solvent like	
VOC:		26.5	
Vapor Pressure:		No data available	
Solubility (water):		Insoluble	
Relative Vapor Density:		No data available	
Flash Point:		No data available	
Heat of Combustion:		46.08 kJ/g	
pH:		Not applicable	
Storage:	Protect from	Protect from sunlight. Do not expose to	
	temperatures exceeding 50°C/122°F.		
Transport Information:			
UN Number		UN1950	
Proper Shipping Name:		Aerosols, flammable, LTD QTY	
Class:		2.1	
Packing Group:		Not regulated	
:			

#### **Directions:**

SHAKE WELL BEFORE USING. Hold can 6-10 inches from surface to be lubricated and spray liberally.

## **Pictograms:**





## Signal Word:

DANGER

#### **Personal Protective Equipment Required:**





DOT Placard: VOC Compliant:



Not for sale in CA, CT, DE, MD, NH and UT.