



Cover Up

#2417

Waste Water Odor Control Treatment

Features

- Bio-based and biodegradable
- Non-emulsifying formula floats on the surface of the water, so it continues to remove deposits as the water level changes
- Creates a barrier that keeps out the air that carries the odors away from the station
- Coats the walls and surfaces of the lift stations to remove heavy grease accumulations quickly and safely



Description

Cover Up is a bio-based and biodegradable odor treatment for use in waste water treatment plants. It coats the walls and surfaces in waste water facilities, grease traps, and lift stations to remove heavy grease accumulations quickly and safely. The special non-emulsifying formula floats on the surface of the water creating an odor absorbing barrier while it continues to remove deposits as the water level changes. Also its pleasant cucumber fragrance also helps to mask any escaped odors.

Applications

- Waste Water Facility
- Drain Lines
- Lift Station

Directions

LIFT STATION & WASTE WATER FACILITY: Use approximately ½ gallon for every square foot of wastewater surface area (1 quart for 100 gallons). Always maintain a protective layer of 1 to 3 inches of Cover Up above water level.

GREASE TRAPS: Start treatment immediately after the grease trap has been pumped. Add 1 quart per cubic foot of capacity. In a week begin preventive maintenance of one gallon daily per 40 cubic feet of trap capacity.

Product Specifications

Appearance	Opaque Green Liquid
Odor	Cucumber Melon
Boiling Point	>575°F/ >302°C
Specific Gravity	.91 (H ² O=1)
Melting Point	N/A
Evaporation Rate(Butyl Acetate=1)	N/A
Solubility (H ₂ O=1)	None.
Vapor Pressure(mmHg)	<1 @ 20° C
Vapor Density(AIR=1)	>1
Flash Point	>500° F/ >260°C
Storage	Store in a cool dry area. Keep out of reach of children. Keep container closed when not in use.
Transportation Information	
Class #	55

Product Information Sheet

Health	1
Flammability	1
Reactivity	0
Personal Protection	B