



# Lub-All

# #1738

Aerosol Gelled Penetrating Lubricant with Teflon®

# Product Information Sheet

### Features

- Allows maximum penetration and rapid set up of the grease-like lubricant
- Helps prevent rust and corrosion
- Lasts longer than conventional lubricants
- Prevents sticking & freezing of rubber to metal
- Will withstand temperatures of -30°F to over 600°F
- Resists water wash out
- Contains no CFC's, which deplete the ozone layer
- Food Processing Acceptability: H2



### Description

LUB-ALL is a transparent, high pressure lubricant with high adhesive strength. LUB-ALL adheres to surfaces and resists throw-off and squeeze out when subjected to high pressures, vibrations, or repeated impact. A unique combination of natural and synthetic lubrication agents coupled with Teflon® makes LUB-ALL one of the best aerosol lubricants available. *Caution: Not to be used near heat, sparks or open flame.*

### Applications

- Wire ropes
- Sprockets
- Open gears
- Cables
- Chains
- Door hinges
- Legs on hoists
- Conveyors

### Directions

Shake well. Saturate area to be lubricated. If necessary, repeat application.

### Product Characteristics

Appearance	Clear, light yellow gel spray
Odor	Solvent
Flash Point (method used)	0°F (T.C.C.)
Specific Gravity (H <sub>2</sub> O=1)	0.80
Evaporation Rate (Butyl Acetate = 1)	N/E
Solubility in water	Insoluble
pH Concentrate	N/A
Boiling Point	N/A
Vapor Density (Air=1)	N/E
Vapor Pressure (mmHg)	N/E
Storage	Do not store near heat or open flame. Store in a cool, dry place. Keep out of reach of children.
Transportation information	
Class #	65
NFMC	155250

®Teflon is a registered trademark of E.I. DuPont de Nemours.

Health	2
Flammability	4
Reactivity	0
Personal Protection	G