



Strip It

#2621

Paint and Resin Remover

Product Information Sheet

Features

- Quick-acting seal and varnish remover
- Non-toxic – does not contain toluene, acetone or methylene chloride
- Removes most types of paint, varnish, shellac, polyurethane, and lacquer from many different surfaces
- Clings to vertical surfaces
- High flashpoint (over 100°F)
- Water flushable
- Non-corrosive to metal
- No methylene chloride



Description

STRIP IT is a highly effective paint and resin remover that is ideal for removing oil and latex paints, shellac, lacquers and polyurethanes from a variety of surfaces such as wood, metal, etc. STRIP IT's non-chlorinated formula and slow evaporation rate makes it ideal for vertical surfaces. Unlike most non-methylene chloride paint strippers, STRIP IT has a high flashpoint and does not contain toxic chemicals such as toluene, acetone or MEK.

Applications

- Wood
- Metal
- Plastic (test in inconspicuous area first)

Directions

Brush on surface and let soak for up to 30 minutes depending on the type and age of paint. Two-part epoxy coatings may require soak times of 2 hours or longer. In certain thick coatings, several applications are necessary. Remove with pressure washer, putty knife, or steel wool.

Product Specifications

Appearance	Clear, colorless liquid
Odor	Solvent
Vapor Density (Air=1)	N/E
Evaporation Rate (Butyl acetate=1)	N/E
Boiling Point	N/E
Solubility in Water	Insoluble
pH Concentrate	N/A
Vapor Pressure (mmHg)	N/E
Specific Gravity (H2O=1)	0.94
Flash Point (method used)	110°F (TOC method)
Emulsifiers	2.0 +/- 0.2%
Solvents	93 +/- 0.5%
Storage	Store in a cool, dry place. Keep container closed when not in use. Keep out of reach of children.
Transportation information	
Class #	55
Proper Shipping Name	Paint and Related material
NFMC	149980-2

Health	2
Flammability	2
Reactivity	0
Personal Protection	G