PRO CHEM, INC. 1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET AWAY PLUS / 1540 MARCH 2010 PAGE 1

HEALTH	1
FIRE	4
REACTIVITY	0
P.P.E.	А

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 1 – Chemical and Company Identification

CHEMICAL FAMILY: Aerosol

SECTION 2 – Composition on Ingredients						
CAS #	NAME	% BY WT.	OSHA PEL/ ACGIH TLV	SARA 302/304(1)*	SARA 313 (2)	
67-63-0	Isopropanol	< 40.0	400 ppm	NO	NO	NO
134-62-3	N,N-diethyl-m- toluamide (DEET)	25	N/e / n/e	NO	NO	NO
113-48-4	N-Octyl Bicycloheptene Dicarboximide	5.00	N/e / n/e	NO	NO	NO
136-45-8	Di-n-propyl isocinchomeronate	2.50	N/e / n/e	NO	NO	NO
PROPELLANT MIXTURE						
74-98-6	Propane		1000 ppm	NO	NO	NO
106-97-8	N-Butane		600 ppm	NO	NO	NO
* See Section '	15 for more information			n/e = none establis	hed	n/a = not applicable

SECTION 3 – Hazards Information

EMERGENCY OVERVIEW: DANGER. Flammable. Harmful or fatal if swallowed. Aspiration hazard. Causes eye irritation. Avoid inhalation of concentrated vapors. May cause nervous system depression. DO NOT spray product directly on face. Keep away from heat and flame. Contents under pressure.

PRIMARY ROUTE OF ENTRY: Inhalation

ACUTE/POTENTIAL HEALTH EFFECTS:

- EYES:Causes irreversible eye damage. DO NOT spray product directly on face.SKIN:May cause skin reactions in rare cases. DO NOT apply over cuts, wounds or
irritated skin.
- **INHALATION:** High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.
- **INGESTION:** Harmful or fatal if swallowed. Aspiration hazard this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

CHRONIC/LONG TERM EFFECTS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Signs and symptoms of exposure to this material through breathing or swallowing may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

TARGET ORGAN EFFECTS:

REPRODUCTIVE/DEVELOPMENTAL INFORMATION: No data.

CARCINOGENIC INFORMATION: This material is not listed as a carcinogen by IARC, NTP or OSHA.

No data.

SECTION 4	First Aid Measures		
EYES:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical		
0.000	attention immediately.		
SKIN:	If irritation develops, seek medical attention.		
INHALATION:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,		
	give oxygen.		
INGESTION:	Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended.		
SECTION 5 – Fire Fighting Measures			
FLASH POINT:	73°F METHOD USED: TCC FLAME EXTENSION: 18"		

EXTINGUISHING MEDIA: Dry Chemical, CO₂, or foam is recommended. **SPECIAL FIRE FIGHTING INSTRUCTIONS:** DANGER. FLAMMABLE. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

SECTION 6 – Accidental Release Measures

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

SECTION 7 – Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120°F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

SECTION 8 – Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Good general ventilation required.

EYE PROTECTION: DO NOT spray product directly on face.

SKIN PROTECTION: DO NOT use under clothing. Avoid over application. After returning indoors, wash treated skin with soap and water. Keep away from eyes and mouth.

RESPIRATORY PROTECTION: When respiratory protection is required, use an organic vapor & particulate cartridge. All respiratory programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

SECTION 9 – Physical and Chemical Properties

APPEARANCE/ODOR: Clear, colorless spray/mist with pleasant fragrance				
EVAPORATION RATE (BUTYL ACETATE=1): N/e				
SOLUBILITY IN WATER:	Negligible	SPECIFIC GRAVITY (H20=1):	0.80	
VAPOR PRESSURE (mmHg):	N/e	pH CONCENTRATE:	N/a	
VAPOR DENSITY (AIR=1):	N/e	BOILING POINT:	180°F	

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.

PRO CHEM, INC.

1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET AWAY PLUS / 1540 MARCH 2010 PAGE 2

HEALTH	1
FIRE	4
REACTIVITY	0
P.P.E.	А

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 10 – Stability and Reactivity

STABILITY:	Stable
INCOMPATIBILITY:	Acids and strong oxidizers
CONDITIONS TO AVOID:	High temperature
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRO	DDUCTS: CO, CO_2

SECTION 11 – Toxicological Information

Isopropanol: SKIN-Rabbit; 24 hr. uncovered-no irritation. EYE-Rabbit; 0.02ml-moderate corneal injury.

SECTION 12 – Ecological Information

Isopropanol: Toxicity to micro-organisms-bacterial inhibition; IC50 Results: 5000 mg/l.

Toxicity to fish-fathead minnow; 96h; LC50 Results: 8300 mg/l

SECTION 13 – Disposal Consideration

Waste Disposal Method: Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

SECTION 14 – Transport Information

D.O.T. Shipping Name / Class:

Consumer Commodity, ORM-D (Domestic Ground Shipments)

SECTION 15 – Regulatory Information

U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2: Acute (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

(1) Title III Section 302/304 Extremely Hazardous Substances - 40 CFR 355 Appendix A
(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s) D001

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

(3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)

(4) Massachusetts (Hazardous Substance Disclosure by Employers)

SECTION 16 – Other Information

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.