

# FUEL AID PLUS #2834

## Multifunctional Fuel Additive



### Features:

- Keeps gasoline engines running cleaner and more efficiently
- Extends engine life
- Reduces emissions
- Rust & corrosion inhibitors for protection of fuel systems
- Good water removal
- Provides upper cylinder lubrication under cold starting conditions
- Reduces intake valve, carburetor and port fuel injector deposits



### Description:

FUEL AID PLUS is a premium additive that helps all types of gasoline-powered engines run cleaner and more efficiently. This formula improves the performance of all gasoline-powered engines, including those with catalytic converters and computer-controlled engines. The special detergents in this additive remove deposits and clogs from fuel injection systems for better acceleration. Dispersant and corrosion inhibitor additives clean gums, varnish, and corrosion deposits from the fuel tank, delivery system and carburetors. This additive also protects engines from further corrosion. It extends engine life by eliminating intake valve deposits and lubricating upper cylinders under cold start conditions. It also lubricates cylinder walls and eliminates severe wear of fuel-delivery systems.

### Effective Against:

- Corrosion
- Gums & Varnish
- Deposits & Clogs

### Applications:

- Fuel Tanks
- Stationary Engines
- Carburetors
- Marine Engines (except outboard)
- Fuel Injectors
- 2-Cycle Outboard Engines

### For Use By:

- DOT
- Fleet Operations
- Golf Courses
- Police Departments
- Rental Car Industries
- Municipalities
- Marinas
- Coast Guard
- Utility Companies

### Product Characteristics:

Appearance:	Clear, colorless liquid
Odor:	Solvent odor
Boiling Point:	No data available
Vapor Pressure:	No data available
Specific Gravity:	0.86 g/mL
Solubility:	Insoluble in water
Relative Density:	No data available
Flash Point:	118°F closed cup
VOC Content:	100%
pH:	No data available
Viscosity (kinematic):	<20 cSt
Storage:	Store in a well-ventilated place. Keep container tightly closed. Keep cool Store locked up.
<b>Transport Information:</b>	
UN Number:	Not regulated
Proper Shipping Name:	Not regulated
Class:	Not regulated
Packing Group:	Not regulated

### Directions:

Add 12 ounces for every 20 gallons of gasoline. In bulk storage tanks, use 2-3 gallons per 1,000 gallons of gasoline fuel.

**Note: Not for use with diesel fuel.**

### Pictograms:



### Signal Word:

DANGER

### Personal Protective Equipment Required:



**DOT Placard:**  
Not regulated.

**VOC Compliant:**  
Yes.