

# FUEL AID PLUS #2834

## Multi-Functional Gasoline Additive



### Features:

- Keeps gasoline engines running cleaner and more efficiently
- Extends engine life
- Reduces emissions
- Rust and corrosion inhibitors for protection of fuel systems
- Good water removal
- Provides upper cylinder lubrication under cold starting conditions
- Reduces intake valve, carburetor and port fuel injector deposits

### Description:

FUEL AID PLUS is a premium additive that helps all types of gasoline-powered engines run cleaner and more efficiently. This formula improves the performance of all gasoline-powered engines, including those with catalytic converters and computer-controlled engines. The special detergents in this additive remove deposits and clogs from fuel injection systems for better acceleration. Dispersant and corrosion inhibitor additives clean gums, varnish, and corrosion deposits from the fuel tank, delivery system and carburetors. This additive also protects engines from further corrosion. FUEL AID PLUS extends engine life by eliminating intake valve deposits and lubricating upper cylinders under cold start conditions. It also lubricates cylinder walls and eliminates severe wear of fuel-delivery systems.



### Effective Against:

- Corrosion
- Gums & Varnish
- Deposits & Clogs

### Applications:

- Fuel Tanks & Fuel Injectors
- Carburetors
- Gasoline Powered Engines
- Marine Engines (except outboard)
- Computer Controlled Engines
- Stationary Engines
- Catalytic Converters
- 2-Cycle Outboard Engines

### For Use By:

- DOT
- Police Departments
- Marinas
- Fleet Operations
- Rental Car Industries
- Coast Guard
- Golf Courses
- Municipalities
- Utility Companies

### Product Characteristics:

Size:	283401	283405 & 283407
Appearance:	Clear, amber liquid	Clear, colorless liquid
Odor:	Hydrocarbon odor	Solvent odor
Boiling Point:	No data available	No data available
Vapor Pressure:	No data available	No data available
Density:	0.79 g/ml	N/A
Solubility (water):	Insoluble in water	Insoluble in water
Relative Density:	No data available	No data available
Flash Point:	> 147°F Closed Cup	118°F Closed Cup
Stability:	1 year	No data available
pH:	No data available	No data available
Viscosity:	No data available	<20 cSt (kinematic)
Storage:	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.	
<b>Transport Information:</b>		
UN Number:	Not regulated for transport	Not regulated
Proper Shipping Name:	Not regulated for transport	Not regulated
Class:	Not regulated for transport	Not regulated
Packing Group:	Not regulated for transport	Not regulated

### Directions:

Add 12 ounces for every 20 gallons of gasoline. In bulk storage tanks, use 2-3 gallons per 1,000 gallons of gasoline fuel.

**Note: Not for use with diesel fuel.**

### Pictograms:



- 16 oz Bottle (283401)



- 1 Gallon (283407) & 5 Gallon (283405)

### Signal Word:

DANGER

### Personal Protective Equipment Required:



**DOT Placard:**  
Not regulated.

**VOC Compliancy:**  
Yes.