

# FUEL ANTI-GEL #2839

Concentrated Diesel Fuel Additive



## Features:

- Reduces pour point
- Inhibits gelling
- Stabilizes fuel
- Keeps all types of fuel oil and diesel fuel flowing in cold weather
- Eliminates the need for tank heaters



## Description:

FUEL ANTI-GEL is an additive for diesel fuels and all grades of heating fuel oils. This concentrated antigel reduces the pour point by as much as 25°F to keep fuel flowing to engines and boilers in cold weather. It also modifies the shape and structure of wax crystals as they form in the cold oil, preventing the clogging of lines and filters. FUEL ANTI-GEL eliminates dangerous failures of oil-fired boilers, furnaces, diesel trucks and generator engines in cold weather.

## Applications:

- Diesel Fuel Tanks
- Heating Oil Fuel Tanks

## For Use By:

- DOT
- Municipalities
- Hospitals
- Bus Garages
- Utilities
- School Bus Barns
- Building Maintenance
- Heavy Equipment Operators
- Fleet Operation Companies

## Product Characteristics:

Appearance:	Hazy. Colorless liquid
Odor:	Characteristic solvent odor
Boiling Point:	No data available
Vapor Pressure:	No data available
Specific Gravity/Density:	0.89 g/ml
Solubility (water):	Insoluble
VOC:	Not determined
Flash Point:	120°F closed cup
Viscosity, Kinematic:	<20 cSt
pH:	No data available
Melting/Freezing Point:	No data available
Storage:	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
<b>Transport Information:</b>	
UN Number:	Not available
Proper Shipping Name:	Not available
Class:	Not available
Packing Group:	Not available

## Directions:

Add 12 ounces to 150 gallons of all grades of fuel. This dosage will lower the pour point of most residual fuels by approximately 20°F. In some cases, additional treatment will lower the pour point by several more degrees. For best results, the fuel should be at least 10°F above normal pour point when antigel additive is blended in.

This diesel additive complies with the Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

**Caution:** Combustible. Harmful or fatal if swallowed. Keep away from heat or open flame. Keep out of reach of children.

## Pictograms:



## Signal Word:

DANGER.

## Personal Protective Equipment Required:



## DOT Placard:

Not available.