

PRO VISION – EYEWEAR

ELITE #4668/4667

- Soft nosepiece for snug fit
- Semi-frame and slim co-injected temple design for lightweight spectacle– 22 gm
- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Wraparound lens for front and side protection
- Abrasion and chemical resistant
- Superior anti-fog coating
- 99.9% UV protection
- Lens Base: 8 Curve
- Available in blue mirror (466801) and clear (466701)



TITAN #4662

- Comfort-fit, rubber temples prevent eyewear from slipping
- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Suitable for both working environments and recreational activities
- 99% UVA/B/C protection
- Mirror Lens
- Wrap around style fits all facial sizes
- High-impact and scratch-resistant
- Lens Base: 8 Curve
- Available in black frame/blue mirror (466201)



INTENSE #4665/4666

- Built-in rubber nosepiece
- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Rubber temple tips
- High-impact and scratch-resistant
- Ventilated, straight-back flexible temples
- 99% UV protection
- Includes black lanyard
- Lens Base: 9 Curve
- Available in orange mirror (466601) and clear (466501)



VISITOR SPECS ANTI-FOG #4663

- Dielectric
- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Fits over most prescription frames
- High-impact and scratch-resistant
- Temples extend from brow bar to avoid interference with prescription frame temples
- 99% UV protection
- Lens Base: 2.5 Curve



TRANSITIONAL LENS #4669

- Soft nosepiece for snug fit
- Semi-frame and slim co-injected temple design for lightweight spectacle– 22 gm
- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Wraparound lens for front and side protection
- Abrasion and chemical resistant
- High-impact and scratch-resistant
- Superior anti-fog coating
- 99.9% UV protection
- Transitional lens changes from clear to dark after exposed to direct UV light
- Lens Base: 8 Curve



PRO VISION – EYEWEAR

PROVOQ #466001/466002:

- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Anti-fog
- Rubber temples provide non-slip comfort
- Ultra-lightweight
- Clear frames with black accents
- Soft nose piece comfortable fit
- Scratch resistant lenses
- 99.9% UVA/B/C protection
- Available in clear (466001) and smoke (466002)



ORANGE CRUSH #464301/464302:

- Soft, adjustable, fully customizable PivotEase™ nosepiece
- Bendable, super-flex TPR temple in bright orange for visibility and style
- TempleTouch™ technology provides comfortable grip on sides of the head
- 10 base curve lens for high-impact protection
- Removable, contoured rubber gasket acts as a cradle, helps keep liquids and dust out
- ANSI-approved hardcoated polycarbonate lenses
- N-Fog + coating offers superior protection for a long-lasting, fog-free view in high heat and humidity
- Available in clear (964301) and smoke (964302)
- Optional gray adjustable strap



PINK GRASSHOPPER #4650:

- N-Fog
- EVA foam dust air filter with built in air channels
- Super flex temples
- Designed to fit smaller head sizes
- Fully dielectric
- Black frames with pink accents
- 99.9% UVA, UVB, UVC protection
- Available in clear



READ #4645/4646/4647:

- Extra side protection
- Bifocal
- Clear frames with black accents
- 99.9% UVA, UVB, UVC protection
- Available in 3 strengths: 1.5, 2.0 & 2.5
- Available in clear



SAFETY GLASSES-CLEAR W/LED LIGHT #4771:

- Built-in rubber nosepiece and rubber temple tips keep eyewear secure for the active worker
- The L1154F (LR44) alkaline batteries provides up to 50 hours of use before replacing
- Easy to use push button on/off switches are located at the top of each temple
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection
- The super bright pivoting LED bulbs (3 lumens per side) help to see in dark places while keeping your hands free to do other tasks
- Three batteries per temples are included (six total)



PRO VISION – EYEWEAR

EVER-LITE – INFINITY BLUE #4133201:

- ANSI Z87.1 + rated
- Soft nosepiece for snug fit
- Semi-frame & slim co-material temple design for lightweight spectacle – 22 gm
- Offers a clear panoramic view without obstruction
- 8 base wraparound lens provides full front side protection
- Scratch-resistant, polycarbonate lens
- 99.9% UV protection
- 75% Blue Light blocked
- High performing, superior anti-fog coating that is durable enough to withstand repeated cleaning without losing adhesion
- Maximum clarity in the most extreme temperature and humidity conditions, and Layer added to the lens that is abrasion, chemical and UV-resistant
- Commonly used in indoor applications where there is an excessive amount of yellow or sodium vapor light. Offers a high level of contrast.
- Available in infinity blue (4133201)



EVER-LITE – AMBER #4133301:

- ANSI Z87.1 + rated
- Soft nosepiece for snug fit
- Semi-frame & slim co-material temple design for lightweight spectacle – 22 gm
- Offers a clear panoramic view without obstruction
- 8 base wraparound lens provides full front side protection
- Scratch-resistant, polycarbonate lens
- 99.9% UV protection
- 75% Blue Light blocked
- Commonly used in indoor, low light applications. Enhances contrast.
- Available in amber (4133301)



INTRUDER CLEAR/TINTED #4133501/4133401:

- ANSI Z87.1 + rated
- Lightweight, frameless protection
- Superior comfort and fit
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection
- Available in Clear (4133501) & Tinted (4133401)
- **Clear Lens:** General purposes for indoor applications that require impact protection.
- **Gray Lens:** Commonly used in outdoor applications. Offers protection from excessive glare.



MONTEAGLE – ICE BLUE #4133601:

- ANSI Z87.1 + rated hardcoated polycarbonate lenses
- Co-injected temples for snug, secure fit
- Adjustable rubber nosepiece
- Scratch-resistant
- 99% protection from harmful UV rays
- Gray polycarbonate lens with a double layer of silver and blue mirror coatings
- Commonly used in outdoor applications



Glossary:

TRP: This is a thermoplastic rubber compound that combines the moldability of plastic with the flexibility of rubber. It keeps its shape but is bendable.

ANSI Z87.1+: High-Velocity Impact Test Method: Lenses to be tested must be secured in a spectacle frame with the entire assembly mounted vertically on a head form. The test consists of dropping a 5 gram pointed weight from a height of about 5 feet onto the lens. The lens must also pass the test of having a 1/4" steel ball shot at the lenses.

PivotEase Nosepiece: This prevents slipping and sliding of safety glasses. Just turn the nose bridge to narrow and put the glasses on. The PivotEase nosepiece automatically adjusts and locks into the perfect, no-slip position.

TempleTouch Technology: This unique feature has raised, rubber nibs molded into the temple tips to provide a gentle but firm grip at the sides of the head and behind the ears.

Adjustable Temples: The arms of these safety glasses ratchet up and down to fit your facial and ear contours with adjustable lengths to settle behind your ears comfortably without compromise to the optics of the glasses.

Base Curve: This is a number that describes the amount of curvature of the front surface of a lens. Base curves range from 0 to 10 or more. The lower the base curve number, the flatter the lenses and the higher the number the more the lens is curved.

Anti-Fog Technology: Our long-lasting, anti-fog lens coating keep your glasses fog free for longer than any other anti-fog lenses. There are no anti-fog standards in the US.

N-Fog: This coating is permanently bonded to the lens and will not wear off or wash off. Glasses with this coating will stay fog free for 6+ minutes. Glasses with this coating exceed the EN 166/168 standard lasting 15 times longer than required. These glasses also retain their anti-scratch, antistatic, and UV protection properties.

N-Fog+: This coating is permanently bonded to the lens and will not wear off or wash off. Glasses with this coating will stay fog free for 6+ minutes. Glasses with this coating exceed the EN 166/168 standard lasting 45 times longer than required. The glasses are virtually fog free. These glasses also retain their anti-scratch, antistatic, and UV protection properties.

EN 166/168 Standard: Requires 8 seconds of anti-fog compliance.

SpringFlex: This temple design cannot be bent out of shape. You can bend it at a right angle and watch it spring back to its naturally curved, molded-to-fit-the-face form.