

EASY ERASE #2143

Waterborne Dry Erase Coating



Features:

- Create writeable/erasable finish
- Use this clear gloss over any paint color
- Low odor formula is safe for indoor use
- Can be applied to many surfaces
- Zero VOC and zero HAPs and low odor
- Cleanup with dry cloth – no harsh chemicals

Description:

EASY ERASE is a zero VOC (Volatile Organic Compounds), zero HAPs (Hazardous Air Pollutants), low odor clear gloss that turns any surface into a writable/erasable surface. Once coating has dried, you can use any dry erase marker to draw or write on the EASY ERASE surface. Cleanup is easy with a dry cloth, eliminating the need for the use of any harsh chemicals. It can be applied to any painted surface and dries to a clear, glossy finish. To have a different color than the wall color, simply apply over a base coat.

A base coat must be used if you are applying EASY ERASE to a non-finished surface such as bare drywall, plaster, wood, masonry, aluminum or galvanized metal.



Applications:

- Schools
- Commercial Settings
- Conference Rooms
- Offices
- Message Boards
- Industrial Plants

Physical Characteristics:

Color:	Clear	Weight/Gallon:	9.0 +/- 0.25 lbs/gal (mixed)
Viscosity:	80-85 KU (mixed)	Gloss:	>90%
Weight Solids:	54% +/- 2.0 (mixed)	Volume Solids:	47% +/- 2.0 (mixed)
Pot Life:	1-2 hours at 70°F	Mix Ratio (by volume):	2:1
Mixing Time:	3-5 minutes.	Induction Time:	None.
Viscosity:	As is	Reduction:	≤8 fl oz/gal for spraying
Reducer:	Water	Cleanup:	Soap and water
Application Method:	Brush/roll/spray.	Wet Film Thickness:	3.0 – 5.0 mils/coat
Dry Film Thickness:	1.4 – 2.3 mils/coat	Dry to Recoat:	4-6 hours
Dry Hard:	48 hours	Full Cure:	5 days

Product Characteristics:

Appearance:	A: Milky white	B: Light yellow liquid
Odor:	A: Mild odor	B: Slight Odor
VOC (mixed):	A: <10 g/L	
Specific Gravity (H ₂ O=1):	A: 1.08 g/cm ³	B: 1.16 g/cm ³
Solubility:	A: Soluble	B: Insoluble
pH:	A: 7-7.5	B: Not available
VOC (combined):	<10 g/L	
Storage:	A: Protect from freezing. Store in a cool dry place. Store in original or similar containers. Store separate from food products. B: Store locked up. Store in well-ventilated place. Keep container tightly closed.	
Transport Information:		
Proper Shipping Name:	A: Not regulated B: Protect from freezing. Store in a cool dry place. Store in original or similar containers. Store separate from food products.	
UN Number:	B: UN3082	
Class:	B: 9	
Packing Group:	B: III	

DOT Placard: Not regulated.


VOC Compliant:
Yes.

Signal Word:
A: Not applicable.
B: DANGER.

Directions:

Mix Part A thoroughly. Add the full contents of Part B to Part A and blend completely (3-5 minutes). A drill mounted impeller is recommended for best mixing. Do not add water to individual components. Apply when air and surface temperatures are 50-90°F and the relative humidity is less than 85%. Do not apply if rain is expected within 48 hours of application. Do not exceed spreading rate as this may cause pinholes, microblistering or a milk appearance. If over 12 hours lapses between coats, lightly scuff sand the surface and remove all dust before applying the next coat. See label for full directions.

Pictograms:



Personal Protective Equipment Required:

