

# LOOSEN UP #1785

## Aerosol Food Grade Penetrating Oil



### Features:

- Prevents rust
- Loosens corroded parts
- Penetrates quickly
- Long lasting lubrication
- Makes disassembly and retooling faster
- Complies with FDA regulations CFR Title 21, 178.3570
- Great to use after pressure washing or steam cleaning to help eliminate rust
- Safe for all metal surfaces and most plastics
- NSF Rating: H1



### Description:

LOOSEN UP is an odorless, colorless, non-flammable penetrating oil that meets NSF H1 requirements. It penetrates quickly and deeply to free corroded and hard to remove nuts, bolts, screws, etc. This unique formula is also an excellent rust inhibitor and the extension tube extends the distance it can be applied, allowing the user to reach the most difficult areas. Its high percentage of rust inhibitors makes this product ideal to use to help eliminate rust after pressure washing and steam cleaning equipment. It is safe to be used in areas with incidental food contact and around food processing area.

### Applications:

- Slides
- Bearings
- Pistons & Rings
- Nuts
- Seals
- Pump Parts
- Belts
- Bolts

### For Use By:

- Food Processing Plant
- Meat & Poultry Plants
- Packaging Plants
- Cosmetic Manufactures
- Water Treatment Plants
- Dairies
- Factories
- Breweries
- Bakeries
- Schools
- Supermarkets
- Warehouses
- Canneries
- Creameries
- Industrial Plants
- Bottling Companies
- Box Manufacturing Plants
- Egg Processors
- Edible Chemical Manufacturing
- Hospitals

### Product Characteristics:

Appearance:	Clear, spray yellow tint spray
Odor:	Mild to no odor
Relative Density (H2O=1):	0.81 - 0.83 @ 77°F (25°C)
Vapor Pressure (mm Hg):	<1.0 @ 77°F (25°C)
Vapor Density (AIR=1):	Not determined
Solubility (water):	Emulsion
Flash Point:	> 200°F (93.3°C)
Viscosity:	Not determined
Toxicity:	5mg/m <sup>3</sup> as oil mist
Cold Stability:	32°F
Storage Stability:	1 year+
Wetting Ability:	Excellent
Propellant:	Carbon Dioxide
Evaporation Rate:	<1
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place.
<b>Transportation Information:</b>	
Proper Shipping Name:	Aerosols, Ltd. Qty
UN Number:	UN1950
Class:	2.2
Packing Group:	Not applicable

### Directions:

Shake can well for 10 seconds prior to spraying. Hold can in upright position 6 to 10 inches from area to be lubricated. Allow to penetrate and loosen parts. Operate component or disassemble parts. Wipe surface clean and reapply. Use only enough product for application. Wipe off any excess.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



### DOT Placard:

Not regulated.

### VOC Compliancy:

Yes.