

FG 450 #1784

Aerosol Food Grade Grease



Features:

- Heavy duty, multipurpose white grease
- Extreme pressure performance
- Excellent water resistance
- Inhibits rust and oxidation
- Operating temperature range of 0°F - 450°F
- Resists throw off
- Excellent adhesion
- Food Processing Acceptable H1



Description:

FG 450 is an ultra-polymer structured white food grease. It is extremely durable and strong with high loading carrying capabilities. It has excellent water and steam resistance. It has outstanding adhesion and resists throw off. This product protects against rust and has a high operating temperature range. It is safe to be used in areas with incidental food contact and around food processing areas.

For Use By:

- Bakeries
- Breweries
- Schools
- Dairies
- Hotels/Motels
- Hospitals
- Food Processing Plants
- Canneries
- Egg Processors
- Creameries
- Healthcare Facilities
- Correctional Facilities
- Edible Chemical Manufacturing
- Colleges
- Universities
- Packaging Plants
- Cosmetic Manufacturers
- Water Treatment Plants
- Culinary School
- Manufacturing Plants
- Bottling Companies
- Box Manufacturing Plants
- Industrial Plants
- Meat and Poultry Plants

Product Characteristics:

Appearance:	Aerosol. Liquefied gas.
Color:	White.
Odor:	Solvent.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Solubility:	Not available.
Flash Point:	-156.0 °F (-104.4 °C) PROPELLANT estimated.
Viscosity:	Not available.
Auto Ignition Temp:	Not available.
Flammability Limit–lower (%):	1.9 % estimated.
Flammability Limit–upper (%):	9.5 % estimated.
Specific Gravity:	2.254 estimated.
Melting/Freezing Point:	Not available.
Boiling Point/Range:	Not available.
Evaporation Rate:	Not available.
Partition Coefficient (n-octanol/water):	Not available.
Storage:	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Transportation Information:	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
UN Number:	UN1950.
Class:	2.1.
Packing Group:	Not applicable.

Directions:

Spray a thin film on surface to be lubricated. For pinpoint application, insert extension tube into actuator. Shake before use.

Pictograms:



Signal Word: DANGER.

Personal Protective Equipment Required:



DOT Placard:

