

**PRO  
CHEM**®

**ATOMIC LUBE**  
Multi-purpose, Hi-Temp,  
Extreme Pressure Grease

Product #2790



**ATOMIC LUBE** is a unique blend of petroleum oil and special synthetic polymers that combine to form an extremely water-resistant, tough lubricating film. It prevents water washout and metal-to-metal contact, even under extreme pressure or shock loading. It is a non-melting, premium quality grease specifically designed for very heavy-duty service in multiple adverse environments. Its unique formulation provides the optimum amount of additives to provide protection from rust, corrosion and oxidation. It can be used in a wide variety of applications, reducing the number of lubricants you need to have on hand.

#### FEATURES:

- Withstands extreme pressure
- Extremely water washout resistant
- Will not melt or run out
- Prevents rust and corrosion
- Excellent metal adherence
- Reduces wear
- Wide temperature range of 10°F to 525°F
- Timken OK Load (lbs): 60
- Pour Point: 10°F
- Flash Point: 525°F
- NLGI Grade 2

#### APPLICATIONS:

Ball Bearings, Bushings, Chassis, Couplings, Cranes, Gears, Roller Bearings, Screw Drives, Slides, Valve Bearings, Valve Operators, Wheel Bearings

#### DIRECTIONS FOR USE:

Remove old grease before applying this product. For ball-type grease fittings fill with this product until old grease is forced out.

#### HAZARDS IDENTIFICATION:

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). There are no known significant effects or critical hazards. See the Safety Data Sheet for more information. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**DISPOSAL AND/OR SPILL INFORMATION:** Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**STORAGE:** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**INGREDIENTS (CAS#S):** Antimony, dialkyl dithiocarbamate (15890-25-2) There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



WARNING: This product can expose you to chemicals including Ethylbenzene, Crystalline silica, respirable powder, which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### KEEP OUT OF REACH OF CHILDREN

For industrial and institutional use only not for household use or resale.  
For additional information reference the product safety data sheet (SDS).

**NET WT. 14 OZ. (397 grams)**

An Exclusive Product of: **PRO CHEM, INC.**  
1475 Bluegrass Lakes Parkway • Alpharetta, GA 30004

[www.procheminc.com](http://www.procheminc.com)  
1-800-241-8180