

PRO-KOTE #2555

All Season Surface Repellant



Features:

- Helps blades stay sharp longer
- Protects against rust and corrosion
- Reduces friction
- Will not wash off
- Leaves a hard, slippery surface of silicone on blades, shovels, etc.

Description:

PRO-KOTE is a specially formulated coating for use on the underside of lawn mowers, weed eaters, hedge trimmers, rototillers and other lawn maintenance equipment. It prevents grass clippings and dirt buildup, clogging and wear-and-tear on equipment. It helps blades stay sharper longer, making equipment last longer. This creates a barrier to protect metal, fiberglass, plastic and painted surfaces from buildup and damage.

PRO-KOTE provides a protective film, preventing asphalt from adhering to dump beds on asphalt trucks. This safe-to-use coating will not degrade the asphalt and will protect the bed from rust and corrosion.

This protective barrier resists graffiti and other stains. It prevents staining and corrosion from urine on bathroom stalls and keeps food from staining smooth restaurant surfaces* such as vinyl booths and plastic or varnished partitions. It may be applied to metal, vinyl, Formica and enamel.

**Nonfood contact surfaces only.*



Applications:

- Hedge Trimmers
- Weed Eaters
- Plastic Partitions
- Bush Hogs
- Shovels
- Lawn Mowers
- Rototillers
- Moldboards*
- Blades
- Dump Beds
- Vinyl Booths*
- Bathroom Stalls
- Rental Equipment
- Garbage Trucks

**Nonfood contact surfaces only.*

Product Characteristics:

Appearance:	Clear, colorless liquid
Odor:	Characteristic solvent odor
Viscosity, Kinematic:	<20 cSt
Specific Gravity:	0.79 g/ml
VOC Content:	>90%
Relative Density:	No data available
Solubility (water):	Insoluble in water
Flash Point:	103°F Closed cup
Storage:	Store in a well-ventilated place. Store in a cool dry area. Store locked up. Keep in original container.
Transport Information:	
DOT:	When transported by ground in non-bulk containers, this product utilizes the exception found under 49 CFR 173.150

Directions:

Spray surface to be treated and allow to dry.
For Indoor Use: Wipe off excess with clean, soft cloth to polish. Avoid overspray on flooring as surface may become slippery.
Equipment may be used immediately after application, but best results are obtained when coating is allowed to dry for 30 minutes.
For maximum protection, apply coating at the end of each work period.

Pictograms:



Signal Word: **DANGER**

Personal Protective Equipment Required:



DOT Placard:

