

# ULTIMATE RED #1793

## Red Grease



### Features:

- Extreme pressure grease
- Prevents rust
- Temperature range 40°F to 575°F
- Chemical resistant
- Holds up to high shock loads
- Sprays like a liquid
- Congeals to a thick grease
- Resists water washout
- Superior long life



### Description:

Ultimate Red is a multipurpose red grease that is easy to identify. Spraying out like a liquid, congealing to a thick grease in minutes, this product holds up very well under extreme pressures and high shock loads. Maintaining a constant viscosity over a wide range of temperatures, it also resists water and even steam washout. With a variety of uses, not only will it provide adequate lubrication, but prevents rust as well.

### Applications:

- Industrial Bearings
- Roller Chains
- Cable and Pulleys
- Electric Motor Shafts
- Hitches
- Automotive Hinges
- Fifth Wheels
- Bearing Surfaces
- Striker Plates

### Product Characteristics:

Appearance:	Red grease
Odor:	Not available
Density VOC:	2.69 lb/gal
Density:	5.73 lb/gal
VOC (%):	47.0%
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place.
<b>Transport Information:</b>	
UN Number:	UN1950
Proper Shipping Name:	Aerosols
Class:	2.1
Packing Group:	N.A.

### Directions:

1. Shake can vigorously for one minute after mixing ball begins to rattle.
2. Spray at 8 to 10 inches distance.
3. Liquid will gel almost instantly. Gel dries to a grease in several minutes.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



### DOT Placard:



### VOC Compliant:

Yes.