

# HY-VIS #1972

## Aerosol Industrial Marking Paint



### Features:

- Meets APWA standard colors
- Non-clogging
- Fast dry and safe on grass
- Inverted Tip
- Water based
- Easy shake up



### Description:

HY-VIS is a heavy-duty, water-based industrial marker with an inverted tip for easy application. This lead-free formula will not harm grass and provides a quicker dry and earlier traffic resistance. Even though it is not water soluble, this product will not wash away during rain or irrigation. Each 20 ounce can will create a crisp line up to 4" wide and 250 feet long. The specially designed cap provides a convenient marking tool that does not have to be removed and provides protection from accidental spraying.

### For Use By:

- Golf Courses
- Utility Companies
- City and County Government
- Construction Sites
- Athletic Fields
- Municipalities
- Colleges/Universities
- Landscaping/Surveying

### Applications:

- Trees
- Fields
- Pavement
- Grass
- Turf
- Sidewalk

### Product Characteristics:

	#197201	#197211	#197231
Appearance:	Aerosol	Aerosol	Aerosol
Odor:	Aromatic	Aromatic	Aromatic
Boiling Point/Range:	-44°C (-47.2°F)	-44°C (-47.2°F)	-44°C (-47.2°F)
Vapor Pressure:	Not determined	Not determined	Not determined
Explosive Limit-Lower (%):	1.7 Vol%	1.5 Vol%	1.7 Vol%
Explosive Limit-Upper (%):	10.9 Vol%	10.9 Vol%	10.9 Vol%
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)		
Flash Point:	19°C (-2.2°F)	19°C (-2.2°F)	19°C (-2.2°F)
Solubility (water):	Not determined	Not determined	Not determined
pH:	Not determined	Not determined	Not determined
Solids Content:	26%	26%	26%
Coverage:	Up to 500 linear feet		
VOC Content (less exempt solvents):	50.5%	48.7%	Not available
Water:	24.4%	22.0%	33.3 %
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
<b>Transport Information:</b>			
UN Number:	UN1950		
Proper Shipping Name:	Consumer Commodity ORM-D Aerosols, flammable		
Class:	2.1		
Packing Group:	Not available		

### Directions:

1. For best results, use when can temperature is between 40°F and 90°F (4°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Invert can and hold 4 to 6 inches (10 to 15cm) above surface to be marked. Press sprayhead to the side to actuate.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert spray-head with a gentle twisting motion.
5. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

### Dry Time:

**To Touch:** 15 minutes @72°F  
30 minutes @35°F

\*Curing/Recoat time is extended with multiple coats and excessively thick coats

### DOT Placard:



**VOC Compliancy:**  
50 State Compliant.

### Pictograms:



**Signal Word:**  
DANGER.

### Available in:

- White #197211
- Fluorescent Orange #197201
- Safety Red #197231

### Personal Protective Equipment Required:

