SAFETY DATA SHEET

PRODUCT NUMBER:	197211		COMPANY PHONE:	1-800-241-8180
PRODUCT NAME: HY-VIS WHITE		EMERGENCY TELEPHON		
PRODUCT DESCRIPTION:	Painting and Coating App	lications	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION: PRO CHEM, INC. 1475 Bluegrass Lake Alpharetta, GA 3000			INFOTRAC.	1-600-333-3033
2. Hazards Identification				
GHS CLASSIFICATION: Flammable Aerosol 1: H222 Extremely flammable aero Pressurized Gas: H280 Contains gas under pressure; i explode if heated. STOT SE 3: H335 May cause respiratory irritant. STOT RE 2: H373 May cause damage to organs throu prolonged or repeated exposure.		SIGNAL WORD: DANGER	SYMBOL:	
organs through prolor PRECAUTIONARY STATEMEN Prevention: Keep aw Pressurized container handling. Use only ou Response: IF INHAL Storage: Store locke	es. No smoking. Do not spray not breathe dust/fume/gas/mis			
B. Composition / Information			rogionalmatorialimoniatione	
Chemical Name	Shi nigrealents	CAS		Concentration % by Weight
Propane		74-98-6		17.64%
Calcium Carbonate			1317-65-3	14.79%
/M & P Naphtha		6	64742-89-8	14.06%
n-butane			106-97-8	10.36%
Titanium Dioxide Mineral Spirits			3463-67-7 64742-47-8	6.11% 5.17%
Chemical characterization: Mixtu Chemical Description: This prod				
SKIN: Remove contaminated INHALATION: Supply fresh air; cons INGESTION:	IEDICAL ATTENTION AND	ea with soap ar nts. DELAYED:	nd water.	
SPECIFIC HAZARDS ARISING Can form explosive ga SPECIAL PROTECTIVE EQUIF	wder or water spray. Fight la FROM THE CHEMICAL: as-air mixtures.	S:	vater spray.	
METHODS & MATERIALS FOR	ctive device against the effec	IUP:	t/aerosol.	

7. Handling and Storage

SAFE HANDLING:

Use only in well ventilated areas.

SAFE STORAGE & INCOMPATIBILITIES:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8. Exposure Controls / Personal Protection

Co	Components with limit values that require monitoring at the workplace:					
	Туре	Value				
	74-98-6 Propane					
	PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
	REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
	TLV (USA)	Refer to Appendix F in TLVs & BEIs book; D, EX				
	106-97-8 n-butane					
	REL (USA)	Long-term value: 1900 mg/m³, 800 ppm				
	TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)				

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Tightly sealed goggles.

Hand/Skin Protection: Nitrile gloves. The glove material must be impermeable and resistant to the substance. Respiratory Protection: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

General Hygiene Considerations: Immediately remove all soiled and contaminated clothing. Wash hands after use. Do not eat or drink while working.

9 Physical & Chemical Propertie

Appearance:	Aerosol.	Flammability(solid/gas):	Extremely flammable.
Odor:	Aromatic.	Explosive Limit-Lower (%):	1.5 Vol%
Odor Threshold:	Not determined.	Explosive Limit-Upper (%):	10.9 Vol%
pH:	Not determined.	Danger of Explosion: In use, ma	y form flammable/explosive vapour-air mixture.
Melting Point/Range:	Undetermined.	Vapor Density:	Not determined.
Boiling Point/Range:	-44°C (-47.2°F)	Vapor Pressure:	Not determined.
Viscosity:	Not determined.	Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Flash Point:	19°C (-2.2°F)	Solubility (water):	Not determined.
Evaporation Rate:	Not applicable.	Auto-Ignition Temp:	Product is not self-igniting.
VOC Content (less exempt solvents):	48.7%	Decomposition Temp:	Not determined.
Water:	22.0%	Partition Coeff(n-octanol/water):	Not determined.

Stability & Reactivity Informatio

REACTIVITY:					
Stable at normal temperatures.					
CHEMICAL STABILITY:					
Not fully evaluated.					
POSSIBILITY OF HAZARDOUS	REACTIONS:				
No dangerous reactions	s known.				
CONDITIONS TO AVOID:					
Do not allow can to exc	eed 120°F. Do not warehouse in subfreezing ter	nperatures.			
INCOMPATIBLE MATERIALS:	-				
No further relevant infor	mation available.				
HAZARDOUS DECOMPOSITION	I PRODUCTS:				
No dangerous decompo	osition products known.				
11. Toxicological Information PRIMARY ROUTE OF ENTRY:					
PRIMARY ROUTE OF ENTRY:	ogical effects: No data available. itizing effects known.				
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect.		Test Results			
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens	itizing effects known.	Test Results			
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components	itizing effects known.	Test Results			
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components 106-97-8 n-butane	itizing effects known.	Test Results			
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components 106-97-8 n-butane Acute	itizing effects known.	<u>Test Results</u> 4 h 658 mg/l			
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components 106-97-8 n-butane Acute Inhalation	itizing effects known. Species				
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components 106-97-8 n-butane Acute Inhalation LC50	itizing effects known. Species				
PRIMARY ROUTE OF ENTRY: Information on toxicol Eyes: Irritating effect. Skin: No irritant effect. Sensitization: No sens Components 106-97-8 n-butane Acute Inhalation LC50	itizing effects known. Species				

	Dermal		
	LD50	Rabbit	>10,000 mg/kg
	Inhalation		
	LC50	Rat	4h >6.82 mg/l
	logical Information		
AQUAT			
PERSIS	Hazardous for water. Do not e STENCE AND DEGRADABILIT		
		er prolonged exposure to natural weathe	ring processes.
OTHER	INFORMATION: This product does not contain	any chlorofluorocarbons (CEC's) hydro	chlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals
	(chromium, lead, cadmium) o		
BIOACO	CUMULATIVE POTENTIAL: No further relevant informatio	n availabla	
MOBILI	TY IN SOIL:	n avallable.	
OTUED	No further relevant informatio	n available.	
OTHER	ADVERSE EFFECTS: No further relevant informatio	n available	
12 Di-			
	posal Consideration SAL INSTRUCTIONS:		
	Dispose of in accordance with		not puncture, incinerate or compact. Partially empty cans must be
		ot heat or cut empty containers with elected by empty cans should be recycled.	tric or gas torches.
	Recommendation. Complete	ely empty can's should be recycled.	
14. Trai	nsportation Information		
DOT:	UN Number: UN1950		flowerschle
ADR:	UN Number: UN1950	Consumer Commodity ORM-D Aerosols	
	UN Proper Shipping Name:		
	Transport Hazard Class(es) Class: 2.1	:	
	Packing Group:		
	Special Precautions For Us EmS: F-D,S-U	er: Warning: Gases.	
	UN "Model Regulation": UN	1950 AEROSOLS, 2.1.	
15 Reg	ulatory Information		
	DERAL REGULATIONS:		
		ly hazardous substances): None of the	
		: toxic chemical listings): None of the in Act (TSCA): All hazardous ingredients fo	r this product are found on the inventory list of substances.
	Consumer Product Safety C		es with 16 CFR 1303 and does not contain more than 90 ppm of lead.
STATE	REGULATIONS:	nemicals known to cause cancer:	
	13463-67-7 titaniun	n dioxide	
	100-41-4 ethyl ben:	zene	
	•	nemicals known to cause birth defects ents in this product are listed.	or reproductive narm:
	Canadian Environmental Pr		for this product appear on the Canadian Domestic Substance List.
	EPA: None of the ingredi	ents is listed	
	er Information		
DISCLA		, information contained herein is accurate	e. However, there is no assumption of liability for the accuracy or
	completeness of the information	on contained herein. Final determination	of suitability of any material is the sole responsibility of the user. All
			tion. Although certain hazards are described herein, we cannot guarantee d in this SDS was obtained from current and reliable sources; however,
			ding its correctness or accuracy. Since the conditions or handling, storag
			r, the manufacturer will not be responsible for loss, injury, or expense

the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

SAFETY DATA SHEET

PRODUCT NUMBER:	197201		COMPANY PHONE:		1-800-241-	8180
PRODUCT NAME:	HY-VIS FLUORESCENT				1-800-535-5053	
PRODUCT DESCRIPTION:	Painting and Coating Appl			NC.		
5		ications	INFOTRAC:		1-800-535-5053	
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Par Alpharetta, GA 30004	kway				
2. Hazards Identification						
GHS CLASSIFICATION:		SIGNAL	SYMBOL:			
Flammable Aerosol 1: H222 Ex Pressurized Gas: H280 Contair explode if heated. STOT SE 3: H335 May cause r STOT RE 2: H373 May cause of	espiratory irritation.	WORD: DANGER		\diamond		
prolonged or repeated exposure						
organs through prolo PRECAUTIONARY STATEME Prevention: Keep av Pressurized containe	nged or repeated exposure. NTS: /ay from heat/sparks/open fla	mes/hot surfac after use. Do	explode if heated. May cause ces. No smoking. Do not spray not breathe dust/fume/gas/mis	on an open flame or	r other ignition s	source.
Response: IF INHAL Storage: Store locke	ED: Remove person to fresh d up. Protect from sunlight. D	air and keep o o not expose t	omfortable for breathing. Call a o temperatures exceeding 50° l/regional/national/internationa	C/122°F. Store is a v	or if you feel un well-ventilated p	well. blace.
3. Composition / Information	on Ingredients					
Chemical Name		CAS		Concentration % by Weight		eight
VM & P Naphtha		64742-89-8			18.21%	
Propane		74-98-6			15.13%	
Calcium Carbonate			1317-65-3		11.75%	
n-butane Mineral Spirits			106-97-8 64742-47-8		8.88% 3.85%	
Isobutyl Acetate		110-19-0			3.2%	
Chemical characterization: Mixt Chemical Description: This prod		nces listed be		าร.	0.270	
4. First Aid Measures						
SKIN: Remove contaminate INHALATION: Supply fresh air; cons INGESTION:	MEDICAL ATTENTION AND	ea with soap a nts. DELAYED:	nd water.			
5. Fire-Fighting Measures						
SUITABLE FIRE EXTINGUISH						
SPECIFIC HAZARDS ARISING		rger fires with	water spray.			
SPECIAL PROTECTIVE EQUI	Can form explosive gas-air mixtures. PECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: A respiratory protective device may be necessary.					
6. Accidental Release Measur PERSONAL PRECAUTIONS: Use respiratory prote METHODS & MATERIALS FO	ctive device against the effect	s of fumes/du	st/aerosol.			

7. Handling and Storage

SAFE HANDLING:

Use only in well-ventilated areas.

SAFE STORAGE & INCOMPATIBILITIES:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8. Exposure Controls / Personal Protection

Components with limit values that require monitoring at the workplace:

Туре	Value
74-98-6 Propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	Refer to Appendix F in TLVs & BEIs book; D, EX
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)
110-19-0 Isobutyl Acetate	
PEL (USA)	Long-term value: 700 mg/m³, 150 ppm
REL (USA)	Long-term value: 700 mg/m³, 150 ppm
TLV (USA)	Short-term value: 712 mg/m³, 150 ppm
	Long-term value: 238 mg/m³, 50 ppm

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Tightly sealed goggles.

Hand/Skin Protection: Nitrile gloves. The glove material must be impermeable and resistant to the substance.

Respiratory Protection: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

General Hygiene Considerations: Wash hands after use. Do not eat or drink while working.

Aerosol	Flammability(solid/gas);	Extremely flammable.
		1.7 Vol%
		10.9 Vol%
Not determined.		y form flammable/explosive vapour-air mixture.
Undetermined.	Vapor Density:	Not determined.
-44°C (-47.2°F)	Vapor Pressure:	Not determined.
Not determined.	Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
19°C (-2.2°F)	Solubility (water):	Not determined.
Not applicable.	Auto-Ignition Temp:	Product is not self-igniting.
50.5%	Decomposition Temp:	Not determined.
24.4%	Partition Coeff(n-octanol/water):	Not determined.
IONS:		
	Undetermined. -44°C (-47.2°F) Not determined. 19°C (-2.2°F) Not applicable. 50.5% 24.4%	Aromatic. Explosive Limit-Lower (%): Not determined. Explosive Limit-Upper (%): Not determined. Danger of Explosion: In use, ma Undetermined. Vapor Density:

CONDITIONS TO AVOID:

Do not allow can to exceed 120°F. Do not warehouse in subfreezing temperatures.

INCOMPATIBLE MATERIALS: No further relevant information available.

HAZARDOUS DECOMPOSITION PRODUCTS:

No dangerous decomposition products known.

11. Toxicological Information						
PRIMARY ROUTE OF ENTRY:						
Information on toxicolog	ical effects: No data available.					
Eyes: Irritating effect.						
Skin: No irritant effect.						
Sensitization: No sensitiz	ring effects known.					
Components	Species	Test Results				
106-97-8 n-butane						
Acute						
Inhalation						
LC50	Rat	4h 658 mg/l				

110-19	9-0 Isobutyl Acetate		
	Acute		
	Oral LD50	Rabbit	4,763 mg/kg
	logical Information		
AQUAT	TIC TOXICITY: Hazardous for water. Do	not ompty into drains	
PERSIS	STENCE AND DEGRADAB		
отиев	1 0	e after prolonged exposure to natural weathe	ering processes.
UTHER	INFORMATION: This product does not co	ntain any chlorofluorocarbons (CFC's), hydro	chlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals
	(chromium, lead, cadmiu	m) or chlorinated solvents.	
BIOACO	CUMULATIVE POTENTIAL No further relevant inform		
MOBILI	ITY IN SOIL:		
OTHER	No further relevant inform ADVERSE EFFECTS:	ation available.	
	No further relevant inform	ation available.	
13. Dis	posal Consideration		
	SAL INSTRUCTIONS:		
		e with local, state and federal regulations. Do Do not heat or cut empty containers with elec	not puncture, incinerate or compact. Partially empty cans must be
		pletely empty cans should be recycled.	
14. Trai	nsportation Information		
DOT:	UN Number: UN1950		
		me: Consumer Commodity ORM-D Aerosols	s, flammable.
ADR:	UN Number: UN1950 UN Proper Shipping Na	me: 1950 Aerosols.	
	Transport Hazard Class		
	Class: 2.1 Packing Group:		
	Special Precautions Fo	r User: Warning: Gases.	
	EmS: F-D,S-U UN "Model Regulation"	UN1950 AEROSOLS, 2.1.	
15 Dog	julatory Information		
	DERAL REGULATIONS:		
	SARA Section 355 (extr	emely hazardous substances): None of the	
		cific toxic chemical listings): None of the i rol Act (TSCA): All hazardous incredients for	ngredients is listed. or this product are found on the inventory list of substances.
	Consumer Product Safe		es with 16 CFR 1303 and does not contain more than 90 ppm of lead.
STATE	REGULATIONS: California Proposition (5 chemicals known to cause cancer:	
	100-41-4 ethyl	benzene	
	•	5 chemicals known to cause birth defects predients in this product are listed.	s or reproductive harm:
			for this product appear on the Canadian Domestic Substance List.
	EPA: 110-19-0 Isobu	tyl Acetate	
16. Oth	er Information		
DIOOL	To the best of our knowle		e. However, there is no assumption of liability for the accuracy or
			n of suitability of any material is the sole responsibility of the user. All ution. Although certain hazards are described herein, we cannot guarantee
			d in this SDS was obtained from current and reliable sources; however,
	the data is provided with	out any warranty, expressed or implied, regar	rding its correctness or accuracy. Since the conditions or handling, storage
			er, the manufacturer will not be responsible for loss, injury, or expense nferred, regarding the product described in this SDS shall be created or
	inferred by any statemen	t in this SDS. Various government agencies i	may have specific regulations regarding the transportation, handling,
	storage, use, or disposal	or this product, which may not be covered by	y this SDS. The user is responsible for full compliance.

SAFETY DATA SHEET

1. Product and Company Iden	tification					
PRODUCT NUMBER:	197231		COMPANY PHONE:		1-800-241-	8180
PRODUCT NAME:	HY-VIS SAFETY RED		EMERGENCY TELEPHON	NE:	1-800-535-	5053
PRODUCT DESCRIPTION:	Painting and Coating Applications		INFOTRAC:		1-800-535-5053	
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes P Alpharetta, GA 30004	arkway				
2. Hazards Identification						
GHS CLASSIFICATION:		SIGNAL	SYMBOL:			
Flammable Aerosol 1: H222 Ext Pressurized Gas: H280 Contains		WORD: DANGER				
explode if heated. STOT SE 3: H335 May cause re STOT RE 2: H373 May cause da prolonged or repeated exposure	amage to organs through				$\mathbf{\nabla}$	V
HAZARD STATEMENTS:			<u> </u>			
Extremely flammable organs through prolon PRECAUTIONARY STATEMEN	ged or repeated exposure.		explode if heated. May cause			Ū
Pressurized container handling. Use only ou Response: IF INHALI Storage: Store locked	: Do not pierce or burn, eve tdoors or in a well-ventilate ED: Remove person to fres I up. Protect from sunlight.	en after use. Do d area. h air and keep c Do not expose t	not breathe dust/fume/gas/mis omfortable for breathing. Call a o temperatures exceeding 50°(t/vapors/spray. Wa a poison center/doc C/122°F. Store is a	sh hands thoroug	ghly after well.
Disposal: Dispose of	contents/container in accor	rdance with loca	l/regional/national/international	regulations.		
3. Composition / Information of	on Ingredients					
Chemical Name		CAS		Concentration % by Weight		eight
VM & P Naphtha		64742-89-8		16.15%		
Propane			74-98-6		15.13%	
Calcium Carbonate			1317-65-3 106-97-8		12.79% 8.88%	
n-butane Mineral Spirits			64742-47-8		4.17%	
Chemical characterization: Mixtu	Ires		04742-47-0		4.1770	
Chemical Description: This prod		tances listed be	ow with nonhazardous additior	IS.		
4. First Aid Measures						
EMERGENCY OVERVIEW:						
	several minutes under runr					
	d clothing. Wash exposed a	irea with soap a	nd water.			
INHALATION: Supply fresh air: cons	ult doctor in case of compla	aints				
INGESTION:		anto.				
Rinse mouth with wate MOST IMPORTANT SYMPTON Dizziness.	er. Do not induce vomiting. IS/EFFECTS, ACUTE AND	DELAYED:				
INDICATION OF IMMEDIATE N No further relevant inf		D SPECIAL TRI	EATMENT NEEDED:			
5. Fire-Fighting Measures						
SUITABLE FIRE EXTINGUISHING MEDIA:						
	CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:					
Can form explosive gas-air mixtures. SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: A respiratory protective device may be necessary.						
6. Accidental Release Measure	25					
PERSONAL PRECAUTIONS:						
	R CONTAINMENT & CLEA		e respiratory protective device	against the effects	of fumes/dust/ae	erosol.

7. Handling and Storage

SAFE HANDLING:

Use only in well-ventilated areas.

SAFE STORAGE & INCOMPATIBILITIES:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8. Exposure Controls / Personal Protection

Components with limit values that require monitoring at the workplace:					
Туре	Value				
74-98-6 Propane					
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
TLV (USA)	Refer to Appendix F in TLVs & BEIs book; D, EX				
106-97-8 n-butane					
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm				
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)				
	Type 74-98-6 Propane PEL (USA) REL (USA) TLV (USA) 106-97-8 n-butane REL (USA)				

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Tightly sealed goggles.

Hand/Skin Protection: Nitrile gloves. The glove material must be impermeable and resistant to the substance. Respiratory Protection: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

General Hygiene Considerations: Keep away from foodstuffs and animal feed. Wash hands after use. Do not eat or drink while working.

9. Physical & Chemical Properties

Appearance:	Aerosol.	Flammability(solid/gas):	Extremely flammable.
Odor:	Aromatic.	Explosive Limit-Lower (%):	1.7 Vol%
Odor Threshold:	Not determined.	Explosive Limit-Upper (%):	10.9 Vol%
pH:	Not determined.	Danger of Explosion: In use, r	may form flammable/explosive vapour-air mixture.
Melting Point/Range:	Undetermined.	Vapor Density:	Not determined.
Boiling Point/Range:	-44°C (-47.2°F)	Vapor Pressure:	Not determined.
Viscosity:	Not determined.	Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Flash Point:	-19°C (-2.2°F)	Solubility:	Not determined.
Evaporation Rate:	Not applicable.	Auto-Ignition Temp:	Product is not self-igniting.
Partition Coeff(n-octanol/water):	Not determined.	Decomposition Temp:	Not determined.
Water:	33.3%		

10. Stability & Reactivity Information

To. Stability & Reactivity informati	UII		
REACTIVITY:			
Stable at normal temperat	ures.		
CHEMICAL STABILITY:			
Not fully evaluated.			
POSSIBILITY OF HAZARDOUS RE	ACTIONS:		
No dangerous reactions k	nown.		
CONDITIONS TO AVOID:			
	d 120°F. Do not warehouse in subfreezing ter	nperatures.	
INCOMPATIBLE MATERIALS:			
No further relevant informa			
HAZARDOUS DECOMPOSITION P			
No dangerous decomposit	ion products known.		
44 Tania da via di lufa una dia u			
11. Toxicological Information			
PRIMARY ROUTE OF ENTRY:			
	jical effects: No data available.		
Eyes: Irritating effect.			
Skin: No irritant effect.			
Sensitization: No sensitiz			
Components	Species	Test Results	
106-97-8 n-butane			
Acute			
Inhalation			
LC50	Rat	4h 658 mg/l	
12. Ecological Information			
AQUATIC TOXICITY:			

Hazardous for water. Do not empty into drains.

PERSI	STENCE AND DEGRADABILITY: The product is degradable after prolonged exposure to natural weathering processes.
BIOAC	CUMULATIVE POTENTIAL:
	No further relevant information available.
MOBIL	ITY IN SOIL: No further relevant information available.
OTHER	RADVERSE EFFECTS:
	No further relevant information available.
13 Dis	posal Consideration
	SAL INSTRUCTIONS:
	Dispose of in accordance with local, state and federal regulations. Do not puncture, incinerate or compact. Partially empty cans must be
	disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
	Recommendation: Completely empty cans should be recycled.
14. Tra	nsportation Information
DOT:	UN Number: UN1950
	UN Proper Shipping Name: Consumer Commodity ORM-D Aerosols, flammable.
ADR:	UN Number: UN1950 UN Proper Shipping Name: 1950 Aerosols.
	Transport Hazard Class(es):
	Class: 2.1
	Packing Group:
	Special Precautions For User: Warning: Gases. EmS: F-D.S-U
	UN "Model Regulation": UN1950 Aersols, 2.1.
15 Por	gulatory Information
	DERAL REGULATIONS:
00.1	SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed.
	SARA Section 313 (Specific toxic chemical listings): None of the ingredients is listed.
	Toxic Substances Control Act (TSCA): All hazardous ingredients for this product are found on the inventory list of substances. Consumer Product Safety Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
STATE	REGULATIONS:
	California Proposition 65 chemicals known to cause cancer:
	100-41-4 ethyl benzene.
	California Proposition 65 chemicals known to cause birth defects or reproductive harm: None of the ingredients in this product are listed.
	Canadian Environmental Protection Act: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
	WHMIS Symbols for Canada: A - Compressed gas.
	EPA: None of the ingredients is listed.
16. Oth	ner Information
DISCL	AIMER:
	To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or
	completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee
	that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however,
	the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage
	and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense
	and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling,