

SPRAY-N-SEAL - WHITE #1453

Aerosol Roof Patch and Leak Sealer



Features:

- Multipurpose sealant
- Coating remains flexible and will not crack or peel
- Resists water
- Protects against UV rays
- Thermoplastic base
- Can be painted over with latex or oil paints
- Resists heat up to 250°F

Description:

SPRAY-N-SEAL is a versatile sealant that provides durable, flexible, rubberized film. It protects against harmful UV rays and resists heat up to 250°F. Additionally, it remains pliable and will not crack or peel, even in cold temperatures. This product contains a thermoplastic elastomer base that makes it highly effective in sealing leaks around windows, doors, roofs and air vents. Its water resistant properties and wide temperature range make it perfect for use on outdoor applications.



For Use On:

- Skylights
- Windows
- Concrete
- Flashings
- Gutters and Shingles
- Lashings
- Air Vents
- Driveway and Sideway Cracks
- Roofs on Campers or Buses
- Semi-Trailers
- Houses
- PVC

For Use By:

- Utility Companies
- Colleges/Universities
- Municipalities
- Warehouses
- Housing Authorities
- Parks and Recreation
- Bus Fleets
- DOT

Product Characteristics:

Appearance:	Aerosol
Odor:	Aromatic
Boiling Point:	-110°C (-166°F)
Vapor Pressure:	Not determined
Solubility (water):	Not determined
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Flash Point:	-19°C (-2.2°F)
VOC Content (less exempt solvents):	49.1%
Water:	0.0%
pH:	Not determined
Explosive Limit-Lower (%):	1.1 Vol%
Explosive Limit-Upper (%):	10.9 Vol%
Shelf Life:	2 years
Coverage:	Up to 18 square feet
Solids Content:	13%
MIR Value:	0.86, cannot exceed 0.95
Storage:	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Consumer Commodity ORM-D Aerosols, flammable.
Class:	2.1
Packing Group:	--

Directions:

1. Surface must be clean and dry before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
 2. Shake can at least one minute after rattle is heard and occasionally during use.
 3. Spray surface with steady even strokes at a distance of 2 to 10 inches (5 to 25cm). Multiple coats may be applied, allowing 20 to 30 minutes between coats.
 4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
 5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.
- Additional Information: This product leaves a slightly bubbly film. When covering a broad area it is recommended that two coats be applied to ensure a non-porous final coating. Allow first coat to dry to touch (about 8-10 minutes) before applying the second and final coat.

Dry Time*:

- To touch 10 minutes
- To topcoat 30 minutes
- *At 72F, 50% humidity, 1.5 mil thickness
- **Curing/Recoat time is extended with multiple coats and excessively thick coats**

Gloss*:

Flat, <15

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

Yes.