

STRIP MASTER - AEROSOL #1580

Aerosol Paint Remover



Features:

- Methylene chloride-free
- Works quickly
- Removes a wide range of paints and sealers from metal, concrete and wood
- Gel-based formula clings to vertical surfaces for longer contact time
- Blistered paint can be scraped off or rinsed off with water
- Blistering will start to occur in 3-4 minutes of application



Description:

STRIP MASTER AEROSOL is a gel-based paint remover. It penetrates deep to remove paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials from all surfaces. With a methylene chloride-free formula, STRIP MASTER AEROSOL is the safer alternative for paint removal. It begins stripping and blistering paint 3-4 minutes after application. After product is done blistering, simply scrape off or rinse with water to remove.

For Use By:

- Paint Shops
- Factories
- Auto Dealers
- Motels/Hotels
- Hospitals
- Offices
- Maintenance Departments
- Furniture Rebuilders
- Sign Builders

Applications:

- Paint
- Lacquers
- Varnish
- Labels
- Shellac
- Enamel
- Carbon Deposits
- Silicone
- Simulated Wood Paneling

Product Characteristics:

Appearance:	Blue green spray
Odor:	Acetone odor
Boiling Point/Range:	Not determined
Vapor Pressure:	Not determined
Solubility(ies):	Miscible
Relative Density:	0.95 - 0.98
Flash Point:	Not determined
pH:	Not applicable
Viscosity:	100 - 300 cps
Flammability(solid/gas):	Extremely flammable aerosol
Storage:	Store in a well-ventilated place. Keep container tightly closed. Obtain, read and follow all safety instructions before use.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, Ltd. Qty.
Class:	2.1
Packing Group:	Not applicable

Directions:

Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

Pictograms:



Signal Word:
DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliancy:
Not available.

STRIP MASTER #2580

Paint Remover



Features:

- Methylene chloride-free
- Works quickly
- Gel-based formula clings to vertical surfaces for longer contact time
- Removes a wide range of paints and sealers from metal, concrete and wood
- Blistering will start to occur in 3-4 minutes of application

Description:

STRIP MASTER is a gel-based paint remover that quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. STRIP MASTER will not run, allowing the product to stay on longer and provide maximum results. The methylene chloride-free formula is a safer alternative to paint removal, but still performs to meet industry expectations.



For Use By:

- Auto Dealers
- Paint Shops
- Sign Builders
- Factories
- Painters
- Schools
- Motels/Hotels
- Hospitals
- Offices
- Maintenance Departments
- Engine Rebuilders
- Furniture Refinishers

For Use On:

- Metal Parts
- Ceramic/Plaster
- Engine Parts
- Wood
- Glass
- Tile
- Concrete
- Valve Seals
- Paint Guns
- Paper
- Stone and Masonry
- Cylinders

Applications:

- Paint
- Lacquer and Varnish
- Gaskets
- Shellac
- Enamel
- Silicone
- Carbon Deposits
- Decals and Glue
- Simulated Wood Paneling

Product Characteristics:

Appearance:	Clear blue green liquid
Odor:	Acetone odor
Boiling Point/Range:	Not determined
Vapor Pressure:	Not determined
Solubility (water):	100% water
Relative Density:	0.95 - 0.98
Flash Point:	Not determined
pH:	Not applicable
Viscosity:	1000 - 1500 cps
Flammability(solid/gas):	Highly flammable liquid
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.
Transport Information:	
UN Number:	UN1993
Proper Shipping Name:	For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S., (Acetone, Dioxolane)
Class:	3
Packing Group:	II

Directions:

Pre-clean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

Yes.

SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	158001	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	STRIP MASTER - AEROSOL	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Paint Remover	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION:

Flammable Aerosol: Category 1
Gases Under Pressure: Liquefied Gas Eye Damage: Category 1
Skin Irritant: Category 2
Specific Target Organ Toxicity (Single Exposure): Category 3
Specific Target Organ Toxicity (Repeated Exposure): Category 2
Reproductive Toxicity: Category 2

SIGNAL WORD:
DANGER

SYMBOL:



HAZARD STATEMENTS:

Extremely flammable aerosol. Pressurized container: may explode if heated Causes serious eye damage. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Take off Immediately all contaminated clothing. Immediately rinse with water for several minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical help. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. Specific treatment (see First Aid Measures section of this SDS). IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Use only outdoors or in a well-ventilated place.

Storage: Store in a well-ventilated place. Keep container tightly closed. Obtain, read and follow all safety instructions before use. If exposed or concerned, get medical advice.

Disposal: Dispose of contents and container in accordance with local, state and national regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

No additional information available.

ADDITIONAL INFORMATION:

Not applicable.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Acetone	67-64-1	30-40%
1,3-Dioxolane	646-06-0	15-30%
Propane/n-Butane	68476-86-8	10-20%
Methanolamine	141-43-5	1-5%
Isopropylidene glycol	100-79-8	1-5%

4. First Aid Measures

EMERGENCY OVERVIEW:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

INHALATION:

Move to fresh air. If breathing is difficult, administer oxygen. If heartbeat or breathing seem irregular, seek immediate medical attention.

INGESTION:

Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS:

Causes serious damage to eyes. Causes skin irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness.

CHRONIC HEALTH HAZARDS:

Causes damage to organs through prolonged and repeated exposure. May cause reproductive effects affecting fertility and/or development of the unborn child.

NOTE TO PHYSICIAN:

There is no specific treatment regimen. Treatment of overexposure should be directed toward the control of symptoms and the clinical condition of the patient.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA:

Dry chemical, foam or carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA:

Water jets or streams may spread fire.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear NIOSH approved Self-Contained Breathing Apparatus with a full-face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

EXTREMELY FLAMMABLE AEROSOL. Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray.

HAZARDOUS COMBUSTION PRODUCTS:

Oxides of carbon

6. Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT:

Refer to Section VIII for proper Personal Protective Equipment.

SPILL: Contain spill, eliminate ignition sources and ventilate area. Prevent spill from entering sewers, storm drains, and natural waterways. Use non-combustible material like vermiculite, sand or earth for larger spills.

WASTE DISPOSAL:

Dispose of in accordance with local, state and federal regulations.

RCRA STATUS:

Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

7. Handling and Storage

HANDLING AND STORAGE:

Store in a cool, dry area. Keep away heat, open flames, or other sources of ignition. Do not reuse empty container. Keep out of reach of children.

OTHER PRECAUTIONS:

Keep out of the reach of children. Follow label directions exactly. Avoid contact with eyes, skin or clothing.

INCOMPATIBILITY:

Strong acids.

8. Exposure Controls / Personal Protection

Hazardous Ingredient	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
1,3-Dioxolane	Not established	20 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Methanolamine	3 ppm	3 ppm
Isopropylidene glycol	Not established	Not established

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves.



Eye/Face Protection: Safety glasses.

Skin Protection: Chemical resistant gloves.

Respiratory Protection: Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

General Hygiene Considerations: Wash hands thoroughly with soap and water after using. If clothing becomes contaminated, remove and wash immediately.

APPROPRIATE ENGINEERING CONTROLS:

Local ventilation/exhaust adequate to maintain vapor concentrations below PEL/TLV.

9. Physical & Chemical Properties

Appearance:	Blue green spray.	Flammability(solid/gas):	Extremely Flammable Aerosol.
Odor:	Acetone odor.	Flammability Limit-lower (%):	Not determined.
Odor Threshold:	Not determined.	Flammability Limit-upper (%):	Not determined.
pH:	Not applicable.	Explosive Limit-Lower (%):	Not determined.
Melting/Freezing Point:	Not determined.	Explosive Limit-Upper (%):	Not determined.
Boiling Point/Range:	Not determined.	Vapor Density (AIR=1):	Not determined.
Viscosity:	100-300 cps	Vapor Pressure (mm Hg):	Not determined.
Flash Point:	Not determined.	Relative Density (H20=1):	0.95 - 0.98
Evaporation Rate:	Not determined.	Solubility(ies):	Miscible.
Decomposition Temp:	Not determined.	Auto-Ignition Temp:	Not determined.
Partition Coeff(n-octanol/water):	Not determined.		

10. Stability & Reactivity Information

REACTIVITY:

Chemically active metals and acids.

CHEMICAL STABILITY:

Stable.

POSSIBILITY OF HAZARDOUS REACTIONS:

None known.

CONDITIONS TO AVOID:

Avoid incompatible materials.

INCOMPATIBLE MATERIALS:

Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon.

11. Toxicological Information**TOXICOLOGICAL INFORMATION:**

Acetone (67-64-1): LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8h) 50100 mg/m3; LC50 (Inhalation, Mouse, 4h) 44,000 mg/m3.

Propane (74-98-6): LC50 (Inhalation, Rat, 4h) 658 mg/L.

n-Butane (106-97-8): LC50 (Inhalation, Rat, 4h) 30957 mg/m3.

Monoethanolamine (141-43-5): LD50 (Oral, Rat) 1720 mg/kg; LD50 (Dermal, Rabbit) 1025 mg/kg; LC50.

Isopropylidene glycol (100-79-8): LD50 (Oral, Rat) 7000 mg/kg; LD50 (Dermal, Rat) 2000 mg/kg; LC50 (Inhalation, Rat, 4h aerosol) >5.11 mg/L

PRIMARY ROUTE OF ENTRY: Eyes, Ingestion, Inhalation, Skin

Eyes: Causes serious eye damage.

Skin: Causes irritation.

Inhalation: Causes dizziness, headaches, nausea.

Ingestion: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.

ACUTE TOXICITY:

Causes serious damage to eyes. Causes skin irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness

MEDICAL CONDITION AGGRAVATED:

May aggravate pre-existing conditions of the liver, kidneys and skin.

CARCINOGENICITY:

OSHA: Not classified. **ACGIH:** No **NTP:** No **IARC:** No **OTHER:** No

CHRONIC HEALTH HAZARDS:

Causes damage to organs through prolonged and repeated exposure. May cause reproductive effects affecting fertility and/or development of the unborn child.

12. Ecological Information**ECOTOXICITY:**

Acetone (67-64-1): LC50 (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC50 (*Daphnia magna*, 48h) 6100 mg/L; EC50 (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC50 (*Pseudomonas putida*, 16h) 1700 mg/L.

PERSISTENCE AND DEGRADABILITY:

Not determined.

BIOACCUMULATIVE POTENTIAL:

Not determined.

MOBILITY IN SOIL:

Not determined.

OTHER ADVERSE EFFECTS:

Avoid release to the environment.

13. Disposal Consideration

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261)

14. Transportation Information

DOT: **UN Number:** UN1950

UN Proper Shipping Name: Aerosols, Ltd. Qty.

Transport Hazard Class(es):

Class: 2.1

Packing Group: Not applicable.

IATA: **UN Number:** UN1950

UN Proper Shipping Name: Aerosols, flammable.

Transport Hazard Class(es):

Class: 2.1

Packing Group: Not applicable.

IMDG: **SHIPPING BY WATER:**

UN Number: UN1950

UN Proper Shipping Name: Aerosols.

Transport Hazard Class(es):

Class: 2.1

Packing Group: Not applicable.

Environmental Hazards Water: N/A

15. Regulatory Information

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):

Acetone (67-64-1) Reportable Quantity = 5,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health, Fire, Pressure.

SARA 313 REPORTABLE INGREDIENTS: **Acetone** (67-64-1).

STATE REGULATIONS:

Acetone (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA.

1,3-Dioxolane (646-06-0): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, MN, NJ, PA.

Dimethyl carbonate (616-38-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, PA.

INTERNATIONAL REGULATIONS:

Acetone (67-64-1) Australia, Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

VOLATILE ORGANIC COMPOUNDS (VOC): 48%

16. Other Information

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	258007	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	STRIP MASTER	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Paint Remover	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable Liquid: Category 2 Eye Irritant: Category 1 Specific Target Organ Toxicity (Single Exposure): Category 3 Skin Corrosive: Category 1 Specific Target Organ Toxicity (Repeated Exposure): Category 1	SIGNAL WORD: DANGER	SYMBOL:				
--	--------------------------------------	----------------	---	---	---	---

HAZARD STATEMENTS:

Highly flammable liquid and vapor. Causes severe skin burns and serious eye damage. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection/protective clothing.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use alcohol resistant foam, Carbon dioxide or dry powder. Do not breathe dusts or mists. Wash hands with soap and water thoroughly after handling. Wash contaminated clothing before reuse. IF INHALED: remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Use only outdoors or in a well-ventilated area. Call a poison center/doctor if you feel unwell. Do not eat, drink or smoke when using this product. Get medical advice/attention if you feel unwell.

Storage: Store locked up in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local, state and federal law.

HAZARDS NOT OTHERWISE SPECIFIED:

No applicable.

ADDITIONAL INFORMATION:

Not applicable.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Acetone	67-64-1	35-45%
1,3-Dioxolane	646-06-0	20-40%
Methanolamine	141-43-5	1-10%

4. First Aid Measures

EMERGENCY OVERVIEW:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

INHALATION:

Move to fresh air. If breathing is difficult, administer oxygen. If heartbeat or breathing seems irregular seek immediate medical attention.

INGESTION:

Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Acute: Eyes: Serious damage, redness, tearing, blurred vision

Skin: Severe burns, defatting and dermatitis

Inhalation: Irritation

Chronic kidney and liver damage possible.

Chronic: Repeated or prolonged exposure may cause liver and kidney damage. These effects have not been observed in humans.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Note to Physician: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Dry chemical, foam or Carbon Dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Not applicable.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Highly flammable. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

Oxides of carbon.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Wear NIOSH approved Self Contained Breathing Apparatus (SCBA) with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Refer to Section 8 for proper Personal Protective Equipment.

METHODS & MATERIALS FOR CONTAINMENT & CLEANUP:

Spill: Contain spill, eliminate ignition sources and ventilate area. Prevent spill from entering sewers, storm drains and natural waterways. Use non-combustible material like vermiculite, sand or earth for larger spills.

Waste Disposal: Dispose of in accordance with federal, state and local regulations. Do not reuse container and recycle or place in trash collection. Drums and pails should be offered for recycling.

RCRA Status: Product should be fully characterized prior to disposal (40 CFR 261).

7. Handling and Storage

SAFE HANDLING:

Keep out of the reach of children. Follow label directions exactly. Avoid contact with eyes, skin or clothing.

SAFE STORAGE & INCOMPATIBILITIES:

Do not use or store near heat or open flame. Store in cool dry place. Follow all label instructions.

Incompatibilities: Strong acids.

8. Exposure Controls / Personal Protection

Hazardous Ingredient	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
1,3-Dioxolane	Not established	Not established
Methanolamine	3 ppm	3 ppm

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves.



Eye/Face Protection: Safety glasses.

Skin Protection: Chemical resistant gloves.

Respiratory Protection: Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (Section 8) are exceeded.

General Hygiene Considerations: Wash hands thoroughly with soap and water after using. If clothing becomes contaminated remove and wash immediately.

APPROPRIATE ENGINEERING CONTROLS:

Local ventilation/exhaust adequate to maintain vapor concentrations below PEL/TLV

9. Physical & Chemical Properties

Appearance:	Clear blue green liquid.	Flammability(solid/gas):	Highly Flammable Liquid.
Odor:	Acetone odor.	Flammability Limit-lower (%):	Not determined.
Odor Threshold:	Not determined.	Flammability Limit-upper (%):	Not determined.
pH:	Not applicable.	Explosive Limit-Lower (%):	Not determined.
Melting/Freezing Point:	Not determined.	Explosive Limit-Upper (%):	Not determined.
Boiling Point/Range:	Not determined.	Vapor Density:	Not determined.
Viscosity:	1000 - 1500 cps	Vapor Pressure:	Not determined.
Flash Point:	Not determined.	Relative Density:	0.95 - 0.98
Evaporation Rate:	Not determined.	Solubility (water):	100% water.
Decomposition Temp:	Not determined.	Auto-Ignition Temp:	Not determined.
Partition Coeff(n-octanol/water):	Not determined.		

10. Stability & Reactivity Information

REACTIVITY:

Chemically active metals and acids.

CHEMICAL STABILITY:

Stable.

POSSIBILITY OF HAZARDOUS REACTIONS:

None known.

CONDITIONS TO AVOID:

Avoid incompatibles.

INCOMPATIBLE MATERIALS:

Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon.

11. Toxicological Information**PRIMARY ROUTE OF ENTRY:** Eyes, Ingestion, Inhalation, Skin**Eyes:** Causes serious eye damage.**Skin:** Causes severe burns.**Inhalation:** Causes dizziness, headaches, nausea.**Ingestion:** Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.**ACUTE TOXICITY:**

Eyes: serious damage, redness, tearing, blurred vision

Skin: severe burns, defatting and dermatitis

Inhalation: Irritation

Chronic kidney and liver damage possible.

Components	Species	Test Results
Acetone (67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	20000 mg/kg
<i>Oral</i>		
LD50	Rabbit	5340 mg/kg

MEDICAL CONDITION AGGRAVATED:

May aggravate pre-existing conditions of the liver, kidneys and skin.

CARCINOGENICITY:**OSHA:** No **ACGIH:** No **NTP:** No **IARC:** No **OTHER:** No**CHRONIC EFFECTS:**

Repeated or prolonged exposure may cause liver and kidney damage. These effects have not been observed in humans.

12. Ecological Information**ECOTOXICITY:**

Components	Species	Test Results
Acetone (67-64-1)		
Aquatic		
Fish LC50	Trout, 96hr	5540 mg/L
Fish LC50	Bluegill, 96hr	8300 mg/L
Fish LC50	Fathead Minnow, 96hr	7500 mg/L

PERSISTENCE AND DEGRADABILITY:

Not determined.

BIOACCUMULATIVE POTENTIAL:

This product is not expected to bioaccumulate.

MOBILITY IN SOIL:

Not determined.

OTHER ADVERSE EFFECTS:

Not known.

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Dispose of in accordance with federal, state and local regulations. Do not reuse container and recycle or place in trash collection. Drums and pails should be offered for recycling. RCRA STATUS: Product should be fully characterized prior to disposal (40 CFR 261).

14. Transportation Information

DOT:	UN Number: UN1993 UN Proper Shipping Name: For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S., (Acetone, Dioxolane) Transport Hazard Class(es): Class: 3 Packing Group: II
IATA:	UN Number: UN1993 UN Proper Shipping Name: For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S., (Acetone, Dioxolane) Transport Hazard Class(es): Class: 3 Packing Group: II
IMDG:	UN Number: UN1993 UN Proper Shipping Name: For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S., (Acetone, Dioxolane) Transport Hazard Class(es): Class: 3 Packing Group: II Environmental Hazards Water: Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

TSCA Status: All Chemicals are listed or exempt.

CERCLA (Comprehensive Response Compensation and Liability Act): None.

SARA 311/312 Hazardous chemical: Acute. Serious eye damage. Flammable.

SARA 313 (TRI reporting): None.

US STATE REGULATIONS:

Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, RTK - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone CA Prop 65: This product can expose you to chemicals including Methanol, which is known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P5Warnings.ca.gov.

INTERNATIONAL REGULATIONS:

All components are listed or exempted.

VOLATILE ORGANIC COMPOUNDS (VOC): 42%

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

Strip Master is a gel-based paint remover that quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal.

FOR USE BY: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices.

FOR USE ON: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

DIRECTIONS FOR USE: Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

MODO DE EMPLEO: Agítese bien antes de usar. Mantenga el bote entre 8 y 10 pulgadas de la superficie que se va a tratar. Aplique una capa mediana o gruesa según se necesite. Una capa gruesa acelerará la reacción. La descascaración toma tres minutos pero puede tardarse hasta veinte minutos dependiendo en el material que se está tratando. Permita que el producto termine el descascaramiento antes de comenzar a remover.

DANGER: Extremely flammable aerosol. Contains gas under pressure; May explode if heated. Causes serious eye damage. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical help. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Use only outdoors or in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed. Obtain, read and follow all safety instructions before use. If exposed or concerned, get medical advice. Dispose of contents and container in accordance with local, state, and national regulations.

PELIGRO: Aerosol extremadamente inflamable. Contiene gas bajo presión; Puede explotar si se calienta. Causa daño ocular grave. Provoca irritación de la piel. Puede causar somnolencia o mareos. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas. Se sospecha que daña la fertilidad o daña al feto. Mantener alejado del calor, chispas, llamas abiertas y superficies calientes. -No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Envase a presión: No perforar ni quemar, incluso después de su uso. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. No respirar el polvo/el humo/el gas/la niebla/los vapores/el aerosol. Lávese bien las manos y la cara después de la manipulación. Utilice guantes/ropa protectora/protección para los ojos/protección facial. EN CASO DE INGESTIÓN: Enjuagar la boca. No induzca el vomito. EN CASO DE CONTACTO CON LA PIEL: Quitar inmediatamente toda la ropa contaminada. Enjuague inmediatamente con agua durante varios minutos. Lave la ropa contaminada antes de volver a usarla. Si se produce irritación de la piel: busque ayuda médica. EN CASO DE INHALACIÓN: Lleve a la persona al aire libre y manténgala cómoda para respirar. Obtenga ayuda médica de emergencia de inmediato. EN CASO DE CONTACTO CON LOS OJOS: Enjuague inmediatamente con agua durante varios minutos. Quite los lentes de contacto si los tiene y es fácil de hacer. Continúe enjuagando. Úselo únicamente al aire libre o en un lugar bien ventilado. Almacenar en un lugar bien ventilado. Mantener el contenedor bien cerrado. Obtenga, lea y siga todas las instrucciones de seguridad antes de su uso. Si está expuesto o preocupado, busque atención médica. Deseche el contenido y el contenedor de acuerdo con las regulaciones locales, estatales y nacionales.

An Exclusive Product of PRO CHEM, INC.
1475 Bluegrass Lakes Parkway, Alpharetta, GA 30004
TO REORDER CALL: 1-800-241-8180
Procheminc.com

CONTAINS (CAS#): Acetone (67-64-1), Dioxolane (646-06-0), Propane/n-Butane (68476-86-8), Monoethanolamine (141-43-5), Isopropylidene Glycol (100-79-8).

Read the Safety Data Sheet (SDS) before using this product.

For Commercial/Industrial Use Only.



Product Code: 158001



PRO CHEM STRIP MASTER

**PAINT REMOVER
REMOVEDOR DE PINTURA**

*Methylene Chloride-Free
Multi-Surface*

*Removes a Wide Range of
Paints and Sealers from Metal,
Concrete and Wood*

DANGER / PELIGRO

**EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.**

**AEROSOL EXTREMADAMENTE INFLAMABLE.
CONTIENE GAS A PRESIÓN;
PUEDE EXPLOTAR SI SE CALIENTA.**

NET WT. 11 OZ. (312 g)

**PRO
CHEM**

STRIP MASTER

PAINT REMOVER REMOVEDOR DE PINTURA

*Methylene Chloride-Free
Multi-Surface*

*Removes a Wide Range of
Paints and Sealers from Metal,
Concrete and Wood*

DANGER/PELIGRO

**HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES
SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.
LÍQUIDO Y VAPORES ALTAMENTE INFLAMABLES.
CAUSA QUEMADURAS GRAVES EN LA PIEL Y
LESIONES OCULARES GRAVES.**

NET CONTENTS: ONE GALLON (3.8 L)

Gel-based paint remover that quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal. FOR USE BY: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. FOR USE ON: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

DIRECTIONS FOR USE: Preclean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically.

MODO DE EMPLEO: Limpie las acumulaciones de grasa y suciedad con un detergente de alto rendimiento. Permita que se seque. Aplique el compuesto sin diluir como una sola capa completa. Permita que actúe hasta que la pintura se llene de arrugas o burbujas. Enjuague con agua o solvente. Use una espátula o cepillo de alambre en las grietas o en acumulaciones muy pesadas. En pisos pintados, un enjuagador puede ser usado para mover el compuesto de un lado a otro cuando este terminado; así el compuesto puede ser rehusado. Añada nuevo producto periódicamente.

DANGER: Highly flammable liquid and vapor. Causes severe skin burns and serious eye damage. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection/protective clothing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use alcohol resistant foam, carbon dioxide, or dry powder. Store locked up in a well-ventilated place. Keep cool. Dispose of contents/container in

accordance with local, state and federal law. Do not breathe dusts or mists. Wash hands with soap and water thoroughly after handling. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Use only outdoors or in a well-ventilated area. Call a poison center/doctor if you feel unwell. Do not eat, drink or smoke when using this product. Get medical advice/attention if you feel unwell.

PELIGRO: Líquido y vapores altamente inflamables. Causa quemaduras graves en la piel y lesiones oculares graves. Puede causar somnolencia o mareos. Provoca daños en los órganos tras exposiciones prolongadas o repetidas. Mantener alejado del calor, chispas, llamas abiertas y superficies calientes. -No fumar. Mantener el contenedor bien cerrado. Contenedor de tierra/bond y equipo receptor. Use equipo eléctrico/de ventilación/iluminación a prueba de explosión. Use solo herramientas que no produzcan chispas. Tomar medidas de precaución contra las descargas electrostáticas. Use guantes protectores/protección para los ojos/protección para la cara/ropa protectora. Si está en la piel (o cabello): Quítese inmediatamente toda la ropa contaminada. Enjuagar la piel con agua/ducharse. En caso de incendio: Utilice espuma resistente al alcohol, dióxido de carbono o polvo seco. Almacene bajo llave en un lugar bien ventilado. Mantener la calma. Deseche el contenido/contenedor de acuerdo con las leyes locales, estatales y federales. No respirar polvos o nieblas. Lávese bien las manos con agua y jabón después de manipular. Lave la ropa contaminada antes de volverla a usar. Si se inhala: Saque a la persona al aire fresco y manténgase cómodo para respirar. Llame inmediatamente a un centro de envenenamiento/médico. Si en los ojos: Enjuague cuidadosamente con agua durante varios minutos. Quítese las lentes de contacto, si están presentes y son fáciles de hacer. Continuar enjuagando. Use solo al aire libre o en un área bien ventilada. Llame a un centro de toxicología/médico si no se siente bien. No coma, beba ni fume cuando use este producto. Obtenga asesoramiento/atención médica si no se siente bien.

CONTAINS (CAS#): Dioxolane (646-06-0), Acetone (67-64-1), Dimethyl Carbonate (616-38-6), Monethanolamine (141-43-5), Isopropylidene Glycol (100-79-8).



Sold By:
An Exclusive Product of PRO CHEM, INC.
1475 Bluegrass Lakes Parkway, Alpharetta, GA 30004
TO REORDER CALL: 1-800-241-8180
www.procheminc.com

Product Code: 258007

