

MARK OUT #1221

Aerosol Vandal Mark & Graffiti Remover



Features:

- Dissolves marks fast without affecting substrates
- Thick gel adheres to all vertical surfaces
- Effective on nearly all forms of graffiti
- Contains no methylene chloride
- Use indoors and outdoors
- Effective on porous and non-porous surfaces



Description:

MARK OUT is a non-chlorinated, heavy-duty, thick clinging gel that provides extended surface contact cleaning time. Cuts quickly through stubborn vandal marks without running or dripping. Effective on porous and non-porous surfaces. Removes spray paint, lipstick, tar, ink, marker, pen, crayons and more. Safe on brick, concrete, stone, tile, stucco, mirrors, porcelain, formica, fiberglass, walls, doors, glass, metal and most painted surfaces.

Applications:

- Spray Paint
- Ink
- Crayons
- Lipstick
- Marker
- Adhesives
- Tar
- Pen
- Scuff Marks
- Fingerprints
- Wax Buildup
- Varnish

For Use By:

- Landscaping Businesses
- Factories
- Housing Authorities
- School Systems
- City & County Governments
- Golf Courses
- Industrial Plants
- Utility Companies
- Colleges/Universities
- Hospitals
- Municipalities
- Warehouses
- Court Houses
- Hotels/Motels
- Correctional Facilities
- Public Safety Officers

Product Characteristics:

| | |
|---------------------------------|---|
| Physical State: | Gas |
| Odor: | Solvent |
| Boiling Point/Range: | 257.08°F (125.05°C) estimated |
| Flash Point: | -156.0°F (-104.4°C) Propellant estimated |
| Flammability limit – lower (%): | 2.5% estimated |
| Flammability limit – upper (%): | 12% estimated |
| Vapor Pressure: | 35 - 55 psig @70°F estimated |
| Auto-Ignition Temp: | 886.24°F (474.58°C) estimated |
| Specific Gravity: | 0.817 estimated |
| Decomposition Temp: | Not available |
| Storage: | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F |
| Transport Information: | |
| UN Number: | UN1950 |
| Proper Shipping Name: | Aerosols, flammable |
| Class: | 2.1 |
| Packing Group: | Not applicable |

Directions:

Shake well before using.

Spray onto marks from a distance of at least 8". Wait 5-10 minutes. Remove with clean cloth or flush with water. If stubborn, repeat application.

Note: Do not use this product on vinyl. Not recommended for high intensity road signs.

Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

This product is not compliant for sale and use in CA, CT, DC, DE, IL, IN, MA, ME, MD, MI, NH, NJ, NY, OH, PA, UT, VA.