

# SURE GRIP #1116

## Aerosol Anti-Skid Epoxy Coating



### Features:

- Adheres to most hard surfaces
- Aids in meeting OSHA safety requirements
- Convenient aerosol – no mixing or mess
- Most cost-effective means of coating small areas
- Application can last up to 6 months, depending on traffic
- Available in Black (111601)



### Description:

SURE GRIP is a unique aerosol that contains a specialized synthetic grit with no sharp edges. This unique formulation is a super hard, texturized one-part epoxy coating that cures very quickly and lasts for months. It has a slip resistant, rough grit surface that reduces the occurrence of slip and fall accidents, helping customers to meet OSHA requirements for safe flooring. Our new convenient aerosol makes applying an anti-skid epoxy coating easier and faster than ever.

### Applications:

- Stairs/Floors
- Fiberglass
- Most Metals
- Walkways
- Docks
- Hand Tools
- Public Restrooms
- Wood
- Cement/Asphalt
- Ladders/Ramps
- Loading Docks
- Step Pads

### For Use By:

- Construction Companies
- Shipping Operations
- Schools
- Hospitals
- Industrial Plants
- Warehouses
- Nursing Homes
- Municipalities
- Machine Shops

### Product Characteristics:

Appearance:	Aerosol
Vapor Pressure:	Not determined
Specific Gravity:	Not available
Explosive Properties	Not available
Solubility (water):	Not determined
Flash Point:	-19°C (-2.2°F)
Boiling Point/Range:	-44°C (-47.2°F)
Flammability Limit – lower (%):	Not available
Flammability Limit – upper (%):	Not available
Heat of Combustion: (NFPA 30B):	Not available
Oxidizing Properties	Not available
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Transport Information:</b>	
UN Number:	UN1950
Proper Shipping Name:	Consumer Commodity ORM-D Aerosols, flammable
Class:	Not available
Packing Group:	Not available
Special Provisions:	Not available
Packaging Exceptions:	Not available

### Directions:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray with steady, even strokes at a distance of 6-10 inches (15 to 25 cm). Several light coats give a better finish than one heavy coat. Tack free in 60 minutes, fully cured in 24 hours.
4. If clogging develops, turn spray head ¼ turn or remove and clean spray head slot. DO NOT stick pin or other object into can opening. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion.
5. To clear spray head for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Slip Resistant Coatings (SRC) do not exceed 80% VOC or 2.45 MIR.

**Shelf Life:** 1 year

**Coverage:** 10 sq. feet per can

### Signal Word:

DANGER

### Personal Protective Equipment Required:



**VOC Compliant:** Yes.

### DOT Placard:



### Pictograms:

