DIRECTIONS: Read entire label before using. Shake well before use

IMPORTANT - TIRE BRITE is slippery and should not be used on or near: gas, brake or clutch pedals; steering wheels; seats of motorcycles or bicycles; or other surfaces which may be adversely affected by a slippery coating. Store can at 50°F to 80°F. Cold temperatures will lower propellant pressure, resulting in poor spray performance. Hold can 8 to 10 inches from tires or surface to be sprayed. Direct spray head away from face. Using a steady hand motion, apply a uniform coating to clean tires for best results. If desired, **TIRE BRITE** may be sprayed on a rag and wiped on tires. Although **TIRE BRITE** will not harm or discolor most materials, always test first in a small, out-of-sight area before using on rubber surfaces.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness.

Keep away from heat, sparks, open flames and hot surfaces.

No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Avoid breathing fumes, mist, vapors and spray. Use only outdoors or in a well-ventilated area. Store locked up. Dispose of contents and container in accordance with local, state and national regulations.

FIRST AID:

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT

CONTAINS (CAS#): Acetone (67-64-1), Dimethicone (63148-62-9), Tert Butyl Acetate (540-88-5), Heptane (142-82-5), Carbon Dioxide (124-38-9). Made in USA

NOT FOR SALE IN CALIFORNIA

Product Code 1287



For Commercial/Industrial Use Only

A Product of:

PRO CHEM, INC.

1475 Bluegrass Lakes Parkway Alpharetta, GA 30004 (800) 241-8180 • www.procheminc.com



TIRE BRITE

- Beautifies Antistatic Safeguards
- Easiest & Fastest Way for a Great Looking Tire

Our Formula Gives You a Deep Black Glossy Tire that Looks Great for Weeks

- No Dealing with Runs or Streak Marks or Messy Foams
 - No Rubbing Which is Time Consuming and Messy
 - Keeps Tires from Drying Out and Looking Old
 - Lasts through Multiple Washes

OTHER USES:

- Rubber Exterior Trim
 - Mud Flaps

USE ON:

Vinyl • Fiberglass • Plastics • Wood

DANGER

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Net Wt. 12 oz (340 g)