

## LONG LIFE

### CUTTING & TAPPING FLUID

is a synthetic lubricant effective in punching, drilling, tapping, sawing, machining, cutting, boring, threading and grinding operations on all steels, titanium, monel and aluminum.

#### LONG LIFE

INCREASES PRODUCTION AS WELL AS TOOL LIFE

RESULTS IN COOLER WORKPIECE WITH LESS TOOL BURNING

- Fluid is transparent providing better visibility of work area.
- Can be removed with cold water or degreaser solvents.
- Cools cutting tools for longer life.
- Lubricates to penetrate surface and provides a continuous non-staining film and protects from corrosion.

#### DIRECTIONS:

Generously spray area to be worked. Reapply as necessary to keep work area cool and well lubricated. Can be removed with water or Solvent Degreaser.

**CAUTION:** Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

#### KEEP OUT OF REACH OF CHILDREN

See Safety Data Sheet for complete safety information.

#### MODO DE USO:

Pulverizar generosamente las zonas a ser trabajadas. En caso de ser necesario, repetir la aplicación a fin de mantener la zona refrigerada y bien lubricada. Puede quitarse con agua o desengrasante de solventes.

**PRECAUCIÓN:** Utilizar con una ventilación adecuada. El uso indebido por concentración e inhalación del producto puede ser dañino o fatal.

#### MANTENER FUERA DEL ALCANCE DE LOS NIÑOS

Mire la hoja de datos de seguridad de para la información completa de seguridad.

Emergency Telephone:  
INFOTRAC 1-800-535-5035



PLEASE RECYCLE  
WHEN EMPTY

Product Code: 1732



**TO REORDER CALL:**  
**1-800-241-8180**  
**www.procheminc.com**



# LONG LIFE

## CUTTING & TAPPING FLUID

### FLUÍDO DE CORTE y ROSCADO

### COOLANT LUBRICANT FOR DRILLS, TAPS, CUTTING TOOLS

#### DANGER / PELIGRO:

**EXTREMELY FLAMMABLE / EXTREMADAMENTE INFLAMABLE.**  
**EYE IRRITANT / IRRITA LOS OJOS.**  
**CONTENTS UNDER PRESSURE / CONTENIDO BAJO PRESIÓN.**  
SEE OTHER CAUTIONS ON BACK PANEL /  
VER OTRAS PRECAUCIONES EN EL PANEL POSTERIOR.  
**NET WT. / PESO NETO: 12 OZ (340 g)**

#### LONG LIFE CUTTING & TAPPING FLUID



**DANGER:** Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of waste and residues in accordance with local authority requirements.

**FIRST AID:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. Call a poison center/doctor if you feel unwell. IF eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash off with soap and water. IF SWALLOWED: Rinse mouth.

**CONTAINS (Cas No.):** Acetone (67-64-1), Butane (106-97-8), Distillates (petroleum), Hydrotrated Light (64742-47-8), Propane (74-98-6).

**PELIGRO:** Aerosol extremadamente inflamable. Provoca irritación ocular grave. Puede provocar somnolencia o vértigo. Mantener alejado de fuentes de calor, chispas, llama abierta o superficies calientes. No fumar. No pulverizar sobre una llama abierta u otra fuente de ignición. Recipiente a presión: no perforar ni quemar, aun después del uso. Evitar respirar el gas. Lavarse concienzudamente tras la manipulación. Utilizar únicamente en exteriores o en un lugar bien ventilado. Llevar protección ocular/ facial. Almacenar en un lugar bien ventilado. Mantener el recipiente cerrado herméticamente. Guardar bajo llave. Proteger de la luz del sol. No exponer a temperaturas superiores a 50°C/122°F. Eliminar los desperdicios y residuos de conformidad con la normativa promulgada por las autoridades locales.

**PRIMEROS AUXILIOS:** EN CASO DE INHALACIÓN: Tránsportése a la persona al exterior y manténgase en una postura que le permita respirar cómodamente. EN CASO DE CONTACTO CON LOS OJOS: Aclárese cuidadosamente con agua durante varios minutos. Quitense las lentes de contacto, si se llevan y resulta fácil hacerlo. Sígase aclarando. EN CASO DE EXPOSICIÓN O PREOCUPACIÓN: Solicítese asistencia médica. Llamar a un centro de información toxicológica o a un médico en caso de malestar. Si persiste la irritación ocular: Consultar a un médico. EN CASO DE CONTACTO CON LA PIEL: Lavar con agua y jabón. EN CASO DE INGESTIÓN: Enjuagar la boca.

**CONTIENE (Núm. Cas):** Acetona (67-64-1), Butano (106-97-8), Destilados (petróleo), Luz Hidrotratada (64742-47-8), Propano (74-98-6).

An Exclusive Product Of:  
**PRO CHEM, INC.**  
1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
1-800-241-8180