

TRUE BOND PATCH is ready to use, premixed asphalt base patching material for repairing potholes. It is a combination of super hard aggregate, refined asphalt and specially formulated polymers. The polymers give TRUE BOND PATCH the high strength adhesive power that holds the patch together and bonds it to the existing pavement. Special wetting agents have been added so it will adhere to wet surfaces as tenaciously as it does to dry surfaces. This adhesive strength allows it to stick together without raveling like common mixes do.

APPLICATIONS:

- Repairing Potholes In Roadways • Parking Lots • Garages
- Sidewalks • Driveways • Railway Crossings • Bridge Decks

DIRECTIONS: TRUE BOND PATCH is extremely easy to apply. First sweep out all loose debris from the hole. Apply TRUE BOND PATCH as is to the areas where it is needed. Pack it down with a hand tamper or roller. If the void is deeper than one inch, tamp material down in successive layers of one inch to assure maximum compression. No drying or curing time is required. Area can be immediately opened to traffic.

The surface should be clean of grease, oil and dirt. If extremely dusty, hose the surface down with water. The surface need not be dry before applying. Take care to keep vertical edges of hole as clean as possible to allow for best adhesion. Material works best over a solid base; do not use over mud or clay. Remove material from the pail just as it is and place it where needed by shoveling or pouring it in. Level material slightly higher than desired depth to allow for compaction. Pack it down with a hand tamper or roller. If the void is deeper than 1 inch, tamp material down in successive layers of 1 inch to assure maximum compression. No drying or curing time is required. Area can be immediately opened to traffic.

COVERAGE RATE: Approximately 7 square feet at 1 inch deep.



TRUE BOND PATCH

Ready-To-Use Asphalt Patching Compound

- Will not harden until compressed
- Long lasting – unaffected by freezing temperatures
- Matches original blacktop surfaces
- Can be used on wet or dry surfaces
- Easy to apply- no mixing required
- Smaller aggregate allows better fill
- Will not track
- Area can be immediately opened to traffic
- Shelf life of up to 2 years

**WARNING: HARMFUL OR FATAL IF SWALLOWED.
AVOID CONTACT WITH EYES. DO NOT TAKE
INTERNALLY.**

See Safety Data Sheet for additional precautions and first aid instructions.

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand this label, find someone to explain it to you in detail.)

NET CONTENTS: 5 GALLONS

TRUE BOND PATCH

SIGNAL WORD: WARNING

HAZARD STATEMENTS:
Suspected of causing cancer.

PRECAUTIONARY STATEMENTS:

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. May be harmful in contact with skin.

RESPONSE: If exposed or concerned: Get medical advice/attention.

STORAGE: Store locked up.

DISPOSAL: Dispose of contents/container to an approved waste disposal plant.

An Exclusive Product of Pro Chem, Inc.
1475 Bluegrass Lakes Parkway • Alpharetta, GA 30004
TO REORDER CALL: 1-800-241-8180 • www.procheminc.com

INGREDIENTS (CAS#): Limestone (1317-65-3), Asphalt (at Ambient Temperature) (8052-42-4), Fuel oil (68476-33-5). This product is a mixture. This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

ADDITIONAL CAUTIONS: Causes eye irritation. Inhalation of vapors can be harmful to upper respiratory tract and central nervous system. Keep away from heat or flame. Wear eye and skin protection when handling. Avoid prolonged or repeated breathing of vapors, mists or fumes. Do not take internally. Observe good hygiene and safety practices when handling this product. KEEP OUT OF REACH OF CHILDREN. Use only with adequate ventilation. Seal bag when not in use. FOR EXTERIOR USE ONLY.

PRODUCT #2462

