

# 4-N-1 BULK #2707

## Penetrating Oil & Demoisturant



### Features:

- Lubricates and creates waterproof film
- High dielectric strength of 39,000 volts, nonconductive
- Nonflammable
- Contains no chlorinated solvents, perchloroethylene or methylene chloride
- Dries wet electric contacts
- Displaces water and moisture from electrical parts and prevents malfunction in equipment exposed to high humidity
- Frees rusted nuts & bolts
- Food Processing Acceptability: H2



### Description:

4-N-1 BULK is a high dielectric, nonflammable liquid that protects against industrial and atmospheric pollution, dust, abrasive matter and chemical fumes. It forms a non-drying, invisible film that prevents moisture-induced deterioration and malfunctions on electrical components and circuitry without any loss in conductivity. It creeps along surfaces and into cracks to lubricate, prevent rust and loosen frozen parts. It leaves a water-displacing shield and a lubricating film to make anything run smoother. 4-N-1 BULK has unlimited uses in automotive, marine, railroad and construction industries.

### Applications:

- Motors
- Hinges
- Molds
- Generators
- Screws
- Linkages
- Lug Nuts
- Bearings
- Fasteners
- Engine Parts
- Frozen Nuts
- Relays
- Bolts
- Starters
- Threaded Parts
- Switches
- Clamps
- Tools
- Gears
- Plugs

### Product Characteristics:

Appearance:	Liquid
Odor:	Not available
Flammability Limit-lower (%):	0.6 % estimated
Flammability Limit-upper (%):	7 % estimated
Specific Gravity:	0.07 estimated
Explosive Properties:	Not explosive
Flash Point:	307.1°F (152.8°C) estimated
Oxidizing Properties:	Not oxidizing
pH:	Not available
Auto-Ignition Temperature:	834.8°F (446°C) estimated
Storage:	Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials
<b>Transport Information:</b>	
Proper Shipping Name:	Not regulated as dangerous goods
UN Number:	Not regulated as dangerous goods
Class:	Not regulated as dangerous goods
Packing Group:	Not regulated as dangerous goods

### Directions:

For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank. Apply as a spray, brush on or use in a dip tank. Allow wetted-out rusted parts to be immersed in solution for several minutes. Always keep container closed to prevent evaporation or contamination.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



### DOT Placard:

Not regulated.

VOC Compliant



# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>PRODUCT NUMBER:</b>	2707	<b>COMPANY PHONE:</b>	1-800-241-8180
<b>PRODUCT NAME:</b>	4-N-1	<b>EMERGENCY TELEPHONE:</b>	1-800-241-8180
<b>PRODUCT DESCRIPTION:</b>	Non-Chlorinated Penetrant, Lubricant, Demoisurant, & Protectant	<b>INFOTRAC:</b>	1-800-535-5053
<b>COMPANY INFORMATION:</b>	<b>PRO CHEM, INC.</b> 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

## 2. Hazards Identification

<b>GHS CLASSIFICATION:</b> <b>Physical hazards:</b> Not classified. <b>Health hazards:</b> Reproductive toxicity (fertility): Category 2 Aspiration Hazard: Category 1. <b>OSHA defined hazards:</b> Not classified.	<b>SIGNAL WORD:</b> <b>DANGER</b>	<b>SYMBOL:</b>	
--	--------------------------------------	----------------	--

### HAZARD STATEMENTS:

May be fatal if swallowed and enters airways. Suspected of damaging fertility. The mixture does not meet the criteria for classification.

### PRECAUTIONARY STATEMENTS:

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** IF SWALLOWED: Immediately call a poison center/doctor. IF EXPOSED OR CONCERNED: Get medical advice/attention. Do NOT induce vomiting.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

### HAZARDS NOT OTHERWISE SPECIFIED:

None known.

### SUPPLEMENTAL INFORMATION:

None.

## 3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Dipropylene Glycol Monomethyl Ether	34590-94-8	2.5-10
Methyl Silicone	556-67-2	2.5-10
Other components below reportable levels		90-100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First Aid Measures

### EMERGENCY OVERVIEW

**WARNING:** IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

**EYES:** Rinse with water. Get medical attention if irritation develops and persists.

**SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists.

### INHALATION:

Move to fresh air. Call a physician if symptoms develop or persist.

### INGESTION:

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.

### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire Fighting Measures

### SUITABLE FIRE EXTINGUISHING MEDIA:

Water fog. Foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO<sub>2</sub>).

### UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

During fire, gases hazardous to health may be formed.

### SPECIFIC FIRE-FIGHTING METHODS:

Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use standard firefighting procedures and consider the hazards of other involved materials.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

### GENERAL FIRE HAZARDS:

No unusual fire or explosion hazards noted.

## 6. Accidental Release Measures

### PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

### METHODS & MATERIALS FOR CONTAINMENT AND CLEAN UP:

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.  
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see Section 13 of the SDS.

### ENVIRONMENTAL PRECAUTIONS:

Avoid discharge into drains, watercourses or onto the ground.

## 7. Handling and Storage

### SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### SAFE STORAGE & INCOMPATIBILITIES:

Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	PEL	600 mg/m <sup>3</sup> 100 ppm

#### US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	150 ppm
	TWA	100 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	900 mg/m <sup>3</sup> 150 ppm
	TWA	600 mg/m <sup>3</sup> 100 ppm

#### US. Workplace Environmental Exposure Level (WEEL) Guides

COMPONENTS	TYPE	VALUE
Methyl Silicone (CAS 556-67-2)	TWA	10 ppm

### BIOLOGICAL LIMIT VALUE:

No biological exposure limits noted for the ingredient(s).

### EXPOSURE GUIDELINES:

#### US - California OELs: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

#### US - Tennessee OELs: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

### ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:



**EYE PROTECTION:** Chemical respirator with organic vapor cartridge and full facepiece.

#### SKIN PROTECTION:

Hand: Wear appropriate chemical resistant gloves.

Other: Wear suitable protective clothing. Use of an impervious apron is recommended.

**RESPIRATORY PROTECTION:** Chemical respirator with organic vapor cartridge and full facepiece.

**THERMAL HAZARDS:** Wear appropriate thermal protective clothing, when necessary.

### GENERAL HYGIENE CONSIDERATIONS:

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical & Chemical Properties

<b>APPEARANCE:</b>		<b>FLAMMABILITY(solid/gas):</b>	Not available.
<b>Physical State:</b>	Liquid.	<b>Flammability Limit-lower (%):</b>	0.6% estimated
<b>Form:</b>	Liquid.	<b>Flammability Limit-upper (%):</b>	7% estimated
<b>Color:</b>	Not available.	<b>Explosive Limit – lower (%):</b>	Not available.
<b>ODOR:</b>	Not available.	<b>Explosive Limit – upper (%):</b>	Not available.
<b>ODOR THRESHOLD:</b>	Not available.	<b>VAPOR PRESSURE:</b>	0.02 psig @70°F estimated
<b>pH:</b>	Not available.	<b>VAPOR DENSITY:</b>	Not available.
<b>MELTING/FREEZING POINT:</b>	Not available.	<b>RELATIVE DENSITY:</b>	Not available.
<b>INITIAL BOILING POINT/RANGE:</b>	518°F (270°C) estimated	<b>SOLUBILITY (water):</b>	Not available.
<b>PARTITION COEFFICIENT (n-octanol/water):</b>	Not available.	<b>AUTO-IGNITION TEMP:</b>	834.8°F (446°C) estimated
<b>VISCOSITY:</b>	Not available.	<b>DECOMPOSITION TEMP:</b>	Not available.
<b>SPECIFIC GRAVITY:</b>	0.504 estimated	<b>FLASH POINT:</b>	291.7°F (144.3°C) estimated
<b>EVAPORATION RATE:</b>	Not available.		

### 10. Stability & Reactivity Information

**REACTIVITY:**

The product is stable and non-reactive under normal conditions of use, storage and transport.

**CHEMICAL STABILITY:**

Material is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:**

No dangerous reaction known under conditions of normal use.

**INCOMPATIBLE MATERIALS:**

Strong oxidizing agents.

**CONDITIONS TO AVOID:**

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

No hazardous decomposition products are known.

### 11. Toxicological Information

**PRIMARY ROUTE OF ENTRY:**

**EYES:** Direct contact with eyes may cause temporary irritation.

**SKIN:** No adverse effects due to skin contact are expected.

**INHALATION:** Prolonged inhalation may be harmful.

**INGESTION:** Expected to be a low ingestion hazard. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:**

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.

**ACUTE TOXICITY:**

May be fatal if swallowed and enters airways.

COMPONENTS	SPECIES	TEST RESULTS
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	9510 mg/kg, 24 Hours
	Rat	10 ml/kg, 24 Hours
		> 19020 mg/kg, Hours
		> 20 ml/kg, Hours
<i>Inhalation</i>		
LC50	Rat	> 553 ppm, 8 Hours
		> 275 ppm, 7 Hours
<i>Oral</i>		
LD50	Rat	>5000 mg/kg
Methyl Silicone (CAS 556-67-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, 24 Hours
		>2.5 ml/kg
<i>Inhalation</i>		
<i>Aerosol</i>		
LC50	Rat	36 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	1700 mg/kg
	Rat	> 4800 mg/kg

\* Estimates for product may be based on additional component data not shown.

**SKIN CORROSION/IRRITATION:**

Prolonged skin contact may cause temporary irritation.

**SERIOUS EYE DAMAGE/IRRITATION:**

Direct contact with eyes may cause temporary irritation.

**RESPIRATORY SENSITIZATION:**

Not available.

**SKIN SENSITIZATION:**

This product is not expected to cause skin sensitization.

**GERM CELL MUTAGENICITY:**

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**CARCINOGENICITY:**

Not applicable.

**IARC Monographs. Overall Evaluation of Carcinogenicity:** Not available.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens:** Not available.

**REPRODUCTIVE TOXICITY:**

This product is not expected to cause reproductive or developmental effects.

**SPECIFIC TARGET ORGAN TOXICITY (single exposure):**

Not classified.

**SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):**

Not classified.

**ASPIRATION HAZARD:**

May be fatal if swallowed and enters airways.

**CHRONIC EFFECTS:**

Prolonged inhalation may be harmful.

**12. Ecological Information****ECOTOXICITY:**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**PERSISTENCE AND DEGRADABILITY:**

No data is available on the degradability of this product.

**BIOACCUMULATIVE POTENTIAL:**

No data available.

**MOBILITY IN SOIL:**

No data available.

**OTHER ADVERSE EFFECTS:**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal Consideration****DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**LOCAL DISPOSAL REGULATIONS:**

Dispose in accordance with all applicable regulations.

**HAZARDOUS WASTE CODE:**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**WASTE FROM RESIDUES/UNUSED PRODUCTS:**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**CONTAMINATED PACKAGING:**

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

**14. Transportation Information**

**DOT:** Not regulated as dangerous goods.

**IATA:** Not regulated as dangerous goods.

**IMDG:** Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:**

Not available.

**15. Regulatory Information****US FEDERAL REGULATIONS:**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):** Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4):** Not listed.

**SARA 304 Emergency release notification:** Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.

**SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):**

**Hazard categories:**

- Immediate Hazard – No.
- Delayed Hazard – Yes.
- Fire Hazard – No.
- Pressure Hazard – No.
- Reactivity Hazard – No.

**SARA 302 Extremely hazardous substance:** Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting): Not regulated.

#### OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated.

#### US STATE REGULATIONS

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):

Methyl Silicone (CAS 556-67-2)

US. Massachusetts RTK - Substance List:

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. New Jersey Worker and Community Right-to-Know Act:

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Pennsylvania Worker and Community Right-to-Know Law:

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Rhode Island RTK: Not regulated.

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other Information

##### DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

**NO Chlorinated Solvents  
(NO 1,1,1-Trichloroethane)  
(NO Perchloroethylene)  
(NO Methylene Chloride)**

**39 kV DIELECTRIC STRENGTH**

**NUT and BOLT LOOSENER** — Rapidly penetrates through rust and corrosion.

**WATER DISPLACER** — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

Electronic Cleaners do not contain more than 75% VOC.

**LUBRICANT** — Assures free and easy movement of parts.

**ANTI-CORROSIVE COATING** — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

**USES:** Motors, relays, switches, plugs, rheostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motorcycles, blowers, hoists, overhead doors.

**DIRECTIONS:**

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on, or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.

Product Code: 2707



Sold by:  
**Pro Chem, Inc.**  
1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | www.procheminc.com



# 4-N-1

## PENETRATING OIL & DEMOISTURANT

**Non-Flammable**

**Contains No Chlorinated Solvents**

- **Frees Rusted Bolts, Studs and Other Fittings**
- **Helps Prevent Corrosion**
- **Penetrates, Lubricates**
- **Prevents Rust and Displaces Moisture**

**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY**

**NET CONTENTS: 5 GALLONS**

**DANGER:**  
**VAPOR HARMFUL**  
**KEEP OUT OF REACH OF CHILDREN**  
**SEE OTHER CAUTIONS ON BACK PANEL**

**4-N-1  
PENETRATING OIL  
& DEMOISTURANT**



**DANGER:** May be fatal if swallowed and enters airways. Suspected of damaging fertility. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

**FIRST AID: IF SWALLOWED:** Immediately call a poison center/doctor. Do NOT induce vomiting. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. **IF ON SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists. **IF IN EYES:** Rinse with water. Get medical attention if irritation develops and persists. **IF INHALED:** Move to fresh air. Call a physician if symptoms develop or persist.

**CONTAINS (CAS No.):** Mineral Oil (8042-47-5), Distillates, Petroleum, Hydrotreated Middle (64742-46-7), Dipropylene Glycol Monomethyl Ether (34590-94-8), Methyl Silicone (556-67-2) and Fragrance (Proprietary).

**HMIS® RATING:** Health, 2\*; Flammability, 1; Physical Hazard, 0; Personal Protection, X.  
\*=-Chronic

**See Safety Data Sheet for complete safety information.**

**Emergency Telephone:  
INFOTRAC 1-800-535-5053**

**CONTAINS NO OZONE  
DEPLETING CHEMICALS!**



MADE IN CANADA



NO Chlorinated Solvents (NO 1,1,1-Trichloroethane)  
(NO Perchloroethylene) (NO Methylene Chloride)

39 kV DIELECTRIC STRENGTH

**NUT and BOLT LOOSENER** — Rapidly penetrates through rust and corrosion.

**WATER DISPLACER** — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

**LUBRICANT** — Assures free and easy movement of parts.

**ANTICORROSIVE COATING** — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

**USES:** Motors, relays, switches, plugs, rheostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motorcycles, blowers, hoists, overhead doors.

**DIRECTIONS:**

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.

Sin Solventes Clorados (Sin 1,1,1-Tricloroetano)  
(Sin Percloroetileno) (Sin Cloruro de Metileno)  
39 kV RIGIDEZ DIELECTRICA

**AFLOJADOR PARA TUERCAS Y PERNOS** — Penetra rápidamente a través de la oxidación y la corrosión.

**DESPLAZADOR DE AGUA** — Desplaza la humedad de las piezas eléctricas. Previene el mal funcionamiento de los equipos eléctricos expuestos a alta humedad.

**LUBRICANTE** — Asegura el movimiento libre y fácil de las piezas.

**RECUBRIMIENTO ANTI-CORROSIVO** — Deja una capa protectora que impide la oxidación, la corrosión y los efectos nocivos de la humedad.

**USOS:** Motores, relés, interruptores, enchufes, reóstatos, montajes eléctricos y electrónicos, medidores de estacionamiento, equipos marinos, máquinas expendedoras, vehículos, aparatos, herramientas, maquinaria, generadores, baterías, cargadores, plantillas, accesorios, ventiladores, bornes de baterías, motos, ventiladores, montacargas, puertas basculantes.

**INSTRUCCIONES:**

1. Para un mejor rendimiento y mayor protección, primero limpie el objeto con solvente desengrasante para eliminar grasa, aceite y sucio. Esto evitará que el material se contamine, especialmente cuando se usa en un tanque de inmersión.
2. Aplicar bien sea rociando, con una brocha o utilice un tanque de inmersión.
3. Permitir que las partes oxidadas estén en contacto con la solución durante varios minutos.
4. Mantenga siempre el envase cerrado para evitar la evaporación o contaminación.



4-N-1

**PENETRATING OIL  
& DEMOISTURANT**  
LUBRICANTE PENETRANTE  
DESHUMIDIFICADOR

Nonflammable

Contains No Chlorinated Solvents

- Frees Rusted Bolts, Studs and Other Fittings
- Helps Prevent Corrosion
- Penetrates, Lubricates
- Prevents Rust and Displaces Moisture

No Inflammable

No Contiene Disolventes Clorados

- Libera Tuercas, Pernos y Otras Piezas Oxidadas
- Ayuda a Prevenir la Corrosión
- Penetra, Lubrica
- Previene la Oxidación y Desplaza la Humedad

**DANGER: VAPOR HARMFUL  
HARMFUL OR FATAL IF SWALLOWED  
KEEP OUT OF REACH OF CHILDREN  
SEE OTHER CAUTIONS ON BACK PANEL**

**PELIGRO: VAPOR DAÑO  
DAÑO O FATAL SI SE TRAGA  
MANTENER FUERA DEL ALCANCE DE LOS NIÑOS  
VER OTROS PRECAUCIONES EN EL PANEL LATERAL.**

**NET CONTENTS / PESO NETO:  
55 GALLONS**

4-N-1  
**PENETRATING OIL & DEMOISTURANT**  
LUBRICANTE PENETRANTE DESHUMIDIFICADOR



**DANGER:** May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

**FIRST AID: IF SWALLOWED:** Immediately call a poison center/doctor. Do NOT induce vomiting. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. **IF ON SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists. **IF IN EYES:** Rinse with water. Get medical attention if irritation develops and persists. **IF INHALED:** Move to fresh air. Call a physician if symptoms develop or persist.

**CONTAINS (CAS No.):** Mineral Oil (8042-47-5), Distillates, Petroleum, Hydrotreated Middle (64742-46-7), Dipropylene Glycol Monomethyl Ether (34590-94-8), Methyl Silicone (556-67-2) and Fragrance (Proprietary).

**PELIGRO:** Puede ser mortal en caso de ingestión y penetración en las vías respiratorias. Se sospecha que perjudica la fertilidad o daña al feto. Pedir instrucciones especiales antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Usar guantes y ropa de protección, protector de ojos/cara. Guardar bajo llave. Eliminar el contenido / recipiente en conformidad con los reglamentos locales / regionales / nacionales / internacionales.

**PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN:** Llámese inmediatamente a un centro toxicológico o a un médico. No provocar el vómito. **EN CASO DE EXPOSICIÓN O PREOCUPACIÓN:** Solicitese asistencia médica. **EN CASO DE CONTACTO CON LA PIEL:** Lavar con agua y jabón. Busque atención médica si la irritación se desarrolla y persiste. **EN CASO DE CONTACTO CON LOS OJOS:** Enjuagar con agua. Busque atención médica si la irritación se desarrolla y persiste. **EN CASO DE INHALACIÓN:** Salir al aire libre. Llame a un médico si los síntomas aparecen o persisten.

**CONTIENE (Nº CAS):** Aceite Mineral (8042-47-5), Destilados de Petróleo, Medio Hidrotreatado (64742-46-7), Éter Monometílico del Dipropilenglicol (34590-94-8), metil silicona (556-67-2) y Fragancia (Proprietaria).

**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY  
SOLO PARA USO INDUSTRIAL E INSTITUCIONAL**

**See Safety Data Sheet for complete safety information. /  
Mire la hoja de datos de seguridad de para la información  
completa de seguridad.**

**Emergency Telephone:  
INFOTRAC 1-800-535-5053**

Product Code: 2707



Sold by:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway

Alpharetta, GA 30004

1-800-241-8180 | www.procheminc.com

MADE IN CANADA WITH  
GLOBALLY SOURCED MATERIALS  
HECHO EN CANADA CON MATERIALES  
GLOBALEMENTE FUENTES

