

SLICK #1482

Aerosol All-Season Wax



Features:

- Keeps grass from sticking to mowers
- Reduces costly equipment failure and repairs
- Reduces horsepower requirements, fuel consumption and corrosion
- No mess
- Protects metal, plastic, fiberglass and painted finishes
- Helps prevent salt corrosion
- Helps increase the efficiency of snow removal



Description:

SLICK is a special blend of silicone and wax that provides a slick, nonstick coating for all types of outdoor equipment. In the springtime, spray on blades and under decks of cutters and mowers to keep grass from sticking to blades and undercarriage. Regular use helps blades and cutting edges remain sharp longer. In the winter, spray on snow removal equipment to keep snow and ice from building up on blades, moldboards and wings. Treated surfaces become water and rust resistant. The coating provides superior release action and lubrication to reduce drag and sticking of many materials to metal and other surfaces. Also excellent for use on road signs to keep snow or ice from sticking and to ensure easy readability.

Applications:

- Edge Trimmers
- Bush Hogs
- Snowplows
- Road Signs
- Lawn Mowers
- Augers
- Shovels
- Moldboards
- Hedge Trimmers
- Rototillers
- Blades
- Flails

Product Characteristics:

Appearance:	Liquid
Form:	Spray aerosol
Odor:	No data available
Flammability (solid/gas):	No data available
Explosive Limit – upper (%):	Estimated 7.5% (V)
Explosive Limit – lower (%):	Estimated 0.9% (V)
Flash Point:	Estimated -156.0°F (-104.4°C)
Evaporation Rate:	No data available
Vapor Pressure:	No data available
Vapor Density (air=1):	No data available
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable
UN Number:	UN1950
Class:	2.1
Packing Group:	II

Directions:

Shake well before using.
Spray surface from a distance of 12 to 14 inches. For best results: Apply product onto clean dry surfaces only. Spray liberally in a sweeping motion over surface to be treated. Reapply treatment frequently to insure peak non-stick performance.

NOTE: To prevent accidental injury, turn off engine and disengage or disable any cutting blades or moving parts before application of product.

DOT Placard:



Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:

