

# MEGA BLAST II #1605

## Solvent Degreaser



### Features:

- Non-flammable
- Leaves no residue
- Dries quickly
- Non-chlorinated
- Non-conductive
- High solvent power
- Safe on most plastics used in contact and circuit board construction
- Dielectric Strength: 14,000 volts



### Description:

MEGA BLAST II provides industry an alternative to products containing chlorinated solvents. Dries quickly, leaving no residue. The low-odor, non-flammable, non-conductive formula cleans and degreases electric motors, power tools, printing presses, refrigeration and air conditioning equipment, generators and starters, office machines, most metals including steel, nickel, zinc, titanium, galvanized steel, copper, magnesium, brass and tin plate. Also safe for use on some plastics, including those used in contact and circuit board construction. May affect certain types of plastics, such as PVC, ABS, acrylic styrenes and polycarbonates. If unsure of compatibility, test in an inconspicuous area prior to use.

### Applications:

- Electrical Motors
- Refrigeration and Air Conditioning Units
- Printing Presses
- Power Tools
- Generators and Starters
- Office Machines

### For Use On:

- Copper
- Zinc
- Galvanized Steel
- Steel
- Magnesium
- Titanium
- Brass and Tin Plate
- Nickel

### For Use By:

- Auto Repair Shops
- Factories
- Aircraft Services
- Electrical Maintenance Services
- Machine Shops
- Printers
- HVAC Services
- Offices

### Product Characteristics:

Appearance:	Clear colorless to yellow liquid
Odor:	Strong solvent odor
Initial Boiling Point/Range:	158°F (70°C)
Vapor Pressure (mm Hg):	Not determined
Vapor Density (AIR=1):	Not determined
Solubility (water):	Non-soluble in water
Relative Density:	1.3
Flash Point:	Not determined
pH:	Not determined
Melting/Freezing Point:	-166.8°F (-110.5°C)
Evaporation Rate:	4.7 (Fast)
Storage Stability:	1 Year +
Wetting Ability:	Moderate
Cold Stability:	0°F
Storage:	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
<b>Transport Information:</b>	
UN Number:	UN 1950
Proper Shipping Name:	Aerosols, Ltd. Qty
Class:	2.2
Packing Group:	Not applicable

### Directions:

Spray surface to be cleaned and wipe with clean cloth. For heavy deposits, let stand for 30 seconds or scrub with brush. Flush a second time and wipe with clean cloth. Electric motors may be cleaned while in operation. Blow dry with compressed air and lubricate bearings after cleaning.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



DOT Placard:  
Not available.

### VOC Restricted States:

Not available for sale in:  
CA. CT. DC. DE. MA. MD. ME. MI. NH. NJ. NY. OH. PA. UT & VA.