

DRY RELEASE #1583

Aerosol Dry Lubricant & Release Agent



Features:

- No Hexane
- Contains PTFE
- Colorless, Non-Staining, Low Odor
- Oil-Free
- Wide temperature range -100°F to 500°F



Description:

DRY RELEASE is a no mess, non-staining dry lubricant. The low odor, colorless formula is non-oily but slicker than silicone and graphite. Excellent anti-stick properties for an effective release on die casts and injection molds. Contains an extremely fine polytetrafluoroethylene powder, creating a lubricant film effective over a wide temperature range (-100°F to 500°F).

Applications:

- Hinges
- Chutes
- Axles
- Chains
- Paper
- Bins
- Machinery
- Pulleys
- Munitions
- Elastomers
- Conveyor Belts
- Industrial Blenders
- Springs
- Gears
- Machine Parts
- Glass
- Leather
- Spray Booths
- Metal Extrusions
- Pulleys Bushings
- Lock & Catches
- Synthetic Filters
- Cord, Twine or Rope
- Skids

Product Characteristics:

Appearance:	White Hazy Spray
Odor:	Petroleum odor
Vapor Pressure (mm Hg):	Not determined
Solubility:	Non-soluble in water
Relative Density (H2O=1):	0.71 - 0.76
Flash Point:	Not determined
pH:	Not applicable
Flammability(solid/gas):	Extremely Flammable Aerosol
Storage:	Use only with adequate ventilation. Wear appropriate protective equipment. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Store in cool, dry, ventilated area. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
UN Number:	UN 1950
Proper Shipping Name:	Aerosols, Ltd. Qty.
Class:	2.1
Packing Group:	Not applicable

Directions:

Shake can for 1 full minute to thoroughly agitate. Apply to clean, dry surface. Hold can 5-10 inches from surface and apply evenly. Thin coats are preferable.

Pictograms:



Signal Word:
DANGER

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:
Not available.