

CHAIN & CABLE LUBE #1794

Aerosol Synthetic Dry Film Lubricant



Features:

- Cleans and lubricates
- Prevents corrosion and rust
- Will not attract dirt
- Non-staining
- Chemical resistant
- Waterproof
- Displaces moisture



Description:

CHAIN & CABLE LUBE is a transparent, heavy-duty dry film lubricant that cleans, penetrates and lubricates. It is formulated with the latest synthetic additives to assure maximum penetration and protection against rust and corrosion. When applied, the carrier solvent quickly evaporates, leaving behind a wax-like extreme pressure lubricant which will not wash-off or attract dust.

CHAIN & CABLE LUBE is formulated to lubricate, preserve and protect not only chains and cables but as an excellent extreme pressure lubricant for all bearings and sliding surfaces. It is designed to fit a wide variety of industrial, agricultural, marine, automotive and household uses.

For Use By:

- Industrial
- Marine
- Automotive
- Household Applications

Applications:

- Paper Mills
- Chain Saws
- Draglines
- Motorcycle Chains
- Bicycle Chains
- Control Cables
- Guns
- Conveyors
- Chain and Cables
- Lock and Hinges
- Bushings and Shafts
- Sliding Doors and Windows
- Conveyor Bearings
- Nuts and Bolts
- Cutting Blades

Product Characteristics:

Physical State:	Liquid
Color:	Amber
Odor:	Mild Solvent
Boiling Point:	232.22°C (450°F)
Vapor Pressure:	<0.08 kPa (<0.6 mm Hg) [room temperature]
Vapor Density:	>1 [Air = 1]
Solubility:	Insoluble in water
Relative Density:	0.83 g/ml
Flash Point:	Open cup: 110°C (230°F) [Cleveland.]
pH:	Not available
Evaporation Rate:	<0.1 (Butyl acetate = 1)
Storage:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use.
Transport Information:	
UN Number:	Not regulated.
Proper Shipping Name:	-
Class:	-
Packing Group:	-

Directions:

Shake well before use. Spray an area to be treated. Carrier evaporates leaving lubricant film.

IMPORTANT: Contains solvent which may affect certain plastics. Test thoroughly before use. Use only in well ventilated area.

Pictograms:



Signal Word:
DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.