

LIKE NU NEW & IMPROVED #173311

Aerosol Ceiling Tile Restorer



Features:

- Easy to use
- Water-based paint that covers and restores ceiling tiles to look brand new
- Fast drying, will not warp or sag ceiling tiles

Description:

LIKE NU NEW & IMPROVED is a water-based paint that covers up and restores stained ceiling tiles to look brand new again. For use on textured and acoustical ceiling tiles. It is fast drying, sprays upright, and will not warp or sag tiles.



Applications:

- Paint Acoustic Tiles
- Paint crown moldings without removing them
- Stained Ceiling Tiles
- Touch up stains on drywall

Product Characteristics:

| | |
|-------------------------------|---|
| Appearance: | Aerosol |
| Odor: | Aromatic |
| Boiling Point: | -44°C (-47.2°F) |
| Danger of Explosion: | In use, may form flammable/explosive vapour-air mixture. |
| Explosive Limit-Lower (%): | 1.7 Vol % |
| Explosive Limit-Upper (%): | 10.9 Vol % |
| Evaporation Rate: | Not applicable |
| Auto-Ignition Temp: | Product is not self-igniting. |
| Relative Density: | Between 0.77 and 0.85 (Water equals 1.00) |
| Flash Point: | -19°C (-2.2°F) |
| Coverage: | Up to 15 square feet |
| Specific Gravity: | 0.83 |
| Cleanup: | Paint or lacquer thinner |
| MIR Value: | 0.93, Non-flat coating (cannot exceed 0.95) |
| HAPS Content: | 16% |
| Storage Temperature: | 40-100°F |
| Application Temperature: | 50-90°F |
| Heat Resistance: | 250°F |
| Resin System: | V.T. Alkyd |
| Shelf Life: | Guaranteed for 2 years |
| Food Contact Rating: | No |
| Storage: | Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Transport Information: | |
| UN Number: | UN1950 |
| Proper Shipping Name: | Aerosols, flammable |
| Class: | 2.1 |
| Packing Group: | - |

Directions:

1. USE CARE — This distinctive sprayhead will release the product if pushed to the side. The paint is sprayed upward when can is held in the upright position.
2. For best results, can should be at room temperature 70°F and 90°F (21°C and 32°C).
3. SHAKE CAN vigorously for one minute after mixing ball is heard and occasionally during use.
4. Before spraying, be sure to cover floor, furniture, and ceiling fixtures to prevent their being spotted with paint. If the ceiling stain is near a wall, be sure to cover the nearby wall area.
5. This product is designed to spray ceiling with the can held in an upright position 8 to 10 inches (20 to 30 cm) from the surface. Press the sprayhead to the side and spray the paint on the stain in either a circular or criss cross pattern.
6. To prevent clogging and to clean the sprayhead for future use, turn can upside down and push the sprayhead to the side for about 2 seconds, or until no more paint comes out.
7. Discard empty can in trash pick-up. DO NOT place in home garbage compactor.

Dry Time*:

To touch: 15 minutes

*At 70°F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*:

Flat
*as measured on a 60 degree gloss meter

DOT Placard:



VOC Compliancy:

Not available.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:

