

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor is dry before applying product. Store materials at room temperature prior to using. Apply material between 55-90° F. Product can be applied without a primer; however, any suitable primer can be used depending on application requirements. Mix the part A and part B together thoroughly (be certain the mix ratio is correct). After the part A and part B are mixed, add in the aggregate. Thoroughly mix to make sure all of the aggregate is wetted out properly. Apply the mixed mortar at the recommended thickness using a hand or power trowel or other suitable equipment.

CHEMICAL CONTENT:

MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, HYDROCARBON RESIN PROPRIETARY, Naphthalene CAS# 91-20-3, HYDROXY MODIFIED RESIN PROPRIETARY, BENZYL ALCOHOL CAS# 100-51-6, DIBENZYL ETHER CAS# 103-50-4, NAPHTHA, PETROLEUM, HYDRODESULFURIZED HEAVY CAS# 64742-82-1, Polyphosphoric acids, reaction products with 2-oxepanone and polyethylene glycol monomethyl ether CAS# 162627-21-6, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, Solvent Naphtha, petroleum, Light Aromatic CAS# 64742-95-6, Cumene (component of Solvent Naphtha, petroleum, light aromatic) CAS# 98-82-8, Phosphoric acid (residual) CAS# 7664-38-2. Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Titanium Dioxide (component of yellow pigment) CAS# 13463-67-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1, Aliphatic amine (trade secret), Triethylenetetramine CAS# 112-24-3, Tertiary Amine (trade secret), Crystalline Silica (quartz) CAS# 14808-60-7.

MIX RATIO: UNIT = 9# part A, 2.2# part B, 50# aggregate

DOT: Part A - Not Regulated, Part B - UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (TERTIARY AMINE), 8, PG III, Part C - Not Regulated

IMO/IMDG: Part A - UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Part B - UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (TERTIARY AMINE), 8, PG III, Part C - Not Regulated

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 3.5 grams per liter. Dispose of any empty containers in accordance with current regulations.

NEW & IMPROVED!

PRO
CHEM

SURE PATCH

Concrete Crack Repair

Sure Patch is a three component, 100% solids epoxy mortar designed for resurfacing and repairing damaged or inferior concrete. Recommended for heavy traffic areas or anywhere high strength and excellent wear characteristics are required.

Contains Parts: A, B, & C

LIGHT GRAY

#2095801



Sold By:
Pro Chem, Inc.
1475 Bluegrass Lakes Parkway
Alpharetta, GA 30004
800-241-8180 | procheminc.com



DANGER!

May cause cancer. Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system). May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes severe eye damage. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention.

IF eye irritation persists: Get medical advice/attention. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehydes and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.

FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.
OBSERVE PRODUCT CAUTION.