

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Remove all dirt and foreign contaminants. Make sure the joint is dry. All loose concrete and previous joint compound must be removed to leave a dry clean sound joint. For best results, edges should be saw cut and backer rods can be used to regulate depths to around 1/2 inch in joint. Mix part A and part B together at the correct mix ratio and mix well with slow speed mixing equipment until uniform in color and consistency being sure to scrape the sides and bottom of the mixing pail thoroughly. Avoid high speed mixing as this could force air into the product. Improper mixing will cause an incomplete cure and soft spots in the joint. Apply the mixed product by pouring the material into the expansion joint to be repaired. Remove any excess material either immediately with a putty knife or allow to cure until it can be cut with a razor type scraper at the joint level.

#### CHEMICAL CONTENT:

CASTOR OIL CAS# 8001-79-4, 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3, 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2, Precipitated Silica CAS# 112926-00-8, Aluminum Oxide Non-fibrous) CAS# 1344-28-1, Sodium oxide CAS# 1313-59-3, Magnesium Oxide CAS# 1309-48-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, Alkyl Quaternary Ammonium Clay CAS# Proprietary, Methyl N-Amyl Ketone CAS# 110-43-0, Dibutyltin Dilurate CAS# 77-58-7, Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4.

MIX RATIO: 1:1 by volume

DOT: Not Regulated.

IMO/IMDG: Not Regulated.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 1 gram per liter. Dispose of empty containers according to local, state and federal law.



## C-JOINT Floor Joint Sealer

C-Joint is a two component, 100% solids polymer system designed for applications where a resilient joint material is needed. Recommended for concrete/cement expansion joints in general industry.

### Part: A

### GRAY

#2095603



Sold By:  
**Pro Chem, Inc.**  
1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### WARNING!

May be Harmful if swallowed. Harmful if inhaled. May cause Respiratory irritation. Causes eye irritation. Causes mild skin irritation.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF SKIN irritation occurs: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

#### TO FIGHT FIRE:

Fight fires with foam, CO<sub>2</sub>, dry chemical or water fog. Use a self-contained breathing apparatus when fighting the fire. Hazardous decomposition products can be CO<sub>2</sub> and other organic compounds.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Remove all dirt and foreign contaminants. Make sure the joint is dry. All loose concrete and previous joint compound must be removed to leave a dry clean sound joint. For best results, edges should be saw cut and backer rods can be used to regulate depths to around 1/2 inch in joint. Mix part A and part B together at the correct mix ratio and mix well with slow speed mixing equipment until uniform in color and consistency being sure to scrape the sides and bottom of the mixing pail thoroughly. Avoid high speed mixing as this could force air into the product. Improper mixing will cause an incomplete cure and soft spots in the joint. Apply the mixed product by pouring the material into the expansion joint to be repaired. Remove any excess material either immediately with a putty knife or allow to cure until it can be cut with a razor type scraper at the joint level.

#### CHEMICAL CONTENT:

CASTOR OIL CAS# 8001-79-4, 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3, 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2, Precipitated Silica CAS# 112926-00-8, Aluminum Oxide Non-fibrous) CAS# 1344-28-1, Sodium oxide CAS# 1313-59-3, Magnesium Oxide CAS# 1309-48-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, Alkyl Quaternary Ammonium Clay CAS# Proprietary, Methyl N-Amyl Ketone CAS# 110-43-0, Dibutyltin Dilurate CAS# 77-58-7.

MIX RATIO: 1:1 by volume

DOT: Not Regulated.

IMO/IMDG: Not Regulated.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 1 gram per liter. Dispose of empty containers according to local, state and federal law.



**PRO**  
**CHEM**

## C-JOINT Floor Joint Sealer

C-Joint is a two component, 100% solids polymer system designed for applications where a resilient joint material is needed. Recommended for concrete/cement expansion joints in general industry.

**Part: A**

**CLEAR**

#2095603



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### WARNING!

May be Harmful if swallowed. Harmful if inhaled. May cause Respiratory irritation. Causes eye irritation. Causes mild skin irritation.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF SKIN irritation occurs: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

#### TO FIGHT FIRE:

Fight fires with foam, CO<sub>2</sub>, dry chemical or water fog. Use a self-contained breathing apparatus when fighting the fire. Hazardous decomposition products can be CO<sub>2</sub> and other organic compounds.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Remove all dirt and foreign contaminants. Make sure the joint is dry. All loose concrete and previous joint compound must be removed to leave a dry clean sound joint. For best results, edges should be saw cut and backer rods can be used to regulate depths to around 1/2 inch in joint. Mix part A and part B together at the correct mix ratio and mix well with slow speed mixing equipment until uniform in color and consistency being sure to scrape the sides and bottom of the mixing pail thoroughly. Avoid high speed mixing as this could force air into the product. Improper mixing will cause an incomplete cure and soft spots in the joint. Apply the mixed product by pouring the material into the expansion joint to be repaired. Remove any excess material either immediately with a putty knife or allow to cure until it can be cut with a razor type scraper at the joint level.

#### CHEMICAL CONTENT:

\*4,4'-DIPHENYLMETHANE DIISOCYANATE CAS# 101-68-8, Modified MDI

CAS# NOT LISTED.

MIX RATIO: 1:1 by volume

DOT: Not Regulated.

IMO/IMDG: Not Regulated.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 1 gram per liter. Dispose of empty containers according to local, state and federal law.



**PRO**<sup>®</sup>  
**CHEM**

## C-JOINT Floor Joint Sealer

C-Joint is a two component, 100% solids polymer system designed for applications where a resilient joint material is needed. Recommended for concrete/cement expansion joints in general industry.

### Part: B

#2095603



Sold By:

**Pro Chem, Inc.**  
1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May be harmful if inhaled. May cause respiratory irritation. May cause long lasting harmful effects to aquatic life

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear respiratory protection. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

#### TO FIGHT FIRE:

Fight fire with CO2, foam, or dry chemical. Hazardous decomposition products may be CO2, CO, NOX or HCN compounds. Fire fighters should wear a self-contained breathing apparatus. Product can react vigorously to water.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Remove all dirt and foreign contaminants. All loose concrete and previous joint compound must be removed to leave a dry clean sound joint. For best results, edges should be saw cut and backer rods can be used to regulate depths to around 1/2 inch in joint. This product has a very short pot life of 1-2 minutes and should be applied using plural component pump equipment or dispensed with a dual cartridge caulking gun using 3/8" diameter 40 element tip. ALWAYS dispense a small beginning portion onto cardboard to prevent non mixed material from entering joint.

#### CHEMICAL CONTENT:

\*4,4'-DIPHENYLMETHANE DIISOCYANATE CAS# 101-68-8, Modified MDI CAS# NOT LISTED, CASTOR OIL CAS# 8001-79-4, 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3, 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2, Precipitated Silica CAS# 112926-00-8, Aluminum Oxide Non-fibrous) CAS# 1344-28-1, Sodium oxide CAS# 1313-59-3, Magnesium Oxide CAS# 1309-48-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, Alkyl Quaternary Ammonium Clay CAS# Proprietary, Methyl N-Amyl Ketone CAS# 110-43-0, Dibutyltin Dilurate CAS# 77-58-7.

MIX RATIO: 1:1 by volume

DOT: Not Regulated.

IMO/IMDG: Not Regulated.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 1 gram per liter. Dispose of empty containers according to local, state and federal law.

**NEW & IMPROVED!**

**PRO**<sup>®</sup>  
**CHEM**

# C-JOINT

## Floor Joint Sealer

C-Joint is a two component, 100% solids polymer designed for applications where a resilient joint material is needed. Recommended for concrete/cement expansion joints in general industry

### CARTRIDGES

### CLEAR

#2095603



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May be harmful if inhaled. May cause respiratory irritation. May be Harmful if swallowed

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear respiratory protection. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

#### TO FIGHT FIRE:

Fight fire with CO<sub>2</sub>, foam, or dry chemical. Hazardous decomposition products may be CO<sub>2</sub>, CO, NO<sub>x</sub> or HCN or other organic compounds. Fire fighters should wear a self-contained breathing apparatus. Product can react vigorously to water.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.**  
**OBSERVE PRODUCT CAUTION.**