





SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	2095901	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	RAPID SET – NEW & IMPROVED – PART A	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Low Temperature Epoxy	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Acute Oral Toxicity - Category 4 Acute Toxicity Inhalation - Category 4 Skin Corrosion/Irritation - Category 2 Serious Eye Irritation - Category 2A Skin Sensitizer - Category 1B Chronic Hazards to Aquatic Environment - Category 2	SIGNAL WORD: DANGER	SYMBOL:		
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------	----------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

HAZARD STATEMENTS:

Warning: Harmful if swallowed.
Warning: Harmful if inhaled.
Warning: Causes skin irritation.
Warning: May cause an allergic skin reaction.
Warning: Causes serious eye irritation.
Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

Prevention: P102 Keep out of reach of children.
P103 Read label before use.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 IF eye irritation persists: Get medical advice/attention.
P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.
P330 Rinse mouth.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 If inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.
P391 Collect spillage.

Disposal: P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

POTENTIAL HEALTH EFFECTS

Eyes: May cause irritation but no corneal injury is likely.
Skin: May cause irritation or allergic skin response.
Ingestion: This material has a probable low acute oral toxicity.
Inhalation: No guide for control known, however, exposure to heated vapors can cause irritation to the nose, throat or mucous membranes.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Epoxy resins can cause sensitization by exposure through contact or high concentration of vapor.

Eyes: Injury if unlikely but stain for evidence of corneal injury.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Respiratory conditions or other allergic ailments.

CARCINOGENICITY:

OSHA: NO NTP: Yes IARC: Yes

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - **Explanation of Carcinogenicity:** IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. Also see Section 11 and Section 15.

Some Colors may Contain Titanium Dioxide. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

OTHER NON-CLASSIFIABLE POTENTIAL HAZARDS:

Carcinogen Category 2

3. Composition / Information on Ingredients					
Chemical Name	CAS	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	NONE	NONE	NONE	60-100
Alkyl Glycidyl Ether	68609-97-2	NONE	NONE	NONE	10-30
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	10-30
Colors may contain @ 3-7%:					
Carbon black (in colors)	1333-86-4	3.5 ppm	3.5 ppm	NONE	<1.0
TITANIUM DIOXIDE (IN COLORS)	13463-67-7	10mg/m3	10mg/m3	5mg/m3	<3.0
Precipitated Silica	112926-00-8	NONE	80mg/m3	NONE	
Iron III oxide	1309-37-1	NONE	5mg/m3	NONE	
Yellow Pigment	Not available	NONE	NONE	NONE	
Zinc Sulfide (component of yellow pigment)					
	1314-98-3	NONE	NONE	NONE	
Barium Sulfate (component of yellow pigment)					
	7727-43-7	NONE	NONE	NONE	
Titanium Dioxide (component of yellow pigment)					
	13463-67-7	NONE	NONE	NONE	
Pigment yellow 65 (component of yellow pigment)					
	6528-34-3	NONE	NONE	NONE	
Iron III hydroxide	20344-49-4	15mg/m3	5mg/m3	NONE	
C.I. Pigment Blue	147-14-8	1mg/m3	1mg/m3	NONE	
Aluminum Oxide	1344-28-1	15mg/m3	10mg/m3	NONE	
Silica, amorphous	7631-86-9	80mg/m3	10mg/m3	NONE	
Iron Oxide Yellow	51274-00-1	15mg/m3	10mg/m3	NONE	
Silica, amorphous	7631-86-9	80mg/m3	10mg/m3	NONE	
SECTION 3 NOTES: (*) Indicates toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.					
Note: Ingredients listed without percentages, the percentages are considered a trade secret.					

4. First Aid Measures	
EMERGENCY OVERVIEW	
EYES:	Flush eyes with water for at least fifteen minutes and consult a physician.
SKIN:	Skin contact will normally cause no more than irritation but wash affected area with soap and water and remove contaminated clothing promptly.
INHALATION:	Remove victim to fresh air and administer oxygen if necessary.
INGESTION:	Low in toxicity, induce vomiting only if large amounts of material are ingested, and otherwise do not induce vomiting. In either case consult with a physician.

5. Fire-Fighting Measures	
FLAMMABLE LIMITS IN AIR, (% by volume)	UPPER: Not available. LOWER: Not available.
FLASH POINT: 200+F	
METHOD USED:	Seta Flash
EXTINGUISHING MEDIA:	Foam, alcohol foam, CO2, dry chemical, water fog
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Cool all fire exposed containers with water.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None known.

6. Accidental Release Measures	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	
Wear respirator and protective clothing. Shut off the source at the leak. Remove excess with vacuum truck and take up the remainder with an absorbent such as clay and place in disposal containers. Flush area with water to remove residue.	

7. Handling and Storage	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:	
Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the SDS's of all the components prior to using material. Properly label all containers.	
OTHER PRECAUTIONS:	
Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles can not be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof.	

8. Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Splash goggles or glasses with side shields.

Skin Protection:

Protective Gloves: Impervious gloves – neoprene or rubber.

Other Protective Clothing or Equipment: Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Respiratory Protection: Use a NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134. General exhaust is usually sufficient in lieu of NIOSH respirator.

Ventilation: General exhaust is usually sufficient to control vapors and exposure hazards.

Work Hygienic Practices: Observe good general hygienic practices.

*See Section 3 for occupational exposure limit values.

9. Physical & Chemical Properties

Appearance & Odor:	Low viscosity liquid – amber color	Vapor Density (AIR=1):	Not applicable.
Odor Threshold:	Not applicable.	Vapor Pressure:	Not applicable.
pH:	Not applicable.	Solubility (water):	Negligible.
Melting/Freezing Point:	Not applicable.	Auto-Ignition Temp:	Not applicable.
Boiling Point/Range:	200°F to 375°F	Decomposition Temp:	Not applicable.
Specific Gravity (H2O=1):	1.1	Partition Coeff(n-octanol/water):	Not applicable.
Evaporation Rate:	Not applicable.		

10. Stability & Reactivity Information

STABILITY:

Stable.

CONDITIONS TO AVOID (STABILITY):

Avoid excessive heat or open flames.

INCOMPATIBILITY (MATERIAL TO AVOID):

Can react vigorously with strong oxidizing agents and strong lewis acids or mineral acids.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO₂, aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. Toxicological Information

No data for the product itself.

Component Data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B.

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

Component CAS# 112926-00-8: LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

Component Iron III oxide CAS# 1309-37-1: Acute Oral Toxicity LD50 >5000 mg/kg (rat), Acute Dermal Toxicity LD50 >5000 mg/kg (rat)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200. Acute oral value of 20 gm/kg or greater in rats

Component Iron III hydroxide CAS# 20344-49-4: Acute Oral Toxicity LD50 >5000 mg/kg (rat).

Component CAS# 2210-79-9: Acute Health Hazard -Ingestion : LD50 : 5,800 mg/kg Species : Rat. Inhalation : LC50 (4 h) : 1220 ppm Species : Rat. Skin. : LD50 : > 2,000 mg/kg Species : Rabbit. Method : Estimated. Eye irritation/corrosion : Mild eye irritation Acute dermal irritation/corrosion : Severe skin irritation. Sensitization : May cause sensitization by skin contact.

12. Ecological Information

No data for the product itself.

Component Data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

Component Carbon LD50 – Intravenous, mouse = 440 mg/kg

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD₂ 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (Lepomis macrochinus), LC50 (96hr) 460 mg/l Fathead minnow (Pimephales promelas), Toxicity to Algae: IC50 (72hr) 700 mg/l

Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component CAS# 112926-00-8: Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l

Component Iron III oxide CAS# 1309-37-1: Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Acute toxicity to Aquatic Invertebrates EC0 > 10000 mg/l (water flea). Toxicity to Microorganisms EC0 > 1000mg/l (pseudomonas putida)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.
Component Iron III hydroxide CAS# 20344-49-4: Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Toxicity to Microorganisms EC0 > 10000mg/l (pseudomonas putida)

13. Disposal Consideration

WASTE DISPOSAL METHOD:

Dispose of the material in a waste disposal site in accordance with local, state and federal law.

14. Transportation Information

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Marine Pollutant

15. Regulatory Information

No data for the product itself.

Component Data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component Carbon: Contains Proposition 65 Chemicals. Carbon: is listed on TSCA and DSL Canada

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List. Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 112926-00-8: Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,

Component Iron III oxide CAS# 1309-37-1: Listed on TSCA Inventory. Section 313/312 hazard category: Chronic health hazard. Potential exposure to all of the California proposition 65 have been determined to be below the No significant risk level (NSRL). Component and its impurities (1%) are on the Pennsylvania, New Jersey right to know substance lists. Component contains the following chemicals listed on the New Jersey and Pennsylvania RTK special hazardous Substance lists: Manganese CAS# 7439-96-5 (0.7%) and Aluminum CAS# 7429-90-5 (0.29%). Component contains the following ingredients which are on the Pennsylvania, Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.075%) and Nickel CAS# 7440-02-0 (0.04%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.04%) and Cobalt CAS# 7440-48-4 (30 ppm).

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Iron III hydroxide CAS# 20344-49-4: Listed on TSCA Inventory. Potential exposure to all of the California proposition 65 chemicals have been determined to be below the No significant risk level (NSRL). Components are on the Pennsylvania right to know substance list.

Component contains the following chemicals listed on the Pennsylvania RTK special hazardous Substance lists: chromium CAS# 7440-47-3 (0.02%) and nickel CAS# 7440-02-0 (0.015%).

Component contains the following ingredients which are on the Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.02%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Nickel CAS# 7440-02-0 (0.015%)

Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70ppm)..

Component CAS# 147-14-8: Component is on the TSCA List. and not controlled under WHMIS. Component is a CERCLA hazardous substance

Component CAS# 1344-28-1: Component is on the Massachusetts, New Jersey, Pennsylvania right to know lists. Component is on TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

Component CAS# 51274-00-1: Component is on the TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	2095901	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	RAPID SET – NEW & IMPROVED – PART B	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Low Temperature Epoxy	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Specific Target Organ Toxicity Following Repeated Exposure - Category 2 Skin Corrosion/Irritation - Category 1B Skin Sensitizer - Category 1B Serious Eye Damage - Category 1 Acute Toxicity Inhalation - Category 4 Germ Cell Mutagenicity - Category 2 Acute Dermal Toxicity - Category 4 Acute Hazard to Aquatic Environment - Category 2 Chronic Hazards to Aquatic Environment - Category 2	SIGNAL WORD: DANGER	SYMBOL:				
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------	----------------	--	--	--	--

HAZARD STATEMENTS:

Warning: May cause damage to organs (kidneys, liver, pancreas and spleen, and edema to the lungs) through inhalation and skin absorption through prolonged or repeated exposure.
 Danger: Causes severe skin burns and eye damage
 Warning: May cause an allergic skin reaction
 Danger: Causes serious eye damage
 Warning: Harmful if inhaled
 Warning: Suspected of causing genetic defects.
 Warning: Harmful in contact with skin.
 Toxic to aquatic life
 Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Prevention: P102 Keep out of reach of children.
 P103 Read label before use
 P260 Do not breathe dust/fume/gas/mist/vapours/spray
 P264 Wash hands thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P273 Avoid release to the environment.
Response: P314 Get medical advice/attention if you feel unwell
 P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
 P363 Wash contaminated clothing before reuse.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P321 If skin irritation or burns develop, Call a doctor/physician.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302 + P352 IF ON SKIN: wash with plenty of soap and water.
 P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
 P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.
 P310 IF IN EYES, immediately call a POISON CENTER or doctor/physician.
 P312 IF INHALED, call a POISON CENTER or doctor/physician if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P391 Collect spillage
Storage: P405 Store locked up
Disposal: P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

POTENTIAL HEALTH EFFECTS

Eyes: Will cause burns to eyes. High vapor concentrations can cause severe irritation to the eyes.
Skin: Can cause skin irritation or possible burns to the skin.
Ingestion: Liquid can cause severe damage to mucous membranes if swallowed.
Inhalation: High concentrations of vapor can cause irritation to the respiratory tract, nausea and dizziness.

HEALTH HAZARDS (ACUTE AND CHRONIC):
Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Respiratory conditions or other allergic ailments.

CARCINOGENICITY:
OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:
No listed ingredients of this product are regulated as carcinogens.

3. Composition / Information on Ingredients

Chemical Name	CAS	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
*PHENOL	108-95-2	5ppm	5ppm	10ppm	15.0
M-XYLENE DIAMINE	1477-55-0	NONE	.1mg/m3	NONE	10-30
Benzene-1, 3-Dimethanamine/Phenol/Formaldehyde					
	57214-10-5	NONE	NONE	NONE	40-70

SECTION 3 NOTES: (*)Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372 are present.* Note: Ingredients listed without percentages, the percentages are considered a trade secret.**

4. First Aid Measures

EMERGENCY OVERVIEW

EYES: Immediately flush eyes with water for at least fifteen minutes while lifting upper and lower lids. Get immediate medical assistance.

SKIN: Flush skin with water for at least 15 minutes and remove all contaminated clothing immediately. Get medical attention if reddening or swelling occurs.

INHALATION:
Remove victim to fresh air and administer oxygen if necessary.

INGESTION:
Do not induce vomiting. Dilute by giving water or milk to drink if victim is conscious. Get medical attention immediately.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:
Not applicable.

5. Fire-Fighting Measures

FLAMMABLE LIMITS IN AIR, (% by volume) **UPPER:** Not available.
LOWER: Not available.

FLASH POINT: 200+F

METHOD USED:
Seta Flash

EXTINGUISHING MEDIA:
Foam, alcohol foam, CO2, dry chemical, water fog

SPECIAL FIRE FIGHTING PROCEDURES:
Toxic fumes will be evolved when this material is involved in a fire. A self-contained breathing apparatus should be available for firefighting. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
None known.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Avoid contact with material. Wear the appropriate safety equipment. Stop spill at source, dyke area to prevent spreading. Pump liquid to salvage tank. Take up remainder with clay or other absorbent and place in disposal containers.


7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
Avoid all skin contact. Avoid breathing vapors. Reseal partially used containers. Properly label all containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices.

OTHER PRECAUTIONS:
Mixed materials contain the hazards of all the components, therefore, read the SDS of all components to become familiar with all hazards prior to using this product.

8. Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Splash goggles or glasses with side shields.

Skin Protection:
Protective Gloves: Impervious gloves – neoprene or rubber
Other Protective Clothing or Equipment: Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Respiratory Protection: NIOSH approved respirator protection required in the absence of proper environmental controls. For emergencies a self-contained breathing apparatus or a full face respirator is recommended.

Ventilation: Avoid breathing vapors. Ventilation must be sufficient to control vapors.

Work Hygienic Practices: Observe good general hygienic practices.

***See Section 3 for occupational exposure limit values.**

9. Physical & Chemical Properties			
Appearance & Odor:	Amber clear liquid with amine odor.	Vapor Density (AIR=1):	Not applicable.
Odor Threshold:	Not applicable.	Vapor Pressure:	Not applicable.
pH:	Not applicable.	Solubility (water):	Negligible.
Melting/Freezing Point:	Not applicable.	Auto-Ignition Temp:	Not applicable.
Boiling Point/Range:	401°F	Decomposition Temp:	Not applicable.
Specific Gravity (H2O=1):	1.0	Partition Coeff(n-octanol/water):	Not applicable.
Evaporation Rate:	Not applicable.		

10. Stability & Reactivity Information	
STABILITY: Stable.	
CONDITIONS TO AVOID (STABILITY): Avoid contact with open flames and all sources of ignitions and sparks.	
INCOMPATIBILITY (MATERIAL TO AVOID): Avoid contact with strong oxidizing agents mineral acids and epoxy resins in uncontrolled amounts.	
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: CO, CO2, NOX	
HAZARDOUS POLYMERIZATION: Will not occur.	

11. Toxicological Information	
No data for the product itself.	
Component Data:	
For the Components. *PHENOL, M-XYLENE DIAMINE and Benzene-1, 3-Dimethaneamine/Phenol/ Formaldehyde: Ingestion LD50 > 2200 mg/kg (rat), Inhalation LC50 (1h) > 20mg/l (rat), Skin LD50 > 1000 mg/kg (rabbit) all estimated. Eye Irritation – Severe eye irritant, Acute dermal irritation – severe skin irritant.	
PHENOL: Adsorption of phenolic solutions through the skin may be very rapid and can cause death. Lesser exposures can cause damage to the kidneys, liver, pancreas and spleen, and edema to the lungs. Chronic exposures can cause death from liver and kidney damage.	

12. Ecological Information	
No data for the product itself.	
Component data:	
PHENOL: Toxicity to Daphnia EC50 (48h) 4.2 mg/l; EC50 (48h) 5.55 mg/l; EC50 (48h) 6.6 mg/l. This component has a low bioaccumulation potential.	

13. Disposal Consideration	
WASTE DISPOSAL METHOD: Dispose of material as a hazardous waste according to federal, state and local regulations.	

14. Transportation Information	
DOT: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS PHENOL SOLUTIONS, M-XYLENE DIAMINE), 8, PG III	
IMO/IMDG: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS PHENOL SOLUTIONS, M-XYLENE DIAMINE), 8, PG III, MARINE POLLUTANT	

15. Regulatory Information	
No data for the product itself.	
Component data:	
For the Components. *PHENOL, M-XYLENE DIAMINE and Benzene-1, 3-Dimethaneamine/Phenol/ Formaldehyde: Components are on the TSCA list as well as EINECS, DSL, AICS, ENCS, ECK, SEPA, and PICCS inventory lists.	
PHENOL: Is a SARA Title III Section 313 Component above the 'de minimus' level.	
This product does not contain any California proposition 65 chemicals. WHMIS hazard classification: Toxic Material Causing Immediate and Serious Toxic effect, Toxic material causing other toxic effects, Corrosive material.	

16. Other Information	
DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.	





SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	2095901	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	RAPID SET – NEW & IMPROVED – PART C	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Low Temperature Epoxy	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Carcinogenicity Category 1, Specific target organ toxicity following repeated exposure Category 1, Specific target organ toxicity (single exposure) Category 3	SIGNAL WORD: DANGER	SYMBOL:		
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------	----------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

HAZARD STATEMENTS:

DANGER: May cause cancer.
DANGER: Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system).
WARNING: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS:

Prevention: P102 Keep out of reach of children.
P103 Read label before use.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P270 Do not eat, drink or smoke when using this product.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
Response: P308 + P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage: P405 Store locked up.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
Disposal: P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

POTENTIAL HEALTH EFFECTS

Eyes: May cause reddening of the eyes or eye irritation from airborne particles.
Skin: None known.
Ingestion: None known.
Inhalation: Prolonged exposure to respirable crystalline quartz may cause delayed lung injury (silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure in some applications such as sand blasting.

HEALTH HAZARDS (ACUTE AND CHRONIC):

May cause delayed silicosis or rapid silicosis in some occupations such as sandblasting, silicosis is a form of a disabling pulmonary fibrosis which can be progressive and could lead to death. Inhalation may lead to lung scarring and massive fibrosis which could be accompanied by right heart enlargement, heart failure, or pulmonary failure, smoking aggravates the effects of exposure.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Respiratory conditions or other allergic ailments can be aggravated by exposure.

CARCINOGENICITY:

OSHA: NO **NTP:** YES **IARC:** YES

ADDITIONAL CARCINOGENICITY INFORMATION:

IARC has determined that crystalline silica inhaled in the form of quartz is carcinogenic to humans (group 1- carcinogenic to humans). The NTP classifies respirable crystalline silica as reasonably anticipated to be a carcinogen.

3. Composition / Information on Ingredients

Chemical Name	CAS	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
SILICON DIOXIDE	14808-60-7	0.05 mg/m ³	0.025 mg/m ³	0.05 mg/m ³	100

SECTION 2 NOTES: (No toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372 are present.**)**

Follow OSHA Hazard Communication Rule 29CFR Sections 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, and state and local community right to know laws. We recommend that smoking be prohibited in areas where respirators must be used.

4. First Aid Measures

EMERGENCY OVERVIEW

EYES: Flush eyes with water for at least fifteen minutes and consult a physician if conditions warrant.

SKIN: Skin contact will normally cause no health risks.

INHALATION:

Remove victim to fresh air and administer oxygen if necessary.

INGESTION:

If ingested, consult a physician.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

Not applicable.

5. Fire-Fighting Measures

FLAMMABLE LIMITS IN AIR,
(% by volume)

UPPER: Not available.

LOWER: Not available.

FLASH POINT: N/A

METHOD USED:

N/A

EXTINGUISHING MEDIA:

Other

SPECIAL FIRE FIGHTING PROCEDURES:

Crystalline silica is neither a fire nor an explosion hazard.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wear respirator and use dustless handling equipment to clean up large spills, place in suitable containers for disposal. Flush area with water after pickup of material.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in cool dry place. Properly label all containers and reseal all partially used containers. Avoid creating any dust when working with this material.

OTHER PRECAUTIONS:

Avoid breathing dust generated from the material. Observe conditions of good general hygiene and safe working practices. Provide training for your employees relating to occupational exposure to quartz dust. See ASTM standard E1132-86 standard practice for health requirements relating to exposure to quartz dust. If better than 500 x PEL use a self-contained breathing apparatus. If sandblasting, use any Type CE supplied air respirator with full face piece or hood.

SAFETY PHRASES:

S22 Do not breathe dust.

S25 Avoid contact with eyes.

S38 In case of insufficient ventilation wear suitable respiratory equipment.

S39 Wear eye/face protection.

8. Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: Splash goggles or glasses with side shields.

Skin Protection:

Protective Gloves: N/A

Other Protective Clothing or Equipment: Provide any equipment necessary to prevent the inhalation of quartz dust.

Respiratory Protection: Use a NIOSH approved respirator as required to prevent over-exposure to quartz dust. Provide sufficient exhaust to keep exposure levels below the ACGIH PEL.

Ventilation: Use exhaust sufficient to maintain airborne particulates below the ACGIH PEL limits established.

Work Hygienic Practices: Observe good general hygienic practices.

***See Section 3 for occupational exposure limit values.**

9. Physical & Chemical Properties

Appearance & Odor:	White of tan sand granular crushed or ground- no odor.	Vapor Density (AIR=1):	Not applicable.
Odor Threshold:	Not applicable.	Vapor Pressure:	Not applicable.
pH:	Not applicable.	Solubility (water):	Insoluble in water.
Melting/Freezing Point:	Not applicable.	Auto-Ignition Temp:	Not applicable.
Boiling Point/Range:	Not applicable.	Decomposition Temp:	Not applicable.
Specific Gravity (H2O=1):	2.6	Partition Coeff(n-octanol/water):	Not applicable.
Evaporation Rate:	Not applicable.		

10. Stability & Reactivity Information

STABILITY:

Stable.

CONDITIONS TO AVOID (STABILITY):

Contact with powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, oxygen trifluoride.

INCOMPATIBILITY (MATERIAL TO AVOID):

Can react vigorously with strong oxidizing agents- see conditions to avoid.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

Silica will dissolve in hydrochloric acid to form a corrosive gas- silicon tetrafluoride.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. Toxicological Information

Silicon Dioxide: Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute. Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

12. Ecological Information

Silicon Dioxide: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

13. Disposal Consideration**WASTE DISPOSAL METHOD:**

Dispose of the material in a waste disposal site in accordance with local, state and federal laws.

14. Transportation Information

DOT: Not regulated.

IMO/IMDG: Not regulated.

15. Regulatory Information

Silicon Dioxide: Risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation. Safety Phrases: S 22 – Do not breathe dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment.

Crystalline Silica (Silicon Dioxide) is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Crystalline Silica (Silicon Dioxide) is on the Canada DSL – WHMIS Classification D2A

Crystalline Silica is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with registry number 9212-5667 and the Philippines Inventory of Chemicals and Chemical Substances list.

16. Other Information

N/A = Not available.

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.