

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, CYCLOALIPHATIC AMINE ADDUCT CAS# 68609-08-5, NONYL PHENOL CAS# 84852-15-3, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III.

**IMO/MDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 gram per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY BLACK

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Black is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Contains Parts: A & B

#244821



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging the fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS)). Suspected of causing genetic defects. Harmful if inhaled. Toxic to aquatic life Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust, fume, gas, mist, vapours, spray. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. IF SKIN irritation, rash or burn occurs: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO and NO<sub>x</sub> compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, CYCLOALIPHATIC AMINE ADDUCT CAS# 68609-08-5, NONYL PHENOL CAS# 84852-15-3, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III.

**IMO/MDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 gram per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY YELLOW

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Yellow is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Contains Parts: A & B

#244831



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging the fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS). Suspected of causing genetic defects. Harmful if inhaled. Toxic to aquatic life Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust, fume, gas, mist, vapours, spray. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. IF SKIN irritation, rash or burn occurs: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO and NO<sub>x</sub> compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush, or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)

**DOT:** Not Regulated.

**IMO/IMDG:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 grams per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY YELLOW

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Yellow is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Part: A

#244831



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### WARNING!

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Wear protective gloves and clothing, eye and face protection. Avoid breathing dust, fume, gas, mist, vapours, spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fires with foam, CO<sub>2</sub>, dry chemical or water fog. Use a self-contained breathing apparatus when fighting the fire. Hazardous decomposition products can be CO<sub>2</sub>, acids and aldehydes.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.**

**OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, CYCLOALIPHATIC AMINE ADDUCT CAS# 68609-08-5, NONYL PHENOL CAS# 84852-15-3,

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)

**DOT:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III.

**IMO/IMDG:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 gram per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY YELLOW

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Yellow is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Part: B

#244831



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging the fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS)). Suspected of causing genetic defects. Harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust, fume, gas, mist, vapours, spray. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation, rash, or burn occurs, call a doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.**

**OBSERVE PRODUCT CAUTION.**

#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush, or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)

**DOT:** Not Regulated.

**IMO/IMDG:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 grams per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY BLACK

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Black is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Part: A

#244821



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### WARNING!

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Wear protective gloves and clothing, eye and face protection. Avoid breathing dust, fume, gas, mist, vapours, spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fires with foam, CO<sub>2</sub>, dry chemical or water fog. Use a self-contained breathing apparatus when fighting the fire. Hazardous decomposition products can be CO<sub>2</sub>, acids and aldehydes.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.**

**OBSERVE PRODUCT CAUTION.**



#### APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90°F - lower temperatures will require more time for material to cure. Check all coats for epoxy blushes. Mix the Part A and Part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove any entrapped air. Apply material with the R.H. below 85%.

#### CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, CYCLOALIPHATIC AMINE ADDUCT CAS# 68609-08-5, NONYL PHENOL CAS# 84852-15-3,

**MIX RATIO:** 12# PART A TO 4.15# PART B (BY WEIGHT); TWO PARTS A TO ONE PART B (BY VOLUME)(VOLUMES APPROXIMATE)

**DOT:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III.

**IMO/IMDG:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

Read the SDS's for all components prior to using. Read our technical data as it contains our warranty and limitations to our liability. For industrial use only. For professional use only. Apply material without thinning. This material has a maximum VOC of 2 gram per liter. Dispose of empty containers according to local, state and federal law.



# FIRM GRIP II EPOXY BLACK

## Two-Part High Build Epoxy Coating

Firm Grip II Epoxy Black is a two component, 100% (+/- 1%) solids, colored epoxy coating, designed for applications where a high build, colorfast, impact resistant floor is needed. Recommended for a high build topcoat or basecoat on concrete or masonry. Product is suitable in many chemical exposure environments.

## Part: B

#244821



Sold By:

**Pro Chem, Inc.**

1475 Bluegrass Lakes Parkway  
Alpharetta, GA 30004  
800-241-8180 | procheminc.com



#### DANGER!

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging the fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS)). Suspected of causing genetic defects. Harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust, fume, gas, mist, vapours, spray. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation, rash, or burn occurs, call a doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

#### TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.

**FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN.  
OBSERVE PRODUCT CAUTION.**