

# FLOOR MARKING TAPES #82111

Laminated Polyester Floor Marking Tape



## Features:

- ANSI Standard Z535.1 for color
- Average dry BPN: 125 (Dynamic slip resistance using ASTM E303-93 (2013) pendulum test method)
- Average dry dynamic coefficient of friction: Overall average: Dry 0.60
- ANSI A137.1 flooring slip resistance test (Dry)
- Size: 4" x 100'
- Safety Yellow (821111), Safety Blue (821112), White (821114), Safety Red (821115)



## Description:

FLOOR MARKING TAPES provide a long-lasting solution for marking floors, aisles, walkways, and workflow in your facilities. This extra-tough, low profile, easy to apply floor marking product is made with thick polyester materials making this tape highly durable, as well as abrasion and chemical resistant.

The rigid construction makes this tape easy to install as well as easy to clean and maintain. The aggressive adhesive will bond to most floors making this tape resistant to tearing, wrinkling or lifting even under heavy forklift traffic. Once applied, the low-profile design makes this tape a great choice for use in areas with the forklift, hand truck, or pedestrian traffic. Removes from most floor surfaces cleanly without chipping, tearing or leaving unsightly adhesive residue.

## Applications:

- Warehouses
- Municipalities
- Forklift Area
- Utilities
- Garages
- Public Safety