

LITHO-LUBE II 30T #2724

Lithium Complex Multi-Purpose Grease



Features:

- Dropping point 500°F (ASTM D566)
- Excellent pressure resistance
- Excellent shearability, shelf life, water resistance & anti-corrosion properties
- Timken OK Load of 30 pounds
- Temperature Range: 0°F to 300°F (-18°C to 150°C)
- NLGI 2
- Lithium complex thickener
- Base Oil: Mineral Oil



Description:

LITHO-LUBE II – 30 Pounds is a Lithium Complex grease formulated as a wide-ranging multi-purpose grease with pressure resistance, shearability, shelf life, water resistance, and anti-corrosion properties, offering the additional protection to meet today's high-performance requirements.

Applications:

- Wheel Bearings
- Axle Assemblies
- Universal Joints
- Pivot Pins
- Fifth-Wheel Hitch Plate
- Steering Linkages
- Spring Pins
- King Pins
- Ball Joints
- Water Pump Bearings
- Roller Bearings
- Plain Bearing
- Thrust Bearings
- Gears
- Electric Motors
- Presses
- Winches
- Hinges
- Latches
- Slides
- Pivot Points
- Bushings
- Bus & County Barns
- Ball Joints
- Universal Joints
- Chassis Lubrication
- Tie-Rod Ends & Steering Knuckles
- Tractor, Mowers & Farm Equipment
- Snow Blowers
- Couplings

Product Characteristics:

Appearance:	Amber semi-solid, mild odor
Color:	Amber
Odor:	Mild Odor
Vapor Pressure:	No data
Solubility (water):	Insoluble in water, soluble in alcohols and petroleum distillates
Relative Density:	0.9
Flash Point:	235°C (455°F) (Cleveland open cup)
Evaporation Rate:	No data
Storage:	Electrical installations/working materials must comply with the technological safety standards.
Transport Information:	
UN Number:	Not regulated
Proper Shipping Name:	Not regulated
Class:	Not regulated
Packing Group:	Not regulated

Directions:

Pump in grease until all old grease comes out. For best results, it is advisable that old grease be removed prior to application.

DO NOT USE ON OXYGEN SERVICE.

Signal Word: None.

Pictograms:



Personal Protective Equipment Required:



DOT Placard:

Not regulated as dangerous goods or hazardous material.