

# DRAIN TAMER #2121201

Drain and Sewer Opener and Maintainer



## Features:

- Fast-acting, odorless and convenient to use
- Opens drain and sewers by dissolving, liquefying and loosening clogs
- Formula is heavier than water allowing it to sink through water to open clogs
- Thick formula sinks to blockage
- Ready-to-use



## Description:

DRAIN TAMER is an odorless, liquid drain and sewer opener dissolves and liquefies fats, oils, hair and other organic matter to keep them open and free flowing. Its powerful formula is heavier than water, so it sinks quickly to the point of obstruction and immediately starts to penetrate and dissolve the blockage. It can be used as a drain maintainer since regular use at weekly intervals can keep problem drains free of blockages.

## Applications:

- Sewer Laterals
- Sewer Mains
- Drains

## For Use On:

- Fats & Oils
- Lint
- Hair
- Paper
- Organic Matter

## Product Characteristics:

Appearance:	Clear to hazy liquid
Physical State:	Liquid
Odor:	Mild Odor
Boiling Point:	No data available
Solubility:	Soluble in water - complete
VOC Content:	0%
Flash Point:	No data available
Specific Gravity/Density:	1.51 g/ml
pH:	14.0
Storage:	Keep container closed when not in use. Store in original container. Store in a dry place. Store in a closed container. Keep cool.
<b>Transport Information:</b>	
UN Number:	UN3266
Proper Shipping Name:	Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide, Potassium Hydroxide)
Class:	8
Packing Group:	II

## Directions:

**FOR SEWER MAINS:** Pour 2-4 gallons into manhole or drain upstream and as close to the obstruction as possible. For best results, use regularly to keep sewer main open and free flowing.

**FOR LATERALS:** Pour 1 gallon into drain upstream and as close to the obstruction as possible.

**FOR DRAINS:** Pour ½ - 1 quart slowly into the drain. Allow to work for 30 minutes. For difficult obstructions, a second application maybe be necessary.

Where there is a history of obstructions, the regular use of this product at weekly intervals (or more often if required) will keep the line open and free flowing.

## DOT Placard:

Not available.

## VOC Compliancy:

Yes.

## Pictograms:



## Signal Word:

DANGER.

## Personal Protective Equipment Required:

