DRAIN COAT #2418

Thick Organic Build-Up Eliminator

Features:

- Clinging formula digests fats, oils and greases (FOG)
- Pleasant fragrance/odor control
- Reduces suspended solids
- Non-toxic, non-acid, non-alkaline, non-polluting, non-pathogenic, biodegradable
- Contains seven strains of non-toxic bacteria
- Can also be used to deodorize carpet



Description:

DRAIN COAT has a unique thickened formula which clings to sides of pipes and drain lines, increasing contact for more effective treatment. Digests and liquefies organic build-up, grease and food by-products in hospitals, nursing homes, schools, prisons, funeral homes, apartments, kennels, clinics, porta-toilets, marinas, and septic tanks. Contains seven strains of non-toxic bacteria. **Note:** This product performs best within a pH range of 5.5 – 8.5. Optimal temperature range for maximum effectiveness is 54° – 113°F; effective up to 212°F. Extremes of pH and temperature, as well as wide shifts in either parameter over a short period of time should be avoided. Cold temperatures reduce the effectiveness of the product and no bacteria activity can be expected below 40°F.

Applications:

- Grease Traps
- Sewer & Drain Lines
- Down Pipes
- Septic Tanks
- Portable Toilets
- RVs

Product Characteristics:

Appearance:	Thick, opaque, pink liquid
Odor:	Floral
Evaporation Rate:	Slow
Specific Gravity:	1.00
Viscosity:	7400 cps
Boiling Point:	212°F
VOC:	0%
Vapor Pressure:	17.5 @ 77°F (25°C)
Vapor Density:	> 1 @ 77°F (25°C)
Solubility(water):	100%
Cold Stability:	32°F
Flash Point:	Not available
(%) Volatile by Volume:	100%
pH:	8.5
Storage:	Store in a cool, dry area away from extremes of temperature. Keep container tightly sealed when not in use. Keep out of the reach of children.
Transport Information:	
Proper Shipping Name:	Cleaning Compound, N.O.S
UN Number:	Not available
Hazard Class/Division:	None
Packing Group:	None

Directions:

SHAKE/STIR WELL BEFORE USE.
GENERAL ODOR CONTROL: To eliminate odor caused by vomit, spoiled food, decomposed animals, waste receptacles, etc., spray directly on malodor and allow bacterial action to work. The added fragrance will quickly neutralize any odor.
CARPET DEODORIZING AND ORGANIC WASTE: Apply directly to malodor and allow bacterial action to work. The added fragrance will quickly neutralize any odor.
GREASE TRAPS: Pour directly into sink or pipe closest to trap, typically at night. Flush down with a cup of lukewarm water. Use 4-5 oz. daily for traps less than 20 cu. ft. For larger traps, use 8-10 oz. daily.
PORTA-TOILETS: Directly add 1 gallon and cover the solids with water. Repeat each time toilet is pumped.
SEPTIC TANKS: Add 1 pint per 25 cu. ft. for initial treatment. Then use 8 oz. per week. Pour directly into toilet. If tank is clogged and odorous, add 1 gallon directly through tank manhole.
DRAIN LINES AND DOWN PIPES: Use 4 oz. for each 2 inches of pipe size 2-4 times weekly.
RECREATIONAL VEHICLES: Initially use 2 oz. per gallon of water. Maintain at 1 oz. per gallon of water. For use at a dump station, use 1 gallon per 50 gallons tank capacity. Maintain at 1 pint per week.
CERTIFIED SALMONELLA AND E. COLI FREE

Note: This product is most effective between a pH range of 5.5 – 8.5. Ideal temperature range for maximum performance is 54° – 113°F; effective up to 212°F. Avoid extreme changes in either temperature, pH and wide shifts in either parameters over a short period of time. Colder temperatures lower the effectiveness of the product and there is no bacteria activity under 40°F.

Pictograms:



DOT Placard:
Not regulated.

Signal Word:

DANGER.

Personal Protective Equipment Required:

