

END CON #1302801

Cold Pipe Insulation Spray



Features:

- Durable, flexible and water resistant
- Durable finish may be painted or primed
- Water resistant coating prevents condensation and dripping
- Repairs wrap around pipe insulation, prolonging life
- Can be used indoors and outdoors

Picture Coming Soon

Description:

END CON is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard-to-reach areas. Expanding spray conforms to irregularly shaped surfaces.

Applications:

- Cold Water Pipes
- Valves and Fittings
- Metal Gutters
- Refrigeration Lines
- Condenser Lines
- Water Tanks
- Air Conditioning Lines
- Refrigeration Trucks

Product Characteristics:

Appearance:	Clear, colorless to slight tint spray.
Odor:	Alcohol
Viscosity:	Not Determined
Evaporation Rate:	Not Determined
Vapor Pressure:	Not Determined
Solubility(ies):	Miscible.
Relative Density (H2O=1):	0.81 @ 77 °F (25 °C).
Flash Point:	Not Determined
pH:	Not Applicable
Storage:	Store in a cool, dry area. Protect from sunlight. Store in a well-ventilated area. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks, open flames or hot surfaces. No smoking.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, Ltd. Qty.
Class:	2.1
Packing Group:	Not Available

Directions:

SHAKE WELL BEFORE USE. Remove dust and loose dirt from surface to be sprayed by wiping with clean, dry cloth. Cover surfaces under area to be treated to avoid overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10" from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

VOC Compliant - Yes