



FLOOR CARE GUIDE

FOR REPAIRS, PATCHES & COATINGS





FLOOR CARE GUIDE -

REPAIRS

W/AGGREGATE

SELF-LEVELING*

RAPID FIX

CRACK FILLER

- 2 Part epoxy
- 1 gallon pre-measured kit
- Crystal clear - no color
- Indoors only
- Can be used as floor leveler & 1st coat of Dura Seal

FLOOR FIX

- 2 Part epoxy
- A & B must all be mixed.
- Amber/translucent color
- Indoors only

C-JOINT

- 2 Part epoxy
- Flexible with rigid surface
- 2 GL kit, 1 GL each A & B
- Mix equal parts A & B as needed & reseal can
- Gray & Clear (translucent, milky white)
- Indoors only
- NOT recommended for large surface area patches

C-JOINT CARTRIDGES

- 2 Part epoxy in tubes
- Flexible with rigid surface. Excellent for small cracks & expansion joints
- 1 unit with A & B tubes enclosed
- Use with C-Joint Gun
- Clear only (translucent, milky white)
- Indoors only

***Any repair deep enough to require more than one kit should use a product with aggregate for strength.**

W/AGGREGATE

RAPID FIX

SURE PATCH

- 3 Part epoxy, A & B in pail with aggregate
- Available in 2 sizes.
- A & B must all be mixed. Then aggregate.
- Various consistency depending on user needs, from pourable slurry to thick mortar
- Gray color
- Indoors & outdoor use.

EPOXY WATERPROOF PATCHING COMPOUND

- 2 Part epoxy
- 2 GL kit, 1 GL each A & B
- Mortar type mix with aggregate pre mixed
- Mix equal parts A & B as needed & reseal can
- Vertical/Horizontal applications
- Gray color
- Indoors only

RAPID SET

- 3 Part epoxy, A & B in pail with aggregate
- Low temperature - Can be used as low as 30*
- A & B must all be mixed. Then aggregate.
- Very short potable life, must be used quickly
- Gray color
- Indoors only

RAPID RESIN REPAIR (Non-Stock)

- 3 Part epoxy, A & B in pail with aggregate
- A & B must all be mixed. Then aggregate.
- Very short potable life, use quickly
- Designed for extremely fast repairs
- Indoor & outdoor use
- Gray color
- DOT rated

FOR REPAIRS, PATCHES & COATINGS

COATINGS

DURA SEAL

- Concrete sealer
- Indoor only
- Stock colors are gray & clear. Available in a variety of colors.
- Dries to a high shine
- Chemical resistant
- Highly resistant to abrasion
- 46% solid
- Two coats are recommended to achieve a 6 mil thickness.
- 225 sq ft coverage per GL & 250 for the second coat.
- Pot life is 90 minutes
- Available in 1 GL or 5 GL pre-measured kits

100% SOLID EPOXY

- Concrete sealer
- Indoor only
- Stock colors, gray & clear but available in a variety of colors.
- Dries to a high shine
- Chemical resistant
- Highly resistant to abrasion
- 100% solid epoxy (Harder product than Dura Seal)
- One coat dries to 16 to 18 mils
- 90-100 sq ft coverage per GL, because it's thicker, the coverage is less than Dura Seal
- Pot life is 20 to 30 minutes, you have to work fast
- Strongly suggested to use a primer
- Available in 3 GL pre-measured kits

SURFACE SEAL

- For use on concrete, metal, masonry, fiberglass, wood, steel & plaster. Can be used vertically such as on drywall's drainwell, cement blocks
- Indoors & outdoor
- Dries to a high gloss, if used outdoors, the UV will dull the gloss.
- Chemical resistant
- Highly resistant to heavy traffic
- Dries to 1.5 to 2 mils
- 500 to 550 sq ft coverage per 2 GL kit
- Pot life is 8 hours
- Available in 2 GL pre-measured kits

ANTISKIDS

DURA SEAL W/ANTI-SKID

- Concrete sealer with non slip finish
- Use exactly as Dura Seal above but with various options to give traction.
- Add 8 oz. of material to each GL of Dura Seal before applying
- OPTIONS: Fine (ground glass), Medium & Course (both silica)
- Sold in 2 quantities: 8 oz. or 40 oz. of each option

FIRM GRIP II

- 2 part epoxy non skid coating
- A & B must all be mixed. Then aggregate.
- Brush or roll on one thick coat, minimum 12 mils
- Distribute grit aggregate on surface immediately
- Smooth bead aggregate available to mix into epoxy
- One kit covers approx. 130 sq. ft. @ 12 mils thickness
- Available in black or yellow
- Can be used on concrete, steel & wood
- Use indoors or outdoors

TRED SAFE (available special order)

- One part acrylic latex non skid coating
- 5 GL pail, aggregate mixed in
- Available in a variety of colors
- Paint on clean dry surface. Recoat as needed
- Not to be used where under water
- Best for foot traffic. Tire traffic requires more recoating
- Indoor use only

TRED SAFE HD

- 2 part epoxy non slip coating
- A & B must all be mixed.
- Aggregate is already mixed into mortar
- Use indoors or outdoors.
- Can be used on concrete, metal & wood
- Extremely effective in wet or dry conditions
- Apply with phenolic roller (withstands moisture & has no glue)

FIRM GRIP II-AGGREGATE

- Aggregate for broadcasting over epoxy
- 25 lb. pail
- Black silicon Carbide. Extremely durable
- 2 sizes of grit: #14-average traction or #8-very coarse
- Clear beads also available for mixing into epoxy

SCAN FOR MORE INFO





**For more information on product & purchasing,
send an email to contactus@procheminc.com**

**Pro Chem, Inc.
1475 Bluegrass Lakes Parkway,
Alpharetta, GA 30004
Procheminc.com
1-800-241-8180**